

COTS Micro-D Back-To-Back Cables Metal Shell



Micro-D Connectors are available as back-to-back complete assemblies. These cables can be used as connector savers or gender changers. These assemblies are wired point-to-point (contact 1 to contact 1, etc.).

- #26 AWG Wire Accomodation
- Environmentally Sealed
- 9 Through 100 Contacts

Note: To specify a back-to-back cable with jackposts on one end and jackscrews on the other, order less hardware (option B) and order hardware separately.

RELATED INFORMATION

Performance Specifications	IBC*
Materials and Finishes	IBC*
Contact Arrangements	7-8
Panel Cutouts, Mounting Dimensions	9
Standard Dimensions	10
Jacking Hardware Kits	C-3,4

* Available on the Inside Back Cover Fold-Out

HOW TO ORDER

Conn. Series	Shell Plating Table III*	Insert Material Table I*	No. of Contacts	Connector Type	Wire Gage (AWG)	Wire Type Table IV*	Wire Color Table IV*	Overall Length	Hardware Table V*
MWDM	1 – Cadmium	L – LCP (Liquid Crystal Polymer)	9	GP – Pin to Pin Connector	6 - 26	E - Std K - Mil J - Space	1 - White	Length in 1 Inch Increments (2 inch minimum)	B P L K M S M1 S1 F R
	2 – Nickel		15						
	4 – Black Anodize		21						
	5 – Gold		25						
	6 – Chem Film		31	GS – Socket to Socket Connector					
	37								
	51	CS - Pin to Socket Connector							
	100								
Sample Part Number: MWDM	5	L	31	GS	6	K	1	2	B

* SEE INSIDE BACK COVER FOLD-OUT FOR COMPLETE INFORMATION