

UK 10-DREHSI



for cartridge fuse inserts

Terminal width 12

(IEC)	rigid	flexible		I	U
[mm ²]	solid	stranded	AWG	[A]	[V]

DIN VDE 0611

as disconnect terminal 0.5-16 0.5-16 20-6 10 800

with fuse 0.5-16 0.5-16 20-6 2) 2)



Description	Light indicator Voltage [V AC/DC]	Current [mA]	Type	Order No.	Pcs. Pkt.
Fuse terminal block , for mounting on  or  for cartridge fuse inserts, 5 x 20, 5 x 25, and 6.3 x 32 mm, with or without indicator pin			UK 10-DREHSI (5 x 20)	30 05 10 9	50
			UK 10-DREHSI/K (5 x 25)	30 05 68 8	50
			UK 10-DREHSI (6,3 x 32)	30 05 50 7	50
Fuse terminal block¹⁾ , as above, however, with light indicator for:	5 - 15	0.5 - 2.5	UK 10-DREHSELED 12 (5 x 20)	30 05 11 2	50
			UK 10-DREHSELED 12 (6,3 x 32)	30 05 63 3	50
Fuse terminal block¹⁾ , as above, however, with light indicator for:	15 - 30	1 - 2.5	UK 10-DREHSELED 24 (5 x 20)	30 05 13 8	50
			UK 10-DREHSELED 24 (6,3 x 32)	30 05 64 6	50
Fuse terminal block¹⁾ , as above, however, with light indicator for:	30 - 60	0.8 - 2	UK 10-DREHSELED 60 (5 x 20)	30 05 15 4	50
			UK 10-DREHSELED 60 (6,3 x 32)	30 05 65 9	50
Fuse terminal block¹⁾ , as above, however, with light indicator for:	110 - 250	0.5 - 1.1	UK 10-DREHSILA 250 (5 x 20)	30 05 17 0	50
			UK 10-DREHSILA 250 (6,3 x 32)	30 05 66 2	50

Accessories

(1) **Fixed bridge**, for cross connections in the terminal center, screw heads with insulated collar, 10-position, divisible, with 10 screws

**FBI 10-12**I_{max.}: 63 A**02 03 45 4**

10

(2) **Insertion bridge**, 10-position, divisible, insulated spine

**EB 10-12**I_{max.}: 63 A**30 06 13 7**

10

(3) **Test plug socket**, for test connection with test plug PS

**PSB 4/7/6****03 03 29 9**

100

(4) **Test plug socket, insulated**, only used with FBI, for test connection with test plug PS

**PSBJ 4/15/6:...** (see [info](#))

(5) **Zack strip**, 10-section, white**ZB 8** (see [info](#))(6) **Screwdriver****SZS 1,0 x 4,0****12 05 06 6**

10

Technical data**Dimensions**

Width / length	[mm]	12 / 62
Height (NS 35:7.5 / NS 35:15 / NS 32)	[mm]	59 / 66.5 / 64

Technical data in accordance with IEC/ DIN VDE

Fuse type / fuse dimensions	– / [mm]	G / 5 x 20 / 5 x 25 / 6.3 x 32
-----------------------------	----------	--------------------------------

Max. power dissipation

at 23 °C acc. to E DIN VDE 0611-6:1995-05	[W]	see info
Max. cross section with insertion bridge (solid / stranded)	[mm ²]	10 / 10
Rated surge voltage / contamination class	[kV] / –	4 / 3
Surge voltage category / insulation material group		III / I

Connection capacity

stranded with ferrule without / with plastic sleeve	[mm ²]	0.5 - 10 / 0.5 - 10
---	--------------------	---------------------

Multi-conductor connection (2 conductors with same cross section)

solid / stranded	[mm ²]	0.5 - 4 / 0.5 - 4
stranded with ferrule without plastic sleeve	[mm ²]	0.5 - 4
stranded with TWIN ferrule with plastic sleeve	[mm ²]	0.5 - 10

Stripping length	[mm]	11
-------------------------	------	----

Internal cylindrical gage (IEC 947-1:1988)		B 6
---	--	-----

Thread / torque	– / [Nm]	M 4 / 1.5 - 1.8
------------------------	----------	-----------------

Insulation material		PA
----------------------------	--	----

Inflammability class acc. to UL 94		V2
------------------------------------	--	----

Temperature indices RTI / Ti		130 / 120
------------------------------	--	-----------

Approval data (UL and CSA)

Nom. voltage / nom. current / conduc.sizes	UL: [V] / [A] / AWG	300 / 20 / 24 - 6
--	---------------------	-------------------

	CSA: [V] / [A] / AWG	300 / 20 / 22 - 6
--	----------------------	-------------------

¹⁾ Light indicator versions for other voltage ranges available on request.

²⁾ see [table](#) (the current is determined by the fuse, the voltage by the light indicator).