

DLK 2,5-PE

Terminal width 6.2

(IEC)	rigid	flexible		I	U
[mm ²]	solid	stranded	AWG	[A]	[V]
DIN VDE 0611	0.2-4	0.2-2.5	24-12	26	400



Description	color	Type	Order No.	Pcs. Pkt.
Three-conductor terminal block, with universal foot, for mounting on 	gray	DLK 2,5-PE	30 11 04 1	50

Accessories

(1) **Fixed bridge**, for cross connections in the terminal center, screw heads with insulating collars, 10-position, divisible, with 10 screws

**FBI 10-6** $I_{\max.}$: 26 A**02 03 25 0**

10

(3) **Zack strip**, 10-section, white

ZB 6 (see [info](#))

(4) **Screwdriver**

SZS 0,6 x 3,5**12 05 05 3**

10

Technical data**Dimensions**

Width / length	[mm]	6.2 / 83
Height (NS 35:7.5 / NS 35:15)	[mm]	70 / 77.5

Technical data in accordance with IEC/ DIN VDE

Maximum load current / cross section	[A] / [mm ²]	24 / 2.5
Rated surge voltage / contamination class	[kV] / –	6 / 3
Surge voltage category / insulation material group	– / –	III / I

Connection capacity

stranded with ferrule without / with plastic sleeve	[mm ²]	0.25 - 2.5 / 0.25- 2.5
---	--------------------	------------------------

Multi-conductor connection (2 conductors with same cross section)

solid / stranded	[mm ²]	0.2 - 1 / 0.2 - 1
stranded with ferrule without plastic sleeve	[mm ²]	0.25 - 1
stranded with TWIN ferrule with plastic sleeve	[mm ²]	0.5 - 1

Stripping length	[mm]	8
-------------------------	------	---

Block diagram

