

DOKD 1,5-TG

Base terminal block
Terminal width 6.2

	(IEC)	rigid	flexible		I	U
	[mm ²]	solid	stranded	AWG	[A]	[V]
Connection data		0.2-4	0.2-2.5	24-12	26	250
Disconnect level		0.2-4	0.2-2.5	24-12	16*	250*

* Current and voltage are determined by the component used.



Description	Type	Order No.	Pcs. Pkt.
Terminal block, for routing on	DOKD 1,5-TG	30 11 05 4	50

Accessories

(2) Insertion bridge , for middle and bottom level, fully insulated	gray	10-pos.		EB 10-DIK GY	$I_{max.} : 26 \text{ A}$	27 15 93 7	10
	red	10-pos.		EB 10-DIK RD	26 A	27 16 77 4	10
	blue	10-pos.		EB 10-DIK BU	26 A	27 16 68 0	10
divisible, insulated spine	blue	80-pos.		EB 80-DIK BU	26 A	27 15 94 0	5
	red	80-pos.		EB 80-DIK RD	26 A	27 15 95 3	5
	white	80-pos.		EB 80-DIK WH	26 A	27 15 78 8	5
(3) Partition plate , for visual and electrical separation of terminal groups, 2 mm thick				ATP-DIKD 1,5		14 13 28 5	50
(4) Zack strip , 10-section, white				ZB 6 (see info)			
(5) Screwdriver				SZS 0,6 x 3,5		12 05 05 3	10

Technical data**Dimensions**

Width / length	[mm]	6.2 / 63
Height (NS 35:7.5 / NS 35:15)	[mm]	54.5 / 62

Technical data in accordance with IEC/ DIN VDE

Maximum load current / cross section	[A] / [mm ²]	26 / 2.5
Max. cross section with insertion bridge (solid / stranded)	[mm ²]	4 / 2.5
Rated surge voltage / contamination class	[kV] / –	4 / 3
Surge voltage category / insulation material	– / –	III / I

Surge voltage category / insulation material group

Connection capacitystranded with ferrule without / with plastic sleeve [mm²] 0.25 - 2.5 / 0.25- 2.5**Multi-conductor connection (2 conductors with same cross section)**solid / stranded [mm²] 0.2 - 1 / 0.2 - 1stranded with ferrule without plastic sleeve [mm²] 0.25 - 1stranded with TWIN ferrule with plastic sleeve [mm²] 0.5 - 1**Stripping length** [mm] 8**Internal cylindrical gage (IEC 947-1:1988) level 1 / 2 / 3** A 3**Thread** M 3**Torque** [Nm] 0.6 - 0.8**Insulation material** PA

Inflammability class acc. to UL 94 V2

Temperature indices RTI / Ti 125 / 100

Approval data (UL and CSA)

Nom. voltage / nom. current / conductor sizes UL: [V] / [A] / AWG 300 / 15 / 30 - 14

CSA: [V] / [A] / AWG 300 / 15 / 28 - 14

Note:Fuse, component and disconnect plugs, see [info 1](#)/[info 2](#).**Application**