

UK-SI



Complete with fuse plug

Terminal width 8.2

(IEC)	rigid	flexible		I	U
[mm ²]	solid	stranded	AWG	[A]	[V]
DIN VDE 0611	0.2-4	0,2-4	24-12	6.3 *	250 *

* The current and voltage are determined by the fuse.



Description	Light indicator Voltage [V AC/DC]	Current [mA]	Color	Type	Order No.	Pcs. Pkt.
Fuse terminal block , for mounting on □ or □ for 5 x 20, 5 x 25 mm cartridge fuse inserts			black	UK-SI	31 18 01 2	50
			blue	UK-SI BU	31 18 09 6	50

Accessories

(2) Insertion bridge , fully insulated,	2-pos.		EBS 2-8	I _{max.} : 32 A	31 18 15 1	100
fully insulated,	3-pos.		EBS 3-8	32 A	31 18 14 8	100
divisible, insulated spine,	10-pos.		EBS 10-8	32 A	31 18 13 5	10
(3) Zack strip , 10-section, white			ZB 8 (see info)			
(4) Screwdriver			SZS 0,6 x 3,5		12 05 05 3	10

Technical data

Dimensions

Width / length	[mm]	8.2 / 59.5
Height (NS 35:7.5 / NS 35:15 / NS 32)	[mm]	58 / 65.5 / 63

Technical data in accordance with IEC/ DIN VDE

Fuse type / fuse dimensions	– / [mm]	G / 5 x 20 / 5 x 25
-----------------------------	----------	---------------------

Max. power dissipation

at 23 °C acc. to E DIN VDE 0611-6:1995-05	[W]	see info
Max. cross section with insertion bridge (solid / stranded)	[mm ²]	4 / 4
Rated surge voltage / contamination class	[kV] / –	4 / 3
Surge voltage category / insulation material group		III / I

Connection capacity

stranded with ferrule without / with plastic	[mm ²]	0.25 - 4 / 0.25 - 4
--	--------------------	---------------------

sleeve

[mm²]**Multi-conductor connection (2 conductors with same cross section)**solid / stranded [mm²] 0.2 - 1.5 / 0.2 - 1.5stranded with ferrule without plastic sleeve [mm²] 0.25 - 1.5stranded with TWIN ferrule with plastic sleeve [mm²] 0.5 - 2.5**Stripping length** [mm] 9**Internal cylindrical gage (IEC 947-1:1988)** A 4**Thread / torque** – / [Nm] M 3 / 0.6 - 0.8**Insulation material** PA

Inflammability class acc. to UL 94 V2

UK-SI

UK-SI BU

Temperature indices RTI / Ti

130 / 120

125 / 100

Approval data (UL and CSA)

Nom. voltage / nom. current / CSA: [V] / [A] / AWG 250 / 10 / 24 - 14

1) see [table](#)**Block diagram**