

DLK 4-PE 


Bridgeable




Terminal width 6.2

(IEC)	rigid	flexible		I	U
[mm ²]	solid	stranded	AWG	[A]	[V]
DIN VDE 0611	0.2-6	0.2-4	24-10	34	400



Description	Color	Type	Order No.	Pcs. Pkt.
Three-conductor terminal block, with universal foot for mounting on 	gray	DLK 4-PE	30 11 99 9	50

Accessories

(1) Fixed bridge , for cross connections in the terminal center, screw heads with insulating collar, 10-position, divisible, with 10 screws		FBI 10-6	I _{max.} : 30 A	02 03 25 0	10
(3) Zack strip , 10-section, white		ZB 6 (see info)			
(4) Screwdriver		SZS 0,6 x 3,5		12 05 05 3	10

Technical data**Dimensions**

Width / length	[mm]	6.2 / 103.5
Height (NS 35:7.5 / NS 35:15)	[mm]	86.5 / 94

Technical data in accordance with IEC/ DIN VDE

Maximum load current / cross section	[A] / [mm ²]	34 / 4
Max. cross section with insertion bridge (solid / stranded)	[mm ²]	6 / 3
Rated surge voltage / contamination class	[kV] / –	6 / 3
Surge voltage category / insulation material group	– / –	III / I

Connection capacity

stranded with ferrule without / with plastic sleeve	[mm ²]	0.25 - 4 / 0.25- 4
---	--------------------	--------------------

Multi-conductor connection (2 conductors with same cross section)

solid / stranded	[mm ²]	0.25 - 4 / 0.25 - 2,5
stranded with ferrule without plastic sleeve	[mm ²]	0.25 - 1.5

stranded with TWIN ferrule with plastic sleeve	[mm ²]	0.5 - 1.5
Stripping length	[mm]	8
Internal cylindrical gage (IEC 60 947-1) level 1 / 2 / 3		A 3
Thread		M 3
Torque	[Nm]	0.5 - 0.6
Insulation material		PA
Inflammability class acc. to UL 94		V0
Approval data (UL and CSA)		
Nom. voltage / nom. current / conductor sizes	UL: [V] / [A] / AWG	600 / 30 / 30 - 10
	CSA: [V] / [A] / AWG	600 / 30 / 30 - 10