

BES 6

Diode 1N 4007
 Reverse voltage: 1300 V
 Maximum continuous current: 1 A
 Dimensions see below

Description	Light indicator: Voltage [V AC/DC]	Current [mA]	Type	Order No.	Pcs. Pkt.
Component plug , complete, for connection of components between 2 neighboring feed-through terminal blocks			BES 6	28 02 54 9	10
Component plug , as above, however, equipped with diode 1N 4007			BES 6-1N4007	28 02 55 2	10
Component plug , with light indicator	15-30 DC	2.5-7.5	BES 6-LA 24	28 02 56 5	10
Component plug , with light indicator	110-250 AC/DC	0.5-1	BES 6-LA 230	28 02 57 8	10

Technical data

Insulation material	PA
Inflammability class acc. to UL 94	V2
Temperature indices RTI / Ti	125 / 100

Data of the components to be soldered

Length including connection wires	10 mm
Width or diameter	6 mm
Diameter of the connection wires	1.3 mm
Max. power dissipation at 25 °C	1 W

Height dimensions a with BES 6 inserted:

Type	Dim. a [mm]	mounting rail
MBK 5	64	NS 15
MBK 5/E	67	NS 15
MBK 5/E-Z	68	NS 15
UK 5 N	75	NS 35/7,5
UKB 4	75	NS 35/7,5
UKK 5	92	NS 35/7,5
UKKB 5	92	NS 35/7,5
UVKB 4	76	NS 35/7,5

Dimensional drawing

