

UKK 5-MTK-P/P







Terminal width 6.2

(IEC)	rigid	flexible	I	U	
[mm ²]	solid	stranded	AWG	[A]	[V]



Connection data

Upper level	0.2-4	0.2-4	24-12	12	400
Lower level	0.2-4	0.2-4	24-12	26	400



Description	Light indicator: Voltage [V]	Current [mA]	Type	Order No.	Pcs. Pkt.
Knife disconnect terminal block , for mounting on  or  , with test socket screw	gray		UKK 5-MTK-P/P	28 00 00 4	50
Double level terminal block , for mounting on  or  , with disconnect knife and LED	24 DC	6.0	UKK 5-MTK-P/P-LA 24 RD/O-U	28 00 02 0	50
	48 DC	5.7	UKK 5-MTK-P/P-LA 48 RD/O-U	28 00 03 3	50
	60 D	5.5	UKK 5-MTK-P/P-LA 60 RD/O-U	28 00 04 6	50
Double level terminal block , as above, however, with two through contacts, without LED	gray		UKK 5-MTKD-P/P	28 00 01 7	50

Accessories

(2) Fixed bridge , for cross connections in the terminal center, screw heads with insulating collar, 10-position, divisible, with 10 screws		FBI 10-6	$I_{max.}: 32 \text{ A}$	02 03 25 0	10
(4) Isolator bridge bar , 10-position, divisible, with 10 screws, for switchable branches with		ISSBI 10-6	$I_{max.}: 18 \text{ A}$	03 01 50 5	10
(5) Bridge bar isolator IS-K 4 as distance piece		IS-K 4		13 02 33 8	100
(7) Zack strip , 10-section, white		ZB 6 (see info)			
(8) Screwdriver		SZG 0,6 x 3,5		12 05 12 1	10

Technical data**Dimensions**

Width / length / end cover width	[mm]	6.2 / 80 / –
Height (NS 35:7.5 / NS 35:15 / NS 32)	[mm]	68 / 76 / 73

Technical data in accordance with IEC/ DIN VDE

UKK 5-MTK... // UKK 5-MTKD...

Maximum load current / cross section	[A] / [mm ²]	26 / 4 // 12 / 4 ²)
Rated surge voltage / contamination class	[kV] / –	6 / 3
Surge voltage category / insulation material group	– / –	III / I

Connection capacity

stranded with ferrule without / with plastic sleeve	[mm ²]	0.25 - 4 / 0.25 - 2.5
---	--------------------	-----------------------

Multi-conductor connection (2 conductors with same cross section)

solid / stranded	[mm ²]	0.2 - 1.5 / 0.2 - 2.5
stranded with ferrule without plastic sleeve	[mm ²]	0.25 - 1.5
stranded with TWIN ferrule with plastic sleeve	[mm ²]	0.5 - 2.5

Stripping length	[mm]	8
-------------------------	------	---

Internal cylindrical gage (IEC 947-1:1988), level 1/2		A 3 / A 4
--	--	-----------

Thread		M 3
---------------	--	-----

Torque	[Nm]	0.6 - 0.8
---------------	------	-----------

Operating cycles of the disconnect knife		100
---	--	-----

Insulation material		PA
---------------------	--	----

Inflammability class acc. to UL 94		V2
------------------------------------	--	----

Temperature indices RTI / Ti		125 / 100
------------------------------	--	-----------

Approval data (UL and CSA)

Nom. voltage / nom. current / conduc. sizes	UL: [V] / [A] / AWG	300 / 15 / 26 - 12
---	---------------------	--------------------

	CSA: [V] / [A] / AWG	300 / 15 / 22 - 12
--	----------------------	--------------------

²) Upper level