

# 4 mm dia. SAFETY SERIES

## ACCESSORIES


- **WIRE GRIPS** *Compatibles with all 4 mm dia. patch cords and banana plugs .*

### WITH FLEXIBLE ROD

The flexible and thin rod allows testing of difficult to access contact points in dense circuitry.

#### CHARACTERISTICS

- Operating voltage : 1 000 V rms
- Current rating max : 2.5 A (at 20°C)
- Material *contact hook* : spring wire in stainless steel
- body* : thermoplastic



- ▶ **Packaging : 10 pieces of the same part number.**

Part number	
R 999 720 600 / Black R 999 721 600 / Red	


### ● SAFETY TEST PROBE

The extra thin probe can make contact through coatings and some types of insulation as well as enabling PCB measurements.

Fitted with a rear-mounted 4 mm dia. socket, it can be used with **BM** (p 26 to p 29) and **BMS** (p 12 to p 16) patch cords. With the safety male/male adaptor (p 19), this probe can be connected to a measurement instrument.

#### CHARACTERISTICS

- Operating voltage max : 1 500 V rms
- Material *tip* : steel
- body* : thermoplastic



- ▶ **Packaging : 10 pieces of the same part number.**

Part number	
R 941 850 600 / Black R 941 851 600 / Red	