

2 mm dia. SERIES

ACCESSORIES

PIN OUTLET

| Part number | Dimensions (12 mm between axes) |
|---|---|
| <p>R 929 992 000* / Blue</p> <p>R 929 992 001* / Red</p> <p>R 929 992 002* / Green</p> <p>R 929 992 003* / Black</p> <p>R 929 992 004* / Yellow</p> | <p><i>Drilling jig : R 282 906 *</i></p> <p><i>Panel piercing dimension: (thickness: 2 mm maximum) 20 holes 5 dia. (contacts) – 5 holes 3 dia. (fixing)</i></p> |

SOLDER OUTLET

| Part number | Dimensions (6 mm between axes) |
|---|---|
| <p>R 929 993 000* / Blue</p> <p>R 929 993 001* / Red</p> <p>R 929 993 002* / Green</p> <p>R 929 993 003* / Black</p> <p>R 929 993 004* / Yellow</p> | <p><i>Drilling jig : R 282 690 *</i></p> <p><i>Panel piercing dimension: (thickness: 2 mm maximum) 20 holes 5 dia. (contacts) – 5 holes 3 dia. (fixing)</i></p> |

PIN OUTLET

| Part number | Dimensions (6 mm between axes) |
|---|---|
| <p>R 929 994 000* / Blue</p> <p>R 929 994 001* / Red</p> <p>R 929 994 002* / Green</p> <p>R 929 994 003* / Black</p> <p>R 929 994 004* / Yellow</p> | <p><i>Drilling jig : R 282 690 *</i></p> <p><i>Panel piercing dimension: (thickness: 2 mm maximum) 20 holes 5 dia. (contacts) – 5 holes 3 dia. (fixing)</i></p> |

NOTA : The size of the contact blocks makes it possible to assemble them side by side while maintaining a distance of 6 mm between axes in all directions.