



Omnimate Range - Pitch 3.50 mm



Pin headers SL-SMT 3.5/180G

new



Technical Data		VDE	UL	CSA
Rated voltage	V	160*	300	300
Rated current	A	13	10	10

*Overvoltage category III / Pollution severity 3

Additional technical data see page 211

Technical Data		VDE	UL	CSA
Rated voltage	V	160*	300	300
Rated current	A	13	10	10

*Overvoltage category III / Pollution severity 3

Additional technical data see page 211

Technical Data		VDE	UL	CSA
Rated voltage	V	160*	300	300
Rated current	A	13	10	10

*Overvoltage category III / Pollution severity 3

Additional technical data see page 211

Solder pin length 1.5 mm

Tape-on-Reel

Colour

Tape width

Poles	Type	56 mm	32 mm	Qty.
2	SL-SMT 3.5/2/180G	1752984001	1752984002	200
3	SL-SMT 3.5/3/180G	1752994001	1752994002	200
4	SL-SMT 3.5/4/180G	1753004001	1753004002	200
5	SL-SMT 3.5/5/180G	1753014001	1753014002	200
6	SL-SMT 3.5/6/180G	1753024001	–	200
7	SL-SMT 3.5/7/180G	1753034001	–	200
8	SL-SMT 3.5/8/180G	1753044001	–	200
9	SL-SMT 3.5/9/180G	1753054001	–	200
10	SL-SMT 3.5/10/180G	1753064001	–	200
11	SL-SMT 3.5/11/180G	1753074001	–	200

For detailed product and application information for SMT see chapter "Other Applications" page 180-188.

Accessories	Page
Fixing	–
Marking	196
Coding	199
Miscellaneous	–

Solder pin length 1.5 mm

Tray

Colour

Poles	Type	Cat. No.	Qty.
2	SL-SMT 3.5/2/180G	1752983001	108
3	SL-SMT 3.5/3/180G	1752993001	108
4	SL-SMT 3.5/4/180G	1753003001	96
5	SL-SMT 3.5/5/180G	1753013001	78
6	SL-SMT 3.5/6/180G	1753023001	66
7	SL-SMT 3.5/7/180G	1753033001	60
8	SL-SMT 3.5/8/180G	1753043001	54
9	SL-SMT 3.5/9/180G	1753053001	48
10	SL-SMT 3.5/10/180G	1753063001	42
11	SL-SMT 3.5/11/180G	1753073001	36
12	SL-SMT 3.5/12/180G	1753083001	36
13	SL-SMT 3.5/13/180G	1753093001	30
14	SL-SMT 3.5/14/180G	1753103001	30
15	SL-SMT 3.5/15/180G	1753113001	30
16	SL-SMT 3.5/16/180G	1753123001	24
17	SL-SMT 3.5/17/180G	1753133001	24
18	SL-SMT 3.5/18/180G	1753143001	24
19	SL-SMT 3.5/19/180G	1753153001	24
20	SL-SMT 3.5/20/180G	1753163001	18
21	SL-SMT 3.5/21/180G	1753173001	18
22	SL-SMT 3.5/22/180G	1753183001	18
23	SL-SMT 3.5/23/180G	1753193001	18
24	SL-SMT 3.5/24/180G	1753203001	18

For detailed product and application information for SMT see chapter "Other Applications" page 180-188.

Accessories	Page
Fixing	–
Marking	196
Coding	199
Miscellaneous	–

Solder pin length 1.5 mm

Standard Box

Colour

Poles	Type	Cat. No.	Qty.
2	SL-SMT 3.5/2/180G	1752982001	100
3	SL-SMT 3.5/3/180G	1752992001	100
4	SL-SMT 3.5/4/180G	1753002001	100
5	SL-SMT 3.5/5/180G	1753012001	50
6	SL-SMT 3.5/6/180G	1753022001	50
7	SL-SMT 3.5/7/180G	1753032001	50
8	SL-SMT 3.5/8/180G	1753042001	50
9	SL-SMT 3.5/9/180G	1753052001	50
10	SL-SMT 3.5/10/180G	1753062001	50
11	SL-SMT 3.5/11/180G	1753072001	50
12	SL-SMT 3.5/12/180G	1753082001	50
13	SL-SMT 3.5/13/180G	1753092001	50
14	SL-SMT 3.5/14/180G	1753102001	50
15	SL-SMT 3.5/15/180G	1753112001	50
16	SL-SMT 3.5/16/180G	1753122001	50
17	SL-SMT 3.5/17/180G	1753132001	20
18	SL-SMT 3.5/18/180G	1753142001	20
19	SL-SMT 3.5/19/180G	1753152001	20
20	SL-SMT 3.5/20/180G	1753162001	20
21	SL-SMT 3.5/21/180G	1753172001	20
22	SL-SMT 3.5/22/180G	1753182001	20
23	SL-SMT 3.5/23/180G	1753192001	20
24	SL-SMT 3.5/24/180G	1753202001	20

For detailed product and application information for SMT see chapter "Other Applications" page 180-188.

Accessories	Page
Fixing	–
Marking	196
Coding	199
Miscellaneous	–