





Pin headers SLD 3.5V/180





$$L = (n/2 - 1) \times 3.5$$

Technical Data		VDE	UL	CSA
Rated voltage	V	160*	300	300
Rated current	A	8	10	10

*Overvoltage category III / Pollution severity 3
Additional technical data see page 212

Pin headers SLD 3.5V/180G






$$L = (n/2 - 1) \times 3.5$$

Technical Data		VDE	UL	CSA
Rated voltage	V	160*	300	300
Rated current	A	8	10	10

*Overvoltage category III / Pollution severity 3
Additional technical data see page 212

Pin headers SLD 3.5V/180F



$$L = (n/2 - 1) \times 3.5$$

Technical Data		VDE	UL	CSA
Rated voltage	V	160*	300	300
Rated current	A	8	10	10

*Overvoltage category III / Pollution severity 3
Additional technical data see page 212

Solder pin length

3.2 mm

4.5 mm

Colour

Poles	Type	Cat. No.	Cat. No.	Qty.
4	SLD 3.5 V/4/180	1640980000	1641490000	50
8	SLD 3.5 V/8/180	1640990000	1641500000	50
12	SLD 3.5 V/12/180	1641000000	1641510000	50
16	SLD 3.5 V/16/180	1641010000	1641520000	20
20	SLD 3.5 V/20/180	1641020000	1641530000	20
24	SLD 3.5 V/24/180	1641030000	1641540000	10
28	SLD 3.5 V/28/180	1641040000	1641550000	10
32	SLD 3.5 V/32/180	1641050000	1641560000	10
36	SLD 3.5 V/36/180	1641060000	1641570000	10
40	SLD 3.5 V/40/180	1641070000	1641580000	10
44	SLD 3.5 V/44/180	1641080000	1641590000	10
48	SLD 3.5 V/48/180	1641090000	1641600000	10

Solder pin length

3.2 mm

4.5 mm

Colour

Poles	Type	Cat. No.	Cat. No.	Qty.
4	SLD 3.5 V/4/180G	1641110000	1641730000	50
8	SLD 3.5 V/8/180G	1641120000	1641740000	50
12	SLD 3.5 V/12/180G	1641130000	1641750000	50
16	SLD 3.5 V/16/180G	1641140000	1641760000	20
20	SLD 3.5 V/20/180G	1641150000	1641770000	20
24	SLD 3.5 V/24/180G	1641160000	1641780000	10
28	SLD 3.5 V/28/180G	1641170000	1641790000	10
32	SLD 3.5 V/32/180G	1641180000	1641800000	10
36	SLD 3.5 V/36/180G	1641190000	1641810000	10
40	SLD 3.5 V/40/180G	1641200000	1641820000	10
44	SLD 3.5 V/44/180G	1641210000	1641830000	10
48	SLD 3.5 V/48/180G	1641220000	1641840000	10

Solder pin length

3.2 mm

4.5 mm

Colour

Poles	Type	Cat. No.	Cat. No.	Qty.
4	SLD 3.5 V/4/180F	1641240000	1641970000	50
8	SLD 3.5 V/8/180F	1641250000	1641980000	50
12	SLD 3.5 V/12/180F	1641260000	1641990000	50
16	SLD 3.5 V/16/180F	1641270000	1642000000	20
20	SLD 3.5 V/20/180F	1641280000	1642010000	20
24	SLD 3.5 V/24/180F	1641290000	1642020000	10
28	SLD 3.5 V/28/180F	1641300000	1642030000	10
32	SLD 3.5 V/32/180F	1641310000	1642040000	10
36	SLD 3.5 V/36/180F	1641320000	1642050000	10
40	SLD 3.5 V/40/180F	1641330000	1642060000	10
44	SLD 3.5 V/44/180F	1641340000	1642070000	10
48	SLD 3.5 V/48/180F	1641350000	1642080000	10

Accessories	Page
Fixing	194
Marking	196
Coding	199
Miscellaneous	-

Accessories	Page
Fixing	194
Marking	196
Coding	199
Miscellaneous	-

Accessories	Page
Fixing	194
Marking	196
Coding	199
Miscellaneous	-