



Direct Mount Terminals

Feed Through

Direct Mount Terminals		ADK 1		ADK 1 F ADK 3 F		MK 2/12		MK 1/3...22	
Feed Through									
Available Options (thickness mm) For Sheet Metal Version		1.5 2.5		1.5 2.5		Part No.		Part No.	
PA		0303860000 0301060000		0476060000 0478660000					
3 pole KrG								0261620000	
12 pole KrG								0261820000	
12 pole PA						0241460000			
22 pole KrG								0301920000	
All types except ADK 1 FT and MK 1/3... internal pin 0.8 x 2.8									
Dimensions									
Width / Length / Height with pins		mm (in.) 6/22/36.5 (.236/.87/1.44)		6/22/36.5 (.236/.87/1.44)		86/15/23 (2.68/.59/.91)		See table below	
Length of solder lug/pin		mm (in.) 8.4 (.33)		8.5/7.5 (.33/.30)		8 (.32)		5 (.20)	
Insulation stripping length		mm (in.) 9 (.35)		11 (.43)		5 (.20)		6 (.24)	
Technical Data									
Rated voltage / rated current / wire size		UL 300 V / 16 A / #22...12 AWG		300 V / 15 A / #26...14 AWG		300 V / 10 A / #24...12 AWG		300 V / 10 A / #24...12 AWG	
		CSA 300 V / 10 A / #26...12 AWG		300 V / 10 A / #22 ...14 AWG		300 V / 10 A / #24...12 AWG		300 V / 10 A / #22...16 AWG	
		VDE 380 VAC / 16 A / 4/1.5 mm²		380 VAC / 20 A / 2.5/1.5 mm²		6 VAC / 20 A / 2.5/1.5 mm²		380 VAC / 20 A / 2.5/1.5 mm²	
Torque		Nm (lb. in.) 0.5 (5.0)		0.9 (8.0)		0.4 (4.0)		0.4 (4.0)	
Clamping screw		M 3 2.5		2.5		2.5		2.5	
End Plate (thickness mm)		Type Part No.		Type Part No.		Dimensions			
		PA AP (3) 0476260000		AP (3) 0476260000				MK 1/3	
		EP		AP (3) 0360000000					
Spacer (thickness mm)									
								