


» Product Return Policy

» Terms & Conditions

» Privacy Policy

Features

- Epoxy mounting saves board space by eliminating mounting holes
- Can be used with either plastic or metal/ceramic BGA packages
- Low cost solution for applications with airflow in a single direction
- Link to thermal epoxies



Width: 25.00

Length: 25.00 Height: 10.00 Base Thickness: 3.30 Fin Thickness: Length 1.65, Width 1.65 # of Fins: Length 5, Width 5 Fin Tip to Tip: 0.00 Finish: Black Anodize

Thermal Performance

Natural Convection: 0.00 (based on a heatsink temperature rise of 75°C above ambient)

21/05/2012

Forced convection: 0.00

based on fully ducted airflow entering at 1.0 m/s (197 LFM).

| Customer Assistance | Popular Products | Our Company | Sign up to receive Aavid news & alerts |
|-----------------------|-----------------------|----------------------------|--|
| Contact Us | Extrusions | About Aavid | |
| Get Design assistance | Board Level | News and Events | email address go |
| Find a Distributor | Liquid Cooling | Management Team | |
| Find a Sales Rep | Heat Pipe Technology | Worldwide Locations | |
| Request a Quote | Heat Sink Accessories | Directions to Headquarters | |
| Placing an Order | Interface Materials | Disclaimer | |
| Terms and Conditions | | Customer Survey | |
| Returns | | Privacy Policy | |

Aavid will lead the electronics thermal management industry worldwide. We will be the first company customers call to enable their thermal designs anywhere in the world. We will respond with extraordinary speed and will provide them with timely and cost-effective solutions because we understand their needs, their industry, and their culture. 2012 Aavid Thermalloy, LLC