

Surface Mount Type TACT Switch(TM) > SKSL Series > SKSLLBE010

Series Common Info

Side Push Half-mount Type with 1.6mm Height (Surface Mount) SKSL Series


| Dimensions | Land Dimensions | Circuit Diagram | Mounting Location of Switch |
| Packing Specifications | Soldering Conditions |

PRINT

Part number		SKSLLBE010
Type	Surface mount	
Operating force	2.2N	
Operating direction	Side push	
Travel	0.15mm	
Operating life (5mA 5V DC)	600,000 cycles	
Initial contact resistance	500mΩ max.	
Series type	Sharp feeling type	
Operating temperature range	-40℃ to +90℃	
Rating (max.)	50mA 12V DC	
Rating (min.)	10μA 1V DC	
Electrical performance	Insulation resistance	100MΩ min. 100V DC for 1min.
	Voltage proof	250V AC for 1 min.
Durability	Vibration	10 to 55 to 10Hz/min., the amplitude is 1.5mm for all the frequencies, in the 3 direction of X, Y and Z for 2 hours respectively
Environmental performance	Cold	-40℃ for 96h
	Dry heat	90℃ for 96h
	Damp heat	60±2℃, 90 to 95%RH for 96h
Minimum order unit (pcs.)	Japan	4,400
	Export	4,400


Dimensions

Unit: mm




Land Dimensions

Unit: mm





Circuit Diagram



Mounting Location of Switch


Unit: mm





Packing Specifications

Taping



Number of packages (pcs.)	1 reel	4,400
	1 case / Japan	44,000
	1 case / export packing	44,000
Tape width (mm)	12	
Export package measurements (mm)	395×395×205	

Soldering Conditions

Condition for Reflow


1. Heating method

Double heating method with infrared heater.

2. Temperature measurement

Thermocouple 0.1 to 0.2 Φ CA(K) or CC(T) at solder joints (copper foil surface). A heat resisting tape should be used for fix measurement.

3. Temperature profile



(1) The above temperature shall be measured of the top of switch. There are cases where PC board's

temperature greatly differs from that of the switch, depending on the material, size, thickness of PC board's and others. Care, should be taken to prevent the switch's surface temperature from exceeding 260℃.

(2) Soldering conditions differ depending on reflow soldering machines. Prior verification of soldering condition is highly recommended.

Manual Soldering

Items	Condition
Soldering temperature	350℃ max.
Duration of soldering	3s max.
Capacity of soldering iron	60W max.

1. Consult with us for availability of TACT switch™ washing.
2. Prevent flux penetration from the top side of the TACT switch™.
3. Switch terminals and a PC board should not be coated with flux prior to soldering.
4. The second soldering should be done after the switch returns to normal temperature.

Notes are common to this series/models.

1. This site catalog shows only outline specifications. When using the products, please obtain formal specifications for supply.
2. Please place purchase orders for taping products per minimum order unit (1 reel or a case).
3. For φ330mm diameter reel requirements, please contact us.
4. Please contact us for automotive use products.

Inquiries about Products

 [Inquiry](#)