





REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A	Initial Release	2016-05-18	Wes	Change Rev.01 To Rev.A




ALTW
CONFIDENTIAL
2016-05-18
R&D DEPT.

ALTW
DCC. DEPT.
CONFIDENTIAL
2016.05.26
ISSUED



White Printing



- Note:
- * Important Dimension To Check.
 - * Waterproof Rate: IP68(Unmated)
In 1 meters water within 24hours.
 - * Working Voltage Rating: AC 300V
 - * Working Current: 20A
 - * Housing: Nylon+GF, Black
 - * Female Pin: Copper Alloy, Gold Plated
 - * Liquid Glue: Black
 - * Nut: Nylon+GF, Black
 - * Gasket: Silicone, Gray
 - * Use Without Waterproof Cap
Panel Thickness Max: 3.6mm
 - * Use With Waterproof Cap
Panel Thickness Max: 2.6mm

UNIT:mm		TITLE X-Lok D Size 20A(For Power) Receptacle Front 3P M Conn F Pin		Amphenol LTW 安費諾亮泰企業股份有限公司		ITEM NO DC-03PMFS-QC800P	DRAWN BY Wes Fan	DATE 2016-05-18
TOLERANCE .X ±0.25 .XX ±0.1 .XXX ±0.05 ANGLES ±1°		SCALE 3:2	SIZE A4	SHEET 1 OF 1		DWG NO DC-03PMFS-QC800P	CHECKED BY Spring Liu	DATE 2016-05-18
REV. A		WC-REV. A.1	QC: Inspection item			CUSTOMER ALTW	APPROVED BY Kevin Hu	DATE 2016-05-18

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.