




REV	ECN NO.	DATE	SIGN	DESCRIPTION
B	LEN-050326	2010/05/18	Kevin Wang	Modify The Dimensions
C	LEN1130368	2011/03/11	Kevin Wang	Modify The Dimensions
D	LEN1180147	2011/08/27	baowei	Add Wire Size



- Note:
- * @@Important Dimensions.
 - * Waterproof Rate: IP67
 - * Male Housing: Nylon+GF, Black
 - * Male Pin: Copper Alloy, Tin Plated
 - * Pin Screws: 1.5mm(HEX), Stainless Steel, For wire assembly, tightened by tool.
 - * Cond. Retainer: Copper Alloy, Tin Plated
 - * O-ring: Silicone, Gray
 - * Flame Class: UL94V-0
 - * One Set Assembled in one PE Bag
 - * 1.5mm Hex Tool for Screws sold separately
 - * Wire Size Range: 14AWG~18AWG

UNIT:mm		TITLE Panel Male Power Conn. 16Amp Screw in Type Pin (Tin Plated)		Amphenol LTW 安費諾亮泰企業股份有限公司		ITEM NO PWG-04PMMB-SC7003	DRAWN BY baowei	DATE 2011/08/27
TOLERANCE .X ±0.25 .XX ±0.1 .XXX ±0.05 ANGLES ±1°		SCALE Free	SHEET 1 OF 1			DWG NO PWG-04PMMB-SC7003	CHECKED BY Micky	DATE 2011/08/27
REV. D		SIZE A4	@@ :Inspection Item		CUSTOMER ALTW		APPROVED BY Victor	DATE 2011/08/27

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.