

Product Line

- Single Pair Ethernet
- ZConnect
- Ceres Connectors
- X-Lok Connectors
- M Series Sensor Connectors
  - MPronto-12
  - MPronto-12 Kit
  - Single Pair Ethernet
  - M8
  - M10.5
  - M12
  - M20
  - M23
  - Distribution Box
  - Guided M8
- FLOS & FLOS+ Connectors
- Power Connectors
- RBL Connectors
- HS-Lok Connectors
- NMEA 2000 Connectors
- RJ Connectors
- USB Connectors
- D-SUB Connectors
- SSL Solution Connectors
- HDMI Connectors
- DVI Connectors
- Fiber Optic Connectors
- Cable Joiner
- FICX Connectors
- Cable Gland - Anti-UV
- Vent
- LED Indicator
- CNC Products

Product Applications

Product Search

Home 〉 Product Line 〉 M Series Sensor Connectors 〉 M12 Bookmark | Share | Print

Share 0 Share

Part Number : M12A-05PFFT-EE0001

Pin : Copper Alloy,Gold Plated

Connector Body : Thermoplastic, UL Recognized.;Zn Alloy ,Nickel Plated

Temperature Range : -55°C~125°C

Download:

Sample 3D model(.stp)

Sample 3D model(.igs)

Add to inquiry list | Check inquiry list | Submit inquiry

Description	Details
Connector	M12 A Code
Connector Gender	Female connector
Current Rating	4A
No. of Contacts	5
Contact Gender	Female pin
Field installable	PCB SMT 180°
Waterproof Rating	Non-Waterproof
Version	0001
Voltage rating	60V AC/DC

* Design and specifications are subject to change without notice.

update: 2021-03-02 00:00:00

Amphenol LTW Unrivaled InterConnects for Harsh Environments

Copyright © 2017 Amphenol LTW TECHNOLOGY CO., LTD. All Rights Reserved.
ADD: 5F-3, No.51, Sec.4, Zhongyang Rd., Tucheng Dist., New Taipei City 236, Taiwan Tel: +886-2-7741-6888
E-mail: sales@ltw-tech.com
Design by TSG Web

TOP