



- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
- 1. BRASS PER QQ-B-626
  - 2. BRASS PER QQ-B-613
  - 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
  - 4. PHOSPHOR BRONZE PER QQ-B-750
  - 5. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
  - 6. TEFLON MIL-P-19468

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
7	HEX NUT			1	HN19-5/8-24X31
6	LOCK WASHER			1	LW-19/16X06
5	GASKET	SILICONE	RED	1	GS-20/16X15
4	BODY			1	N7910-4
3	CONTACT PIN			1	N7900-3
2	INSULATOR		NATURAL	1	N7900-2T-50-B
1	HOUSING			1	N7910-1

DIMENSIONS ARE IN MILLIMETERS			
UNLESS OTHERWISE SPECIFIED	TOLERANCES		
	0.5-6	= ±0.2	
	6-30	= ±0.4	
	30-120	= ±0.6	
	120-315	= ±1	
	315-1000	= ±1.6	
	1000-2000	= ±2.4	
SCALE	2/1	ISSUE	A

PART NO.	N7471A1-NT3G-50	
APPROVED	DATE	10-11-01'
CHECKED	DATE	10-11-01'
DRAWN	DATE	10-11-01'
FILE NO.		

**Amphenol**

TITLE N FEMALE TO FEMALE BULKHEAD ADAPTOR

DRAWING NO. KJ-N7471A1-NT3G-50

ITEM NO.

F  
E  
D  
C  
B  
A

F  
E  
D  
C  
B  
A

1 2 3 4 5 6 7 8

1 2 3 4 5 6 7 8