



NOTES:

1. INSERTION LOSS $\leq 0,5\text{dB}$, MEASURED AGAINST REF. CONNECTOR

2. RETURN LOSS $\geq 45\text{dB}$, MATED CONDITION.

A INFO ON BAG LABEL:

- PART NUMBER AND FACTORY ORDER NUMBER

- INSERTION LOSS AND RETURN LOSS

- UNIQUE SERIAL NUMBER

4. CABLE:

- 9/125/900 μm

- 0,9mm DIAM

- COLOUR: NATURAL

- TIGHT BUFFER

- BUFFER MATERIAL: PVC

PART NUMBER	"L" (METER)
0-1348543-1	1,0 -0/+0,1
0-1348543-2	2,0 -0/+0,1
0-1348543-3	3,0 -0/+0,1
0-1348543-4	4,0 -0/+0,1
0-1348543-5	5,0 -0/+0,1
0-1348543-6	6,0 -0/+0,1
0-1348543-7	7,0 -0/+0,1
0-1348543-8	8,0 -0/+0,1
0-1348543-9	9,0 -0/+0,1
1-1348543-0	10,0 -0/+0,1
1-1348543-1	11,0 -0/+0,2
1-1348543-2	12,0 -0/+0,2
1-1348543-3	13,0 -0/+0,2
1-1348543-4	14,0 -0/+0,2
1-1348543-5	15,0 -0/+0,2
1-1348543-6	16,0 -0/+0,2
1-1348543-7	17,0 -0/+0,2
1-1348543-8	18,0 -0/+0,2
1-1348543-9	19,0 -0/+0,2
2-1348543-0	20,0 -0/+0,2
9-1348543-1	1,5 -0/+0,1

QTY	PART NUMBER	DESCRIPTION	ITEM
1	-	BAG LABEL A	-
1	-	FRONT OUTERSHELL	9
1	-	STRAIN RELIEF BLUE	8
1	-	COMPRESSION SPRING	7
1	-	DUST CAP, MU	6
1	-	COUPLING DEVICE BLUE	5
1	-	REAR OUTERSHELL	4
1	-	CRIMP EYELET	3
1	-	SUBASSY FERRULE/FERRULEHOLDER 125 μm	2
1	-	0,9mm TIGHT BUFFER CABLE	1

SEE TABLE	QTY	PART NUMBER	DESCRIPTION	ITEM
	-	-	CUSTOMER DRAWING	FOR REFERENCE ONLY WILL NOT BE UPDATED
	-	-	© COPYRIGHT 19 - BY AMP HOLLAND B.V.	ALL INTERNATIONAL RIGHTS RESERVED. AMP PRODUCTS MAY BE COVERED BY U.S. AND FOREIGN AND/OR PATENTS PENDING.
	-	-	THIS DRAWING IS UNPUBLISHED	RELEASED FOR PUBLICATION
D		EH02-0129-03	SG RM 16 APR 03	
C		EH-0010-01	EV JE 03 JAN 01	
B		EH-1298-00	SvP RG 22 NOV 00	
A		EH-0340-00	SvP JE 13 MAR 00	
LTR.		REVISION RECORD	DR. CHK. DATE	
DR.: S.V.PUIJENBROEK	CHK.: R.MAARTENS	APP.: R.MAARTENS	DWG.No.	REV.LTR. SHEET
DATE: 13 MAR 00	DATE: 16 APR 03	DATE: 16 APR 03	C-1348543	D 1 of 1



MU/PC PIGTAIL, SM
0,9 mm TIGHT BUFFERED CABLE