




Personal Systems Products
Computer Industry

Wire-to-Board Connectors

1.25mm Pitch Connectors
(AMP SLIM)



Material and Finish:

Tab Contact – Phosphor bronze, pre-tin plated

Tab Housing – Nylon 66, GF20%, UL94V-0 rated, brown (natural)


Material and Finish:

Housing – Nylon 46, GF30%, UL94V-0 rated, color white (natural)

Contacts – Phosphor bronze, plated tin-lead


Solder Peg - Phosphor bronze, plated tin-lead

Tab Contact Type - Part No. 353069-1





Tab Contact:
Wire Range – AWG 32-38
[0.335-0.89mm]
Wire Insulation Range –
0.45-0.93mm


Tab Housing



Receptacle Assemblies



Offset Type



Horizontal Type

Product Facts:

- **Wire-to-Board Connectors**
- **Contacts on 1.25mm centerline**
- **Low profile, compact construction with above-the-board heights of 1.30mm with the offset-mount type and 1.85mm with the horizontal-mount type mating length of 7.3mm**
- **Uses receptacle contacts on board-mounting side and tab contacts on the wire-mount side**
- **Design eliminates pin damage problem**
- **Ensures low insertion force and high reliability by using low-cost tin-plated contacts**
- **Recommended for use in miniature, slim-type equipment such as notebook PCs, LCD monitors, cam coders, etc.**
- **Direct insertion of FPCs is possible in lieu of connector**

No. of Pos.	Part Numbers		
	Tab Housing	Offset Receptacle ¹	Horizontal Receptacle ¹
8	0-353068-8	0-353118-8	0-353119-8
14	1-353068-4	1-353118-4	1-353119-4
20	2-353068-0	2-353118-0	2-353119-0

¹3000 per reel