




**Spade Tongue Terminals, Insulation Support**




**A**  
With Serrations




**B**  
Without Serrations




**C**  
With Serrations



**D**  
Round Tongue



**E**  
Wrap Around Ins. Support



Flanged †

Type	Wire Range		Insul. Size	Stud Size/ Dia.	Stock Thk.	Material and Finish	Dimensions				Part Number
	AWG	mm <sup>2</sup>					W	L	E	C	
E	28-22	0.08-0.4	.035-.045	5	.016	Tin Plated Brass	.240	.545	.435	.215	350502-1
			0.89-1.14		0.41		6.10	13.84	11.05	5.46	
			.035-.045	5	.016	Brass	.240	.545	.435	.215	350502-2
			0.89-1.14		0.41		6.10	13.84	11.05	5.46	
A	26-20	0.12-0.6	.048-.078	6	.020	Tin Plated Brass	.250	.563	.422	.215	60124-2
			1.22-1.98		0.51		6.35	14.30	10.72	5.46	
			.185	6	.020	Tin Plated Brass	.295	.585	.443	.236	63374-1
			4.70		0.51		7.49	14.60	11.25	5.99	
			.048-.078	6	.014	Tin Plated Brass	.250	.590	.442	.215	60445-2
			1.22-1.98		0.36		6.35	14.99	11.23	5.46	
			.048-.078	10	.014	Tin Plated Brass	.300	.590	.442	.215	60501-1
			1.22-1.98		0.36		7.62	14.99	11.23	5.46	
A	24-20	0.2-0.6	.048-.078	8	.115	Brass	.187	.517	.392	.185	42160-1
			1.22-1.98		2.92		4.75	13.13	9.96	4.70	
			.048-.078	8	.115	Tin Plated Brass	.187	.517	.392	.185	42160-2
			1.22-1.98		2.92		4.75	13.13	9.96	4.70	
			.080-.100	8	.020	Tin Plated Brass	.290	.621	.470	.220	41589
			2.03-2.54		0.51		7.37	15.77	11.94	5.59	
			.080-.100	10	.020	Tin Plated Brass	.290	.621	.470	.220	41590
			2.03-2.54		0.51		7.37	15.77	11.94	5.59	
D	24-20	0.2-0.6	.075-.100	4	.020	Tin Plated Brass	.250	.535	.442	.218	61238-1
A	20-16	0.5-1.4	.090-.130	6	.020	Tin Plated Brass	.275	.657	.465	.175	40763
			2.29-3.30		0.51		6.98	16.69	11.81	4.44	
			.090-.130	8	.020	Tin Plated Brass	.275	.657	.465	.175	41343
			2.29-3.30		0.51		6.98	16.69	11.81	4.44	
C	20-16	0.5-1.4	.100-.140	6	.020	Brass	.280	.755	.525	.225	60389-1
			2.54-3.56		0.51		7.11	19.18	13.33	5.71	
			.100-.140	8	.020	Brass	.280	.755	.525	.225	60390-1
			2.54-3.56		0.51		7.11	19.18	13.33	5.71	
B	18-14	0.8-2.0	.130-.180	8	.025	Tin Plated Brass	.312	.645	.520	.209	60251-2
			3.30-4.57		0.64		7.92	16.38	13.21	5.31	
			.100-.140	10	.030	Tin Plated Brass	.343	.752	.612	.312	40808
			2.54-3.56		0.76		8.71	19.10	15.54	7.92	
			.130-.180	6	.020	Tin Plated Brass	.275	.657	.463	.175	60725-1
			3.30-4.57		0.51		6.98	16.69	11.76	4.44	
			.130-.180	6	.018	Tin Plated Brass	.296	.750	.540	.235	60773-2
			3.30-4.57		0.46		7.52	19.05	13.72	5.97	
A	18-14	0.8-2.0	.100-.140	8	.018	Brass	.296	.750	.540	.235	60774-1
			2.54-3.56		0.46		7.52	19.05	13.72	5.97	
			.100-.140	8	.018	Tin Plated Brass	.296	.750	.540	.235	60774-2
			2.54-3.56		0.46		7.52	19.05	13.72	5.97	
			.100-.140	10	.018	Brass	.296	.750	.540	.235	60775-1
			2.54-3.56		0.46		7.52	19.05	13.72	5.97	

† Terminals flangeable by designated applicator.

Note: The part numbers listed are for use with existing machine models. For AMP-O-LECTRIC Model G applicators part numbers, call the Technical Support Center at 1-800-522-6752.