



PART NUMBER	"L" (METER)
0-0106888-1	1,0 -0/+0,1
0-0106888-2	2,0 -0/+0,1
0-0106888-3	3,0 -0/+0,1
0-0106888-4	4,0 -0/+0,1
0-0106888-5	5,0 -0/+0,1
0-0106888-6	6,0 -0/+0,1
0-0106888-7	7,0 -0/+0,1
0-0106888-8	8,0 -0/+0,1
0-0106888-9	9,0 -0/+0,1
1-0106888-0	10,0 -0/+0,1
1-0106888-1	11,0 -0/+0,2
1-0106888-2	12,0 -0/+0,2
1-0106888-3	13,0 -0/+0,2
1-0106888-4	14,0 -0/+0,2
1-0106888-5	15,0 -0/+0,2
1-0106888-6	16,0 -0/+0,2
1-0106888-7	17,0 -0/+0,2
1-0106888-8	18,0 -0/+0,2
1-0106888-9	19,0 -0/+0,2
2-0106888-0	20,0 -0/+0,2

NOTES:

- INSERTION LOSS $\leq 0,5\text{dB}$, MEASURED AGAINST REF. CONNECTOR
- RETURN LOSS $\geq 65\text{dB}$, MATED CONDITION.
- $\triangle 3$ APC ANGEL = 8°

$\triangle 4$ INFO ON CABLE LABEL:

 - PART NUMBER
 - FACTORY ORDER NUMBER
 - INSERTION LOSS, AND RETURN LOSS
 - UNIQUE SERIAL NUMBER
- CABLE:
 - 9/125/900 μm
 - CABLE DIAMETER 2,0mm
 - CABLE COLOUR: YELLOW
 - EASY STRIP BUFFER
 - OUTER SHEATH MATERIAL: THERMO PLASTIC

QTY	DESCRIPTION	ITEM
2	CABLE LABEL	10
2	FRONT OUTERSHELL	9
2	TULE GREEN	8
2	COMPRESSION SPRING	7
2	DUST CAP, MU	6
2	COUPLING DEVICE GREEN	5
2	REAR OUTERSHELL	4
2	CRIMP EYELET	3
2	SUBASSY FERRULE/FERRULEHOLDER 125 μm	2
L	$\phi 2,0\text{mm}$ SM CABLE 125 μm	1

SEE TABLE	D	EH02-0389-02	SG	RM	23 JAN 03	<p>CUSTOMER DRAWING FOR REFERENCE ONLY WILL NOT BE UPDATED</p> <p>© COPYRIGHT 19- BY AMP HOLLAND B.V. ALL INTERNATIONAL RIGHTS RESERVED. AMP PRODUCTS MAY BE COVERED BY U.S. AND FOREIGN AND/OR PATENTS PENDING. THIS DRAWING IS UNPUBLISHED RELEASED FOR PUBLICATION</p> <p>AMP AMP HOLLAND B.V. 's-Hertogenbosch, The Netherlands.</p> <p>NAME FOSM LEAD 2.0mm MU/APC - MU/APC</p>
	C	EH-0137-01	SM	SM	31 JAN 01	
	B	EH-1101-99	PS	WW	19 MAY 95	
	0	EH00-1386-95	WW	WW	NOV 95	
LTR.	REVISION RECORD		DR.	CHK.	DATE	
DR.:	S.MEEUWSEN	CHK.:	R. MAARTENS	APP.:	R. MAARTENS	DWG.No.
DATE:	04-03-94	DATE:	23 JAN 03	DATE:	23 JAN 03	C-106888
REV.LTR.	D		SHEET	1 OF 1		A2