

**LINEAR TECHNOLOGY MATERIALS DECLARATION**

ltc4283cuhf#trpbf

(Engineering Calculation)

QFN 5mm X 7mm Exp. Pad

(printed on: 2020-07-11 22:34:37)

**TOTAL MASS (g) : 0.092777**

COMPONENT MATERIAL	VENDOR/ INDUSTRY NAMES	CONSTITUENT NAME	CAS NUMBER	CONSTITUENT MASS (g)	CONSTITUENT (PPM) OF MATERIAL	CONSTITUENT (PPM) OF TOTAL PKG.		
Active Device	Linear Technology	Silicon (Si)	7440-21-3	0.005377	1000000	57956.265625		
Die Coat	Dow Corning	Silicone	69430-27-9	0.000000	0	0		
Lead Frame	Cu	Copper (Cu)	7440-50-8	0.037381	975000	402912.96875		
		Iron (Fe)	7439-89-6	0.000920	24000	9916.26660156		
		Phosphorus (P)	7723-14-0	0.000012	300	129.342605591		
		Zinc (Zn)	7440-66-6	0.000027	700	291.020843506		
		Nickel (Ni)	7440-02-0	0.000000	0	0		
		Silicon (Si)	7440-21-3	0.000000	0	0		
		Magnesium (Mg)	7439-95-4	0.000000	0	0		
		Tin (Sn)	7440-31-5	0.000000	0	0		
<b>Lead Frame Total:</b>				<b>0.038340</b>	<b>1000000</b>	<b>413249.59375</b>		
Plating	PMI	Exter. Plating Pb	7439-92-1	0.000000	0	0		
		Exter. Plating Sn	7440-31-5	0.001850	1000000	19938.71875		
		<b>External Plating Total:</b>				<b>0.001850</b>	<b>1000000</b>	<b>19938.71875</b>
		Inter. Plating Ni	7440-02-0	0.000000	0	0		
		Inter. Plating Ag	7440-22-4	0.000831	1000000	8956.97558594		
<b>Internal Plating Total:</b>				<b>0.000831</b>	<b>1000000</b>	<b>8956.97558594</b>		
Die Attach	ELECTRICALLY CONDUCTIVE ADHESIVE	Silver (Ag)	7440-22-4	0.001850	750000	19940.3164062		
		Tin (Sn)	7440-31-5	0.000000	0	0		
		Lead (Pb)	7439-92-1	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.000000	0	0		
		Indium (In)	7440-74-6	0.000000	0	0		
		Metal Oxide		0.000000	0	0		
		Antimony (Sb)	7440-36-0	0.000000	0	0		
		Resin (EP)		0.000617	250000	6650.36523438		
<b>Die Attach Total:</b>				<b>0.002467</b>	<b>1000000</b>	<b>26590.6816406</b>		
Encapsulation	MULTI-AROMATIC RESIN Br/Sb FREE	Resin (EP)		0.005689	130000	61319.1679688		
		Bromine (Br)	40039-93-8	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.037634	860000	405639.9375		
		Antimony Trioxide (Sb2O3)	1309-64-4	0.000000	0	0		
		Metal Hydroxide		0.000000	0	0		
		Carbon Black (C)	1333-86-4	0.000438	10000	4721.00488281		
		<b>Encapsulation Total:</b>				<b>0.043761</b>	<b>1000000</b>	<b>471680.125</b>
Bond Wire Estimated	AFW/TANAKA/ Kn	Gold (Au)	7440-57-5	0.000151	1000000	1627.56103516		
					<b>TOTAL MASS (g) :</b>	<b>0.092777</b>		