

LazrSPEED® 300 MPO (female) to MPO (male), ReadyPATCH® Armored Extension Cable, 24-Fiber, Plenum

Product Classification

Portfolio	Uniprise®
Brand	LazrSPEED® ReadyPATCH®
Product Type	Fiber extension cable assembly
Regional Availability	North America

Construction Materials

Fiber Type	OM3, LazrSPEED® 300
Total Fibers, quantity	24
Fibers per Subunit, quantity	12
Furcation Color	Aqua

Dimensions

Breakout Length	33 in
Cord Length, maximum	999 ft 999 m
Cord Length, minimum	10 ft 3 m
Ordering Note	For lengths greater than 999 ft (304 m), orders must be in meters Minimum length may vary based on cable configuration

Environmental Specifications

Environmental Space	Plenum
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)

General Specifications

Construction Type	ReadyPATCH® armored trunk/extension/cross-connect, indoor
Interface, connector A	MPO-12/UPC Female
Interface, connector B	MPO-12/UPC Male
Color, connector A	Aqua
Color, connector B	Aqua

Mechanical Specifications

Cable Retention Strength, maximum	4.40 lb @ 90 ° 11.24 lb @ 0 °
--	----------------------------------

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

ISO 9001:2015

Classification

Compliant

Designed, manufactured and/or distributed under this quality management system



Included Products

P-024-MZ-5L-F12 (Product Component—not orderable) — LazrSPEED® Plenum MPO Trunk Cable, interlocking aluminum armored with plenum jacket, 24 fiber with 12 fiber subunits

- CS-5L-MP (Product Component—not orderable) — LazrSPEED® 300 OM3 Bend-Insensitive Multimode Fiber

860366145 (Product Component—not orderable) — LazrSPEED® MPO Female 12 Fiber Connector, aqua

860366186 (Product Component—not orderable) — LazrSPEED® MPO Male 12 Fiber Connector, aqua