

RCA High Performance Plug, 734, 1505 AC

OBSOLETE

Regional Availability	North America
Product Type	Broadcast video connector
General Specifications	
Body Style	Straight
Compatible Cable type	RG 1505A RG 734
Inner Contact Attachment Method	Crimp
Interface	RCA male
Electrical Specifications	
Connector Impedance	75 ohm
Voltage Rating	1000 V
Mechanical Specifications	
Attachment Durability	500 cycles

Environmental Specifications

Operating Temperature	-40 °C to +65 °C (-40 °F to +149 °F)
Storage Temperature	-55 °C to +85 °C (-67 °F to +185 °F)
Relative Humidity	0%–95%, non-condensing
Flammability Rating	UL 94 V-0

Page 1 of 2

©2020 CommScope, Inc. All rights reserved. All trademarks identified by ® or [™] are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: September 17, 2020



CRCA-1

Packaging and Weights

Packaging quantity

1

Page 2 of 2

©2020 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: September 17, 2020

