
Product Change Notification(PCN)

Issue Date: 14.08.2013
Modification / Revision Date: 14.08.2013

IEEE 1394, 6 contacts, vertical version, DIP (2010 catalogue page 137)

Change Notification # : PCN 20131408-A-IEE-DIP

Description of changes: CHANGE OF MANUFACTURING LOCATION
CHANGE OF ORDERCODE
1. Amendment of the specification
2. Tolerance : New : x.xx ±0.13 // x.x ±0.25
3. Change of dimensions, see sheet 3
4. Catalogue 2010 shows different specification
5. Draw.-No. ASS 3559 COrev03 substitutes ASS 3559 COrev02

Date of change and Implementation: Change: KW 33/13 [Datecode of Production]
Implementation: KW 33/13

Key Characteristics of Change: Dimensions and Tolerances

Products Affected: A-IEE-DIP-C change to A-IEE-DIP

Reason for Change: Change of manufacturing location

Response : No response to this notification is required.





ASSMANN WSW components GmbH
Auf dem Schüffel 1
D-58513 Lüdenscheid
Tel.: +49-2351 - 554-0
Fax: +49-2351 - 554-99225

Product Change Notification(PCN)

Issue date: 14.08.2013
Modification / Revision date: 14.08.2013

A-IEE-DIP-C

Old version



NOTES:




1. Insulation: PBT UL94V-0, Color Black
2. Contact : Brass
3. Plating : Selective 30µ" Gold over 50µ" Nickel
4. Shell : Brass
5. Shell Plating: 80µ" Nickel over 50µ" Cu
6. Durability: 1500 cycles @

- (1) 8.4 ±0.30mm
- (2) 11.10 ±0.20mm
- (3) 2.80 ±0.20mm
- (4) 17.8 ±0.30mm
- (5) 13.5 ±0.30mm
- (6) 12.0 ±0.30mm

A-IEE-DIP


New version

①



NO.	Name	Material	Finish	Q'TY
1	Housing	PBT	Black	1
2	Pin Terminal	Brass t=0,2 Ni60-100µ" Sn:120-200µ"		6
3	Shell	Brass t=0,4 Ni 80-120µ"		1
4	Bottom Cover	PBT	Black	1

- (1) 8.7 ±0.25mm
- (2) 11.3 ±0.25mm
- (3) 1.5+1.5 ±0.13mm
- (4) 18.0 ±0.25mm
- (5) 13.85 ±0.13mm
- (6) 12.3 ±0.25mm



PCN Revision History:

Date of Revision: 14.08.2013

Revision Number: 00

