


High Power Resistive Products

Leaded Chip Terminations - LT Series

GENERAL SPECIFICATIONS

- **Nominal Impedance:** 50 Ω standard. Additional values available upon request. (DC Resistance may differ from selected impedance)
- **Tolerance:** $\pm 5\%$ standard. Additional tolerances available. (Refer to How to Order)
- **Operating Temp Range:** -55 to +150°C
- **Temperature Coefficient:** <150 ppm/°C
- **Resistive Elements:** Tantalum
- **Substrate Material:** Aluminum Nitride
- **Leads:** 99.99% Pure Silver
- **Cover:** Alumina
- **Reliability:** MIL-PRF-55342
- **RoHS Compliant**



Dimensions are in mm (inches)

Values in Inches

Part Number	W $\pm .010$	L $\pm .010$	T $\pm .005$	A $\pm .005$	Frequency* (GHz)	VSWR* (Typ.)	Power Max** (Watts)	Impedance Values (Ohms)
LT11020TxxxxJ	0.200	0.100	0.025	0.040	DC to 18.0	1.25:1	20W	10-75 Ω
LT12010TxxxxJ	0.100	0.200	0.040	0.040	DC to 4.0	1.20:1	30W	16.5-123.8 Ω
LT12525TxxxxJ	0.245	0.245	0.040	0.040	DC to 4.0	1.15:1	60W	10-75 Ω
LT12525TxxxxJ01	0.245	0.245	0.040	0.040	DC to 2.5	1.15:1	100W	11.5-86.3 Ω
LT12525TxxxxJ02	0.245	0.245	0.040	0.040	DC to 4.0	1.20:1	100W	10-75 Ω
LT12335TxxxxJ	0.350	0.230	0.040	0.040	DC to 4.0	1.15:1	100W	10-75 Ω
LT13725TxxxxJ	0.250	0.375	0.040	0.040	DC to 4.0	1.20:1	125W	18.2-136.6 Ω
LT13725TxxxxJ01	0.250	0.375	0.040	0.040	DC to 1.1	1.20:1	150W	20.8-156.3 Ω
LT13725TxxxxJ02	0.250	0.375	0.040	0.040	DC to 4.0	1.25:1	150W	18.2-136.6 Ω
LT13725TxxxxJ03	0.250	0.375	0.040	0.120	DC to 4.0	1.25:1	150W	18.2-136.6 Ω
LT13737TxxxxJ	0.370	0.370	0.040	0.040	DC to 2.0	1.25:1	200W	8-60 Ω
LT13737TxxxxJ01	0.370	0.370	0.040	0.040	DC to 1.0	1.20:1	250W	12.9-96.6 Ω
LT13737TxxxxJ02	0.370	0.370	0.040	0.040	DC to 2.0	1.25:1	250W	8-60 Ω
LT13737TxxxxJ03	0.370	0.370	0.040	0.120	DC to 2.0	1.25:1	250W	8-60 Ω

xxxx denotes Ohm value (See How to Order Below)

*Frequency and VSWR values are based upon a 50 Ω impedance

**Test Condition: Chip soldered to a large copper carrier whose surface is at 100°C; maximum rated power applied.

Specification: The resistance of the film shall change no more than <2% during and after a 1000-hr. Burn-in per MIL-PRF-55342.

HOW TO ORDER

LT1

Case Style

2010

Case Size

T

Termination

T = Ag over Ni
Chip Attach
(See Note Below for
Additional Options)

0050

Value

Impedance in Ω
Example:
0050 = 50 Ω
0100 = 100 Ω
25R5 = 25.5 Ω

J

Tolerance


Code	Tol.
G	$\pm 2\%$
J	$\pm 5\%$

BK

Packaging

BK = Plastic Carrier

POWER DERATING



Note: Special Order Terminations:

P = Pd over Ni Chip Attach

Pricing, lead times, and MOQ's vary