



Product Description

Three 16 AWG stranded (65x34) bare copper conductors, PVC insulation, Beldfoil® shield (100% coverage), PVC jacket.

Technical Specifications

Physical Characteristics (Overall)

AWG	Stranding	Material	No. of	Conductors
16	65x34	BC - Bare Copper	3	
Condu	ctor Count:			3
Condu	uctor Size:			16 AWG

PVC - Polyvinyl Chloride 0.033 in

	i olytiliyi olilollao	0.000

Material

Color Chart

Color
Light Blue
Brown
Green/Yellow

Outer Shield Material

Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Aluminum/Polyester	Beldfoil®	100 %	TC - Tinned Copper	20	7x28 mm

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.365 in	0.047 in

Nominal Wall Thickness

Construction and Dimensions

Type of Cordage:	SJT
Cabling	
Filler	
Jute	
Print Legend:	16-3SJT 60°C (UL) E3462 CSA LL7874 16-3 SJT 60°C FT2 Shielded
Electrical Characteris	tics

 Max. Recommended Current [A]

 13 Amps per conductor @ 25°C; 10 Amps per conductor @ 25°C (over 50 ft.)

 10 Amps per conductor @ 25°C (over 50 ft.)

Voltage

Dielectric Withstand Voltage UL Voltage Rating

2000 V AC Applied For 1 Min. 300 V RMS	
Electrical Characteristics Notes:	Dielectric Withstand Voltage: 2000 V AC Applied For 1 Min
Temperature Range	
UL Temp Rating:	60°C
UL Temp Rating: Mechanical Characteristics	60°C

Standards

NEC/(UL) Specification:	SIT
CSA AWM Specification:	511

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

CSA Flammability:	FT2
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No

Part Number

Variants		
ltem #	Color	Footnote
19363 010250	Black	С
Footnote:		

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.