

CSA Control Cable


600V Type TC/CIC Cables

Description	Part Number	No. of Cond.	Cable Weight		Jacket Thickness		Nominal OD	
			Lbs./1000 Ft.	kg/km	Inch	mm	Inch	mm

14 AWG Stranded (7x22) Bare Copper • Separator Tape

Cross-linked Polyethylene Insulation • Black PVC Jacket

CSA C22.2#230 Type TC
CSA C22.2#239 Type CIC
FT4 Flame Test



27000	2	110	164	.045	1.14	.368	9.35
27001	3	127	189	.045	1.14	.388	9.86
27002	4	151	224	.045	1.14	.420	10.67
27003	5	175	260	.045	1.14	.460	11.68
27004	6	198	295	.045	1.14	.500	12.70
27005	7	218	324	.045	1.14	.500	12.70
27006	8	249	370	.060	1.52	.610	15.49
27007	9	276	411	.060	1.52	.630	16.00
27008	10	328	488	.060	1.52	.630	16.00
27009	11	333	495	.060	1.52	.650	16.51
27010	12	359	535	.060	1.52	.650	16.51
27011	13	390	580	.060	1.52	.755	19.18
27012	14	409	609	.060	1.52	.755	19.18
27013	15	434	646	.060	1.52	.755	19.18
27014	16	454	675	.070	1.78	.810	20.57
27015	17	485	722	.075	1.91	.860	21.84
27016	18	505	751	.075	1.91	.860	21.84
27017	19	525	781	.075	1.91	.860	21.84
27018	20	558	831	.080	2.03	.887	22.53
27019	21	578	860	.080	2.03	.920	23.37
27020	22	614	914	.085	2.16	.970	24.64
27021	23	634	944	.085	2.16	.970	24.64
27022	24	716	1065	.090	2.29	1.040	26.42
27023	25	735	1094	.090	2.29	1.040	26.42
27024	26	755	1124	.090	2.29	1.040	26.42
27025	27	773	1151	.095	2.41	1.070	26.42
27026	28	795	1183	.095	2.41	1.100	27.94
27027	29	815	1213	.095	2.41	1.100	27.94
27028	30	832	1238	.095	2.41	1.100	27.94
27830	37	997	1484	.095	2.41	1.190	30.23

-25°C Installed

-40°C to +90°C (Wet/Dry)

Color Code: 2 conductors — Black, White (If required, a Red conductor can be used in place of White.)
3 conductors — Black, Red, Blue (If required, a White conductor can be used in place of Blue.)
4 conductors — Black, Red, Blue, White
5 or more conductors — number coded

