



ABC200-1024G

[Share](#)[DESCRIPTION](#) [SUPPORT](#) [REQUEST QUOT](#) [DOCUMENTS](#) [3D DRAWING](#)**Part Status:** End of Life**Last Time Buy Date:** 31th December 2021**Last Time Ship Date:** 31th March 2022Contact [Tech Help](#) for assistance

Power (W)	200
Output Voltage (VDC)	24
Output Current (A)	8.5
Voltage Input (VAC)	90-264
Operating Temperature (°C)	-10 to 50
Isolation	Isolated
Cooling Type	Fan
Mounting Type	Chassis Mount
Dimensions LxWxH (in)	4 x 2 x 1.5
Length (in)	4
Width (in)	2
Height (in)	1.5
Number of Outputs	1
Vout 1 (VDC)	24
Iout 1 (A)	8.5
RoHS	RoHS Compliant
Package	Open Frame

BEL GROUPS

[Bel Fuse-Circuit Protection](#)
[Bel Magnetic Solutions](#)
[Bel Power Solutions](#)
[Cinch Connectivity Solutions](#)
[CUI Inc.](#)
[EOS Power](#)
[Signal Transformer](#)
[Stewart Connector](#)
[TRP Connector](#)

PRODUCTS

[Aviation Spares](#)
[Cable Assemblies](#)
[Circuit Protection](#)
[Discrete Magnetics](#)
[High Frequency Magnetics](#)
[Integrated Connector Modules](#)
[Interconnects](#)
[Linear Magnetics](#)
[Microwave Components](#)
[Optical Connectivity](#)
[Patching Solutions](#)
[Power Supplies](#)
[Surface Mount Products](#)

RESOURCES

[Bel Extranet](#)
[Brochures & Catalogs](#)
[Cross Reference Tool](#)
[Distributor Stock](#)
[Order Status](#)
[Product Configurators](#)
[Product Discontinuances](#)
[Quality & Environment](#)
[Technical Library](#)

EXPLORE BEL

[About Us](#)
[Bel Extranet](#)
[Careers](#)
[Investors](#)
[News Room](#)

SOCIAL MEDIA

