


Home / Catalog / 8903VBG



## Insulating Covers: 8903VBG

Hard plastic covers designed to fit over TO-3 devices that protect from electrical shock during field service and repair. Aavid covers are available in screw-on and snap-on attachment methods for easy use and installation.

8903 Screw Mounted Cover Pan head screws not provided - MS 51957-30 or equivalent recommended - secure the cover to the TO-3. At the typical mounting screw torque of .68 - .90 Nm (6-8 inch pounds), the TO-3 cover material cold-flows around the screw head to securely fasten the cover.

Included are No.6 split washers as inserts to provide electrical connection of mounting screws to the TO-3 collector and an insulating snap-in cover for the screw heads. A test probe hole is provided in the top of the cover.

The 8903VB is made from thermoplastic polyester that meets the requirements of UL Bulletin 94 V-0. In addition to its excellent flammability rating, thermoplastic polyester offers resistance to most chemical environments, heat deflection temperature to 215.6°C (420°F) and UL continuous use temperature of 130 °C (266 °F).

If you are unable to add to your cart please be aware that no stock is available for purchase, please request a quote or email sales.na@aavid.com for availability.

- Buy Product
- Get a Sample
- Request a Quote

**Select Product Variation**

8903VBG

Price per piece

**\$3.28**

Quantity

- 1 +

Add to Cart

- Product Details
- Data and Performance
- Drawings
- Downloads

### Product Overview

**8903VBG**

Hard plastic covers designed to fit over TO-3 devices that protect from electrical shock during field service and repair. Aavid covers are available in screw-on and snap-on attachment methods for easy use and installation.

**8903 Screw Mounted Cover**  
Pan head screws not provided - MS 51957-30 or equivalent recommended - secure the cover to the TO-3. At the typical mounting screw torque of .68 - .90 Nm (6-8 inch pounds), the TO-3 cover material cold-flows around the screw head to securely fasten the cover.

Included are No.6 split washers as inserts to provide electrical connection of mounting screws to the TO-3 collector and an insulating snap-in cover for the screw heads. A test probe hole is provided in the top of the cover.

The 8903VB is made from thermoplastic polyester that meets the requirements of UL Bulletin 94 V-0. In addition to its excellent flammability rating, thermoplastic polyester offers resistance to most chemical environments, heat deflection temperature to 215.6°C (420°F) and UL continuous use temperature of 130 °C (266 °F).

- About Aavid**
- Locations
  - Privacy Policy
  - Cookie Policy
  - Terms and Conditions
  - Return Policy

- Products & Services**
- Catalog
  - Manufacturing Capabilities
  - Design & Engineering Services
  - Boyd Corporate Website

