

SINGLE CAPACITANCE

Filters:

Use Shift + Click or Ctrl + Click to make multiple selections









Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length	Diameter
1 μ F	240V	-10%/+10%	-40°C	70°C	1.31 in.	1.56 in.	1.31 in.	1.75 in.
2 μ F	300V	-6%/+6%			1.91 in.	2.12 in.	1.91 in.	1.75 in.
3 μ F	310V				1.97 in.	2.16 in.	1.97 in.	1.87 in.
4 μ F	330V				2.16 in.	2.19 in.	2.16 in.	2 in.
5 μ F	370V				2.91 in.	2.36 in.	2.91 in.	2.12 in.
Reset	Reset	Reset	Reset	Reset	Reset	Reset	Reset	Reset

[Reset All](#)

Products:

Show entries

Showing 1 to 4 of 4 entries. *Select product series below to filter by your selections.*

Type	Description	Status	Form Factor	Voltage (Vac)	Capacitance (F)
MPF	 Motor-Run	For New Design		330V - 440V	1 μ F - 80 μ F
Z Motor-Run	 Motor-Run and General Purpose	For New Design		370V - 440V	3 μ F - 60 μ F
Z Power Supply	 Power Supply	For New Design		240V - 660V	10 μ F - 120 μ F
SF	 Motor-Run	Not for New Design		240V - 660V	1 μ F - 100 μ F

Showing 1 to 4 of 4 entries.

Previous Next

Parts:

Show entries

Showing 1 to 322 of 322 entries.

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>Z23S2415M50N</u>	Yes	15 μ F	240V	-6%/+6%	-40°C	70°C	—	3.75 in.	—
<u>Z23S2420M50N</u>	Yes	20 μ F	240V	-6%/+6%	-40°C	70°C	—	2.75 in.	—
<u>Z23S2425M50N</u>	Yes	25 μ F	240V	-6%/+6%	-40°C	70°C	—	2.56 in.	—
<u>Z23S2430M50N</u>	Yes	30 μ F	240V	-6%/+6%	-40°C	70°C	—	3.13 in.	—
<u>Z23S2440M50N</u>	Yes	40 μ F	240V	-6%/+6%	-40°C	70°C	—	3.75 in.	—
<u>Z23S2450M50N</u>	Yes	50 μ F	240V	-6%/+6%	-40°C	70°C	—	3.75 in.	—
<u>Z26S2480M50N</u>	Yes	80 μ F	240V	-6%/+6%	-40°C	70°C	—	3.75 in.	—
<u>Z26S2412N50N</u>	Yes	120 μ F	240V	-6%/+6%	-40°C	70°C	—	3.95 in.	—
<u>Z26S3012N50N</u>	Yes	120 μ F	300V	-6%/+6%	-40°C	70°C	—	4.92 in.	—
<u>Z26S3190M50N</u>	Yes	90 μ F	310V	-6%/+6%	-40°C	70°C	—	4.75 in.	—
<u>23FD3303A-F</u>	Yes	3 μ F	330V	-10%/+10%	-40°C	70°C	—	2.38 in.	—

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>23FD3304A-F</u>	Yes	4 μ F	330V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>23FD3305A-F</u>	Yes	5 μ F	330V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>23FD3306A-F</u>	Yes	6 μ F	330V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>23FD3307A-F</u>	Yes	7 μ F	330V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>23FD3308A-F</u>	Yes	8 μ F	330V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>23FD3310A-F</u>	Yes	10 μ F	330V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>32FD3701A-F</u>	Yes	1 μ F	370V	-10%/+10%	-40°C	70°C	2.16 in.	2.19 in.	1.31 in.
<u>32FD3702A-F</u>	Yes	2 μ F	370V	-10%/+10%	-40°C	70°C	2.16 in.	2.19 in.	1.31 in.
<u>21FD3703A-F</u>	Yes	3 μ F	370V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>32FD3703A-F</u>	Yes	3 μ F	370V	-10%/+10%	-40°C	70°C	2.16 in.	2.19 in.	1.31 in.
<u>Z50S3703M</u>	Yes	3 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	1.56 in.	2.16 in.

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>21FD3704A-F</u>	Yes	4 μ F	370V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>32FD3704A-F</u>	Yes	4 μ F	370V	-10%/+10%	-40°C	70°C	2.16 in.	2.19 in.	1.31 in.
<u>Z50S3704M</u>	Yes	4 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	1.56 in.	2.16 in.
<u>Z23S3704M</u>	Yes	4 μ F	370V	-10%/+10%	-40°C	70°C	—	2.16 in.	—
<u>Z50S3705M</u>	Yes	5 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	1.56 in.	2.16 in.
<u>Z23S3705M</u>	Yes	5 μ F	370V	-10%/+10%	-40°C	70°C	—	2.16 in.	—
<u>32FD3705A-F</u>	Yes	5 μ F	370V	-10%/+10%	-40°C	70°C	2.16 in.	2.19 in.	1.31 in.
<u>21FD3705A-F</u>	Yes	5 μ F	370V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>21FD3706A-F</u>	Yes	6 μ F	370V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>Z50S3706M</u>	Yes	6 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	2.38 in.	2.16 in.
<u>Z23S3706M</u>	Yes	6 μ F	370V	-10%/+10%	-40°C	70°C	—	2.16 in.	—

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>32FD3706A-F</u>	Yes	6 μ F	370V	-10%/+10%	-40°C	70°C	2.16 in.	2.19 in.	1.31 in.
<u>21FD3707A-F</u>	Yes	7 μ F	370V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>32FD37075A-F</u>	Yes	7.5 μ F	370V	-10%/+10%	-40°C	70°C	2.16 in.	2.19 in.	1.31 in.
<u>Z50S3707N</u>	Yes	7.5 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	2.38 in.	2.16 in.
<u>Z23S3707N</u>	Yes	7.5 μ F	370V	-10%/+10%	-40°C	70°C	—	2.16 in.	—
<u>21FD3708A-F</u>	Yes	8 μ F	370V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>Z50S3710M</u>	Yes	10 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	2.75 in.	2.16 in.
<u>Z23S3710M</u>	Yes	10 μ F	370V	-10%/+10%	-40°C	70°C	—	2.36 in.	—
<u>21FD3710A-F</u>	Yes	10 μ F	370V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>32FD3710A-F</u>	Yes	10 μ F	370V	-10%/+10%	-40°C	70°C	2.16 in.	2.88 in.	1.31 in.
<u>Z23S3710M50N</u>	Yes	10 μ F	370V	-6%/+6%	-40°C	70°C	—	2.36 in.	—

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>21FD37125A-F</u>	Yes	12.5 μ F	370V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>37FD37125A-F</u>	Yes	12.5 μ F	370V	-10%/+10%	-40°C	70°C	2.91 in.	2.38 in.	1.91 in.
<u>Z50S3712N</u>	Yes	12.5 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	3.25 in.	2.16 in.
<u>Z23S3712N</u>	Yes	12.5 μ F	370V	-10%/+10%	-40°C	70°C	—	2.36 in.	—
<u>32FD37125A-F</u>	Yes	12.5 μ F	370V	-10%/+10%	-40°C	70°C	2.16 in.	2.88 in.	1.31 in.
<u>21FD3715A-F</u>	Yes	15 μ F	370V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>Z50S3715M</u>	Yes	15 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	3.94 in.	2.16 in.
<u>Z23S3715M</u>	Yes	15 μ F	370V	-10%/+10%	-40°C	70°C	—	2.56 in.	—
<u>37FD3715A-F</u>	Yes	15 μ F	370V	-10%/+10%	-40°C	70°C	2.91 in.	2.38 in.	1.91 in.
<u>21FD37175A-F</u>	Yes	17.5 μ F	370V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>37FD37175A-F</u>	Yes	17.5 μ F	370V	-10%/+10%	-40°C	70°C	2.91 in.	2.38 in.	1.91 in.

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>21FD3720A-F</u>	Yes	20 μ F	370V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>Z64S3720M</u>	Yes	20 μ F	370V	-10%/+10%	-40°C	70°C	1.91 in.	2.38 in.	2.91 in.
<u>Z23S3720M</u>	Yes	20 μ F	370V	-10%/+10%	-40°C	70°C	—	2.75 in.	—
<u>37FD3720A-F</u>	Yes	20 μ F	370V	-10%/+10%	-40°C	70°C	2.91 in.	2.38 in.	1.91 in.
<u>37FD37225A-F</u>	Yes	22.5 μ F	370V	-10%/+10%	-40°C	70°C	2.91 in.	2.38 in.	1.91 in.
<u>23FD3725A-F</u>	Yes	25 μ F	370V	-10%/+10%	-40°C	70°C	—	2.91 in.	—
<u>21FD3725A-F</u>	Yes	25 μ F	370V	-10%/+10%	-40°C	70°C	—	2.84 in.	—
<u>Z64S3725M</u>	Yes	25 μ F	370V	-10%/+10%	-40°C	70°C	1.91 in.	2.75 in.	2.91 in.
<u>Z23S3725M</u>	Yes	25 μ F	370V	-10%/+10%	-40°C	70°C	—	3.15 in.	—
<u>37FD3725A-F</u>	Yes	25 μ F	370V	-10%/+10%	-40°C	70°C	2.91 in.	2.91 in.	1.91 in.
<u>38FD37275A-F</u>	Yes	27.5 μ F	370V	-10%/+10%	-40°C	70°C	3.66 in.	2.91 in.	1.97 in.

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>38FD3730A-F</u>	Yes	30 μ F	370V	-10%/+10%	-40°C	70°C	3.66 in.	2.91 in.	1.97 in.
<u>Z23S3730M</u>	Yes	30 μ F	370V	-10%/+10%	-40°C	70°C	—	3.15 in.	—
<u>21FD3730A-F</u>	Yes	30 μ F	370V	-10%/+10%	-40°C	70°C	—	2.84 in.	—
<u>23FD3730A-F</u>	Yes	30 μ F	370V	-10%/+10%	-40°C	70°C	—	2.91 in.	—
<u>37FD3730A-F</u>	Yes	30 μ F	370V	-10%/+10%	-40°C	70°C	2.91 in.	2.91 in.	1.91 in.
<u>37FD3735A-F</u>	Yes	35 μ F	370V	-10%/+10%	-40°C	70°C	2.91 in.	3.91 in.	1.91 in.
<u>Z23S3735M</u>	Yes	35 μ F	370V	-10%/+10%	-40°C	70°C	—	4.25 in.	—
<u>23FD3735A-F</u>	Yes	35 μ F	370V	-10%/+10%	-40°C	70°C	—	2.91 in.	—
<u>21FD3735A-F</u>	Yes	35 μ F	370V	-10%/+10%	-40°C	70°C	—	3.84 in.	—
<u>38FD3735A-F</u>	Yes	35 μ F	370V	-10%/+10%	-40°C	70°C	3.66 in.	2.91 in.	1.97 in.
<u>37FD3740A-F</u>	Yes	40 μ F	370V	-10%/+10%	-40°C	70°C	2.91 in.	3.91 in.	1.91 in.

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>Z24S3740M</u>	Yes	40 μ F	370V	-10%/+10%	-40°C	70°C	—	3.55 in.	—
<u>38FD3740A-F</u>	Yes	40 μ F	370V	-10%/+10%	-40°C	70°C	3.66 in.	2.91 in.	1.97 in.
<u>23FD3740A-F</u>	Yes	40 μ F	370V	-10%/+10%	-40°C	70°C	—	2.91 in.	—
<u>21FD3740A-F</u>	Yes	40 μ F	370V	-10%/+10%	-40°C	70°C	—	3.84 in.	—
<u>Z24S3745M</u>	Yes	45 μ F	370V	-10%/+10%	-40°C	70°C	—	3.95 in.	—
<u>38FD3745A-F</u>	Yes	45 μ F	370V	-10%/+10%	-40°C	70°C	3.66 in.	2.91 in.	1.97 in.
<u>37FD3745A-F</u>	Yes	45 μ F	370V	-10%/+10%	-40°C	70°C	2.91 in.	3.91 in.	1.91 in.
<u>24FD3745A-F</u>	Yes	45 μ F	370V	-10%/+10%	-40°C	70°C	—	2.91 in.	—
<u>23FD3745A-F</u>	Yes	45 μ F	370V	-10%/+10%	-40°C	70°C	—	3.84 in.	—
<u>23FD3750A-F</u>	Yes	50 μ F	370V	-10%/+10%	-40°C	70°C	—	3.84 in.	—
<u>38FD3750A-F</u>	Yes	50 μ F	370V	-10%/+10%	-40°C	70°C	3.66 in.	2.91 in.	1.97 in.

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>Z24S3750M</u>	Yes	50 μ F	370V	-10%/+10%	-40°C	70°C	—	3.88 in.	—
<u>24FD3750A-F</u>	Yes	50 μ F	370V	-10%/+10%	-40°C	70°C	—	2.91 in.	—
<u>24FD3755A-F</u>	Yes	55 μ F	370V	-10%/+10%	-40°C	70°C	—	2.91 in.	—
<u>23FD3755A-F</u>	Yes	55 μ F	370V	-10%/+10%	-40°C	70°C	—	3.84 in.	—
<u>23FD3760A-F</u>	Yes	60 μ F	370V	-10%/+10%	-40°C	70°C	—	3.84 in.	—
<u>24FD3760A-F</u>	Yes	60 μ F	370V	-10%/+10%	-40°C	70°C	—	2.91 in.	—
<u>Z26S3760M56N</u>	Yes	60 μ F	370V	-6%/+6%	-40°C	70°C	—	3.75 in.	—
<u>24FD3765A-F</u>	Yes	65 μ F	370V	-10%/+10%	-40°C	70°C	—	3.91 in.	—
<u>38FD3770A-F</u>	Yes	70 μ F	370V	-10%/+10%	-40°C	70°C	3.66 in.	3.91 in.	1.97 in.
<u>24FD3770A-F</u>	Yes	70 μ F	370V	-10%/+10%	-40°C	70°C	—	3.91 in.	—
<u>Z26S3770M50N</u>	Yes	70 μ F	370V	-6%/+6%	-40°C	70°C	—	4.33 in.	—

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>Z26S3775M50N</u>	Yes	75 μ F	370V	-6%/+6%	-40°C	70°C	—	4.75 in.	—
<u>24FD3780A-F</u>	Yes	80 μ F	370V	-10%/+10%	-40°C	70°C	—	4.75 in.	—
<u>Z26S3790M50N</u>	Yes	90 μ F	370V	-6%/+6%	-40°C	70°C	—	4.33 in.	—
<u>32FB4401A-F</u>	Yes	1 μ F	440V	-10%/+10%	-40°C	70°C	2.16 in.	2.19 in.	1.31 in.
<u>32FB4402A-F</u>	Yes	2 μ F	440V	-10%/+10%	-40°C	70°C	2.16 in.	2.19 in.	1.31 in.
<u>32FB4403A-F</u>	Yes	3 μ F	440V	-10%/+10%	-40°C	70°C	2.16 in.	2.19 in.	1.31 in.
<u>Z50S4403M</u>	Yes	3 μ F	440V	-10%/+10%	-40°C	70°C	1.31 in.	1.56 in.	2.16 in.
<u>32FB4404A-F</u>	Yes	4 μ F	440V	-10%/+10%	-40°C	70°C	2.16 in.	2.19 in.	1.31 in.
<u>32FB4405A-F</u>	Yes	5 μ F	440V	-10%/+10%	-40°C	70°C	2.16 in.	2.19 in.	1.31 in.
<u>Z50S4405M</u>	Yes	5 μ F	440V	-10%/+10%	-40°C	70°C	1.31 in.	2.12 in.	2.16 in.
<u>32FB4406A-F</u>	Yes	6 μ F	440V	-10%/+10%	-40°C	70°C	2.16 in.	2.19 in.	1.31 in.

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>37FB44075A-F</u>	Yes	7.5 μ F	440V	-10%/+10%	-40°C	70°C	2.91 in.	2.38 in.	1.91 in.
<u>32FB44075A-F</u>	Yes	7.5 μ F	440V	-10%/+10%	-40°C	70°C	2.16 in.	2.88 in.	1.31 in.
<u>Z50S4407N</u>	Yes	7.5 μ F	440V	-10%/+10%	-40°C	70°C	1.31 in.	3.15 in.	2.16 in.
<u>Z50S4410M</u>	Yes	10 μ F	440V	-10%/+10%	-40°C	70°C	1.31 in.	3.25 in.	2.16 in.
<u>37FB4410A-F</u>	Yes	10 μ F	440V	-10%/+10%	-40°C	70°C	2.91 in.	2.38 in.	1.91 in.
<u>32FB4410A-F</u>	Yes	10 μ F	440V	-10%/+10%	-40°C	70°C	2.16 in.	2.88 in.	1.31 in.
<u>37FB44125A-F</u>	Yes	12.5 μ F	440V	-10%/+10%	-40°C	70°C	2.91 in.	2.38 in.	1.91 in.
<u>Z50S4415M</u>	Yes	15 μ F	440V	-10%/+10%	-40°C	70°C	1.31 in.	4.13 in.	2.16 in.
<u>Z23S4415M</u>	Yes	15 μ F	440V	-10%/+10%	-40°C	70°C	—	3.25 in.	—
<u>21FB4415A-F</u>	Yes	15 μ F	440V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>37FB4415A-F</u>	Yes	15 μ F	440V	-10%/+10%	-40°C	70°C	2.91 in.	2.38 in.	1.91 in.

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>37FB44175A-F</u>	Yes	17.5 μ F	440V	-10%/+10%	-40°C	70°C	2.91 in.	2.91 in.	1.91 in.
<u>23FB4420A-F</u>	Yes	20 μ F	440V	-10%/+10%	-40°C	70°C	—	2.91 in.	—
<u>21FB4420A-F</u>	Yes	20 μ F	440V	-10%/+10%	-40°C	70°C	—	2.84 in.	—
<u>38FB4420A-F</u>	Yes	20 μ F	440V	-10%/+10%	-40°C	70°C	3.66 in.	2.91 in.	1.97 in.
<u>37FB4420A-F</u>	Yes	20 μ F	440V	-10%/+10%	-40°C	70°C	2.91 in.	2.91 in.	1.91 in.
<u>Z23S4420M</u>	Yes	20 μ F	440V	-10%/+10%	-40°C	70°C	—	3.15 in.	—
<u>23FB44225A-F</u>	Yes	22.5 μ F	440V	-10%/+10%	-40°C	70°C	—	2.91 in.	—
<u>21FB44225A-F</u>	Yes	22.5 μ F	440V	-10%/+10%	-40°C	70°C	—	2.84 in.	—
<u>23FB4425A-F</u>	Yes	25 μ F	440V	-10%/+10%	-40°C	70°C	—	2.91 in.	—
<u>21FB4425A-F</u>	Yes	25 μ F	440V	-10%/+10%	-40°C	70°C	—	3.84 in.	—
<u>38FB4425A-F</u>	Yes	25 μ F	440V	-10%/+10%	-40°C	70°C	3.66 in.	3.91 in.	1.97 in.

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>37FB4425A-F</u>	Yes	25 μ F	440V	-10%/+10%	-40°C	70°C	2.91 in.	3.91 in.	1.91 in.
<u>Z64S4425M</u>	Yes	25 μ F	440V	-10%/+10%	-40°C	70°C	1.91 in.	3.25 in.	2.91 in.
<u>Z23S4425M</u>	Yes	25 μ F	440V	-10%/+10%	-40°C	70°C	—	3.54 in.	—
<u>Z24S4430M</u>	Yes	30 μ F	440V	-10%/+10%	-40°C	70°C	—	3.75 in.	—
<u>24FB4430A-F</u>	Yes	30 μ F	440V	-10%/+10%	-40°C	70°C	—	2.91 in.	—
<u>23FB4430A-F</u>	Yes	30 μ F	440V	-10%/+10%	-40°C	70°C	—	3.84 in.	—
<u>38FB4430A-F</u>	Yes	30 μ F	440V	-10%/+10%	-40°C	70°C	3.66 in.	3.91 in.	1.97 in.
<u>Z26S4430M50N</u>	Yes	30 μ F	440V	-6%/+6%	-40°C	70°C	—	2.95 in.	—
<u>37FB4435A-F</u>	Yes	35 μ F	440V	-10%/+10%	-40°C	70°C	2.91 in.	4.75 in.	1.91 in.
<u>Z24S4435M</u>	Yes	35 μ F	440V	-10%/+10%	-40°C	70°C	—	3.94 in.	—
<u>24FB4435A-F</u>	Yes	35 μ F	440V	-10%/+10%	-40°C	70°C	—	2.91 in.	—

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>23FB4435A-F</u>	Yes	35 μ F	440V	-10%/+10%	-40°C	70°C	—	3.84 in.	—
<u>38FB4435A-F</u>	Yes	35 μ F	440V	-10%/+10%	-40°C	70°C	3.66 in.	3.91 in.	1.97 in.
<u>24FB4440A-F</u>	Yes	40 μ F	440V	-10%/+10%	-40°C	70°C	—	3.91 in.	—
<u>38FB4440A-F</u>	Yes	40 μ F	440V	-10%/+10%	-40°C	70°C	3.66 in.	3.91 in.	1.97 in.
<u>37FB4440A-F</u>	Yes	40 μ F	440V	-10%/+10%	-40°C	70°C	2.91 in.	4.75 in.	1.91 in.
<u>Z24S4440M</u>	Yes	40 μ F	440V	-10%/+10%	-40°C	70°C	—	4.33 in.	—
<u>23FB4440A-F</u>	Yes	40 μ F	440V	-10%/+10%	-40°C	70°C	—	3.84 in.	—
<u>Z26S4440M50N</u>	Yes	40 μ F	440V	-6%/+6%	-40°C	70°C	—	4.5 in.	—
<u>24FB4445A-F</u>	Yes	45 μ F	440V	-10%/+10%	-40°C	70°C	—	3.91 in.	—
<u>Z26S4445M</u>	Yes	45 μ F	440V	-10%/+10%	-40°C	70°C	—	3.35 in.	—
<u>38FB4445A-F</u>	Yes	45 μ F	440V	-10%/+10%	-40°C	70°C	3.66 in.	3.91 in.	1.97 in.

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>24FB4450A-F</u>	Yes	50 μ F	440V	-10%/+10%	-40°C	70°C	—	3.91 in.	—
<u>38FB4450A-F</u>	Yes	50 μ F	440V	-10%/+10%	-40°C	70°C	3.66 in.	3.91 in.	1.97 in.
<u>Z26S4450M</u>	Yes	50 μ F	440V	-10%/+10%	-40°C	70°C	—	3.25 in.	—
<u>Z26S4455M</u>	Yes	55 μ F	440V	-10%/+10%	-40°C	70°C	—	3.25 in.	—
<u>38FB4455A-F</u>	Yes	55 μ F	440V	-10%/+10%	-40°C	70°C	3.66 in.	4.75 in.	1.97 in.
<u>24FB4455A-F</u>	Yes	55 μ F	440V	-10%/+10%	-40°C	70°C	—	3.91 in.	—
<u>Z26S4456M51N</u>	Yes	56 μ F	440V	-6%/+6%	-40°C	70°C	—	3.75 in.	—
<u>Z26S4456M50N</u>	Yes	56 μ F	440V	-6%/+6%	-40°C	70°C	—	4.5 in.	—
<u>38FB4460A-F</u>	Yes	60 μ F	440V	-10%/+10%	-40°C	70°C	3.66 in.	4.75 in.	1.97 in.
<u>Z26S4460M</u>	Yes	60 μ F	440V	-10%/+10%	-40°C	70°C	—	3.75 in.	—
<u>24FB4460A-F</u>	Yes	60 μ F	440V	-10%/+10%	-40°C	70°C	—	4.75 in.	—

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>24FB4470A-F</u>	Yes	70 μ F	440V	-10%/+10%	-40°C	70°C	—	4.75 in.	—
<u>Z26S5530M50N</u>	Yes	30 μ F	550V	-6%/+6%	-40°C	70°C	—	3.75 in.	—
<u>Z26S5592MT5</u>	Yes	92 μ F	550V	-6%/+6%	-40°C	70°C	—	7.5 in.	—
<u>Z26S5846M50N</u>	Yes	46 μ F	580V	-6%/+6%	-40°C	70°C	—	4.75 in.	—
<u>Z26S5870M50N</u>	Yes	70 μ F	580V	-6%/+6%	-40°C	70°C	—	6.69 in.	—
<u>Z26S5892MT5</u>	Yes	92 μ F	580V	-6%/+6%	-40°C	70°C	—	7.5 in.	—
<u>Z26S6021M50N</u>	Yes	21 μ F	600V	-6%/+6%	-40°C	70°C	—	3.15 in.	—
<u>Z26S6025M50N</u>	Yes	25 μ F	600V	-6%/+6%	-40°C	70°C	—	3.31 in.	—
<u>Z26S6028M50N</u>	Yes	28 μ F	600V	-6%/+6%	-40°C	70°C	—	3.75 in.	—
<u>Z26S6030M56N</u>	Yes	30 μ F	600V	-6%/+6%	-40°C	70°C	—	4.75 in.	—
<u>Z26S6040M56N</u>	Yes	40 μ F	600V	-6%/+6%	-40°C	70°C	—	4.75 in.	—

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>Z26S6045M50N</u>	Yes	45 μ F	600V	-6%/+6%	-40°C	70°C	—	4.75 in.	—
<u>Z26S6620M50N</u>	Yes	20 μ F	660V	-6%/+6%	-40°C	70°C	—	3.54 in.	—
<u>Z62S6625M50N</u>	Yes	25 μ F	660V	-6%/+6%	-40°C	70°C	1.97 in.	3.75 in.	3.66 in.
<u>Z64S6625M50N</u>	Yes	25 μ F	660V	-6%/+6%	-40°C	70°C	1.31 in.	4.29 in.	2.16 in.
<u>Z26S6630M50N</u>	Yes	30 μ F	660V	-6%/+6%	-40°C	70°C	—	3.75 in.	—
<u>Z62S6635M50N</u>	Yes	35 μ F	660V	-6%/+6%	-40°C	70°C	1.97 in.	4.75 in.	3.66 in.
<u>Z62S6650M50N</u>	Yes	50 μ F	660V	-6%/+6%	-40°C	70°C	1.97 in.	5.12 in.	3.66 in.
<u>SFA24T4K219B-F</u>	No	4 μ F	240V	-10%/+10%	-40°C	70°C	1.31 in.	2.19 in.	2.16 in.
<u>SFA24T5K219B-F</u>	No	5 μ F	240V	-10%/+10%	-40°C	70°C	1.31 in.	2.19 in.	2.16 in.
<u>SFA24T6K219B-F</u>	No	6 μ F	240V	-10%/+10%	-40°C	70°C	1.31 in.	2.19 in.	2.16 in.
<u>SFA24T7.5K219B-F</u>	No	7.5 μ F	240V	-10%/+10%	-40°C	70°C	1.31 in.	2.19 in.	2.16 in.

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>SFA24T10K219B-F</u>	No	10 μ F	240V	-10%/+10%	-40°C	70°C	1.31 in.	2.19 in.	2.16 in.
<u>SFA24T15K288B-F</u>	No	15 μ F	240V	-10%/+10%	-40°C	70°C	1.31 in.	2.88 in.	2.16 in.
<u>SFA24T20K288B-F</u>	No	20 μ F	240V	-10%/+10%	-40°C	70°C	1.31 in.	2.88 in.	2.16 in.
<u>SFC24T25K291B-F</u>	No	25 μ F	240V	-10%/+10%	-40°C	70°C	1.91 in.	2.91 in.	2.91 in.
<u>SFC24T30K291B-F</u>	No	30 μ F	240V	-10%/+10%	-40°C	70°C	1.91 in.	2.91 in.	2.91 in.
<u>SFC24T35K291B-F</u>	No	35 μ F	240V	-10%/+10%	-40°C	70°C	1.91 in.	2.91 in.	2.91 in.
<u>SFC24T40K291B-F</u>	No	40 μ F	240V	-10%/+10%	-40°C	70°C	1.91 in.	2.91 in.	2.91 in.
<u>SFC24T45K291B-F</u>	No	45 μ F	240V	-10%/+10%	-40°C	70°C	1.91 in.	2.91 in.	2.91 in.
<u>SFC24T50K291B-F</u>	No	50 μ F	240V	-10%/+10%	-40°C	70°C	1.91 in.	2.91 in.	2.91 in.
<u>SFC24T60K391B-F</u>	No	60 μ F	240V	-10%/+10%	-40°C	70°C	1.91 in.	3.91 in.	2.91 in.
<u>SFC24T70K391B-F</u>	No	70 μ F	240V	-10%/+10%	-40°C	70°C	1.91 in.	3.91 in.	2.91 in.

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>SFP37T2K238B-F</u>	No	2 μ F	370V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>SFA37T2K156B-F</u>	No	2 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	1.56 in.	2.16 in.
<u>SFA37T2K219B-F</u>	No	2 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	2.19 in.	2.16 in.
<u>SFP37T3K238B-F</u>	No	3 μ F	370V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>SFA37T3K156B-F</u>	No	3 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	1.56 in.	2.16 in.
<u>SFA37T3K219B-F</u>	No	3 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	2.19 in.	2.16 in.
<u>SFP37T4K238B-F</u>	No	4 μ F	370V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>SFA37T4K156B-F</u>	No	4 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	1.56 in.	2.16 in.
<u>SFA37T4K219B-F</u>	No	4 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	2.19 in.	2.16 in.
<u>SFP37T5K238B-F</u>	No	5 μ F	370V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>SFA37T5K156B-F</u>	No	5 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	1.56 in.	2.16 in.

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>SFA37T5K219B-F</u>	No	5 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	2.19 in.	2.16 in.
<u>SFP37T6K238B-F</u>	No	6 μ F	370V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>SFA37T6K156B-F</u>	No	6 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	1.56 in.	2.16 in.
<u>SFA37T6K219B-F</u>	No	6 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	2.19 in.	2.16 in.
<u>SFP37T7.5K238B-F</u>	No	7.5 μ F	370V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>SFA37T7.5K219B-F</u>	No	7.5 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	2.19 in.	2.16 in.
<u>SFP37T10K238B-F</u>	No	10 μ F	370V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>SFA37T10K288B-F</u>	No	10 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	2.88 in.	2.16 in.
<u>SFP37T12.5K238B-F</u>	No	12.5 μ F	370V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>SFA37T12.5K288B-F</u>	No	12.5 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	2.88 in.	2.16 in.
<u>SFP37T15K238B-F</u>	No	15 μ F	370V	-10%/+10%	-40°C	70°C	—	2.38 in.	—

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>SFA37T15K288B-F</u>	No	15 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	2.88 in.	2.16 in.
<u>SFP37T17.5K238B-F</u>	No	17.5 μ F	370V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>SFC37T17.5K291B-F</u>	No	17.5 μ F	370V	-10%/+10%	-40°C	70°C	1.91 in.	2.91 in.	2.91 in.
<u>SFP37T20K238B-F</u>	No	20 μ F	370V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>SFA37T20K388B-F</u>	No	20 μ F	370V	-10%/+10%	-40°C	70°C	1.31 in.	3.88 in.	2.16 in.
<u>SFC37T20K291B-F</u>	No	20 μ F	370V	-10%/+10%	-40°C	70°C	1.91 in.	2.91 in.	2.91 in.
<u>SFP37T25K284B-F</u>	No	25 μ F	370V	-10%/+10%	-40°C	70°C	—	2.84 in.	—
<u>SFC37T25K291B-F</u>	No	25 μ F	370V	-10%/+10%	-40°C	70°C	1.91 in.	2.91 in.	2.91 in.
<u>SFP37T30K284B-F</u>	No	30 μ F	370V	-10%/+10%	-40°C	70°C	—	2.84 in.	—
<u>SFC37T30K291B-F</u>	No	30 μ F	370V	-10%/+10%	-40°C	70°C	1.91 in.	2.91 in.	2.91 in.
<u>SFS37T35K291B-F</u>	No	35 μ F	370V	-10%/+10%	-40°C	70°C	—	2.91 in.	—

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>SFC37T35K291B-F</u>	No	35 μ F	370V	-10%/+10%	-40°C	70°C	1.91 in.	2.91 in.	2.91 in.
<u>SFS37T40K291B-F</u>	No	40 μ F	370V	-10%/+10%	-40°C	70°C	—	2.91 in.	—
<u>SFC37T40K391B-F</u>	No	40 μ F	370V	-10%/+10%	-40°C	70°C	1.91 in.	3.91 in.	2.91 in.
<u>SFS37T45K384B-F</u>	No	45 μ F	370V	-10%/+10%	-40°C	70°C	—	3.84 in.	—
<u>SFC37T45K391B-F</u>	No	45 μ F	370V	-10%/+10%	-40°C	70°C	1.91 in.	3.91 in.	2.91 in.
<u>SFS37T50K384B-F</u>	No	50 μ F	370V	-10%/+10%	-40°C	70°C	—	3.84 in.	—
<u>SFC37T50K391B-F</u>	No	50 μ F	370V	-10%/+10%	-40°C	70°C	1.91 in.	3.91 in.	2.91 in.
<u>SFS37T55K384B-F</u>	No	55 μ F	370V	-10%/+10%	-40°C	70°C	—	3.84 in.	—
<u>SFT37T60K291B-F</u>	No	60 μ F	370V	-10%/+10%	-40°C	70°C	—	2.91 in.	—
<u>SFT37T65K291B-F</u>	No	65 μ F	370V	-10%/+10%	-40°C	70°C	—	2.91 in.	—
<u>SFT37T70K291B-F</u>	No	70 μ F	370V	-10%/+10%	-40°C	70°C	—	2.91 in.	—

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>SFT37T75K391B-F</u>	No	75 μ F	370V	-10%/+10%	-40°C	70°C	—	3.91 in.	—
<u>SFT37T80K391B-F</u>	No	80 μ F	370V	-10%/+10%	-40°C	70°C	—	3.91 in.	—
<u>SFT37T90K475B-F</u>	No	90 μ F	370V	-10%/+10%	-40°C	70°C	—	4.75 in.	—
<u>SFT37T100K475B-F</u>	No	100 μ F	370V	-10%/+10%	-40°C	70°C	—	4.75 in.	—
<u>SFP44T2K238B-F</u>	No	2 μ F	440V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>SFA44T2K156B-F</u>	No	2 μ F	440V	-10%/+10%	-40°C	70°C	1.31 in.	1.56 in.	2.16 in.
<u>SFA44T2K219B-F</u>	No	2 μ F	440V	-10%/+10%	-40°C	70°C	1.31 in.	2.19 in.	2.16 in.
<u>SFP44T3K238B-F</u>	No	3 μ F	440V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>SFA44T3K156B-F</u>	No	3 μ F	440V	-10%/+10%	-40°C	70°C	1.31 in.	1.56 in.	2.16 in.
<u>SFA44T3K219B-F</u>	No	3 μ F	440V	-10%/+10%	-40°C	70°C	1.31 in.	2.19 in.	2.16 in.
<u>SFP44T4K238B-F</u>	No	4 μ F	440V	-10%/+10%	-40°C	70°C	—	2.38 in.	—

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>SFA44T4K156B-F</u>	No	4 μ F	440V	-10%/+10%	-40°C	70°C	1.31 in.	1.56 in.	2.16 in.
<u>SFA44T4K219B-F</u>	No	4 μ F	440V	-10%/+10%	-40°C	70°C	1.31 in.	2.19 in.	2.16 in.
<u>SFP44T5K238B-F</u>	No	5 μ F	440V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>SFA44T5K219B-F</u>	No	5 μ F	440V	-10%/+10%	-40°C	70°C	1.31 in.	2.19 in.	2.16 in.
<u>SFP44T6K238B-F</u>	No	6 μ F	440V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>SFA44T6K288B-F</u>	No	6 μ F	440V	-10%/+10%	-40°C	70°C	1.31 in.	2.88 in.	2.16 in.
<u>SFP44T7.5K238B-F</u>	No	7.5 μ F	440V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>SFA44T7.5K288B-F</u>	No	7.5 μ F	440V	-10%/+10%	-40°C	70°C	1.31 in.	2.88 in.	2.16 in.
<u>SFP44T10K238B-F</u>	No	10 μ F	440V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>SFA44T10K388B-F</u>	No	10 μ F	440V	-10%/+10%	-40°C	70°C	1.31 in.	3.88 in.	2.16 in.
<u>SFP44T12.5K238B-F</u>	No	12.5 μ F	440V	-10%/+10%	-40°C	70°C	—	2.38 in.	—

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>SFC44T12.5K291B-F</u>	No	12.5 μ F	440V	-10%/+10%	-40°C	70°C	1.91 in.	2.91 in.	2.91 in.
<u>SFA44T12.5K388B-F</u>	No	12.5 μ F	440V	-10%/+10%	-40°C	70°C	1.31 in.	3.88 in.	2.16 in.
<u>SFP44T15K284B-F</u>	No	15 μ F	440V	-10%/+10%	-40°C	70°C	—	2.84 in.	—
<u>SFC44T15K291B-F</u>	No	15 μ F	440V	-10%/+10%	-40°C	70°C	1.91 in.	2.91 in.	2.91 in.
<u>SFA44T15K388B-F</u>	No	15 μ F	440V	-10%/+10%	-40°C	70°C	1.31 in.	3.88 in.	2.16 in.
<u>SFP44T17.5K284B-F</u>	No	17.5 μ F	440V	-10%/+10%	-40°C	70°C	—	2.84 in.	—
<u>SFC44T17.5K291B-F</u>	No	17.5 μ F	440V	-10%/+10%	-40°C	70°C	1.91 in.	2.91 in.	2.91 in.
<u>SFP44T20K284B-F</u>	No	20 μ F	440V	-10%/+10%	-40°C	70°C	—	2.84 in.	—
<u>SFC44T20K391B-F</u>	No	20 μ F	440V	-10%/+10%	-40°C	70°C	1.91 in.	3.91 in.	2.91 in.
<u>SFS44T25K291B-F</u>	No	25 μ F	440V	-10%/+10%	-40°C	70°C	—	2.91 in.	—
<u>SFC44T25K391B-F</u>	No	25 μ F	440V	-10%/+10%	-40°C	70°C	1.91 in.	3.91 in.	2.91 in.

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>SFS44T30K291B-F</u>	No	30 μ F	440V	-10%/+10%	-40°C	70°C	—	2.91 in.	—
<u>SFC44T30K391B-F</u>	No	30 μ F	440V	-10%/+10%	-40°C	70°C	1.91 in.	3.91 in.	2.91 in.
<u>SFT44T35K291B-F</u>	No	35 μ F	440V	-10%/+10%	-40°C	70°C	—	2.91 in.	—
<u>SFD44T35K391B-F</u>	No	35 μ F	440V	-10%/+10%	-40°C	70°C	1.97 in.	3.91 in.	3.66 in.
<u>SFT44T40K391B-F</u>	No	40 μ F	440V	-10%/+10%	-40°C	70°C	—	3.91 in.	—
<u>SFD44T40K391B-F</u>	No	40 μ F	440V	-10%/+10%	-40°C	70°C	1.97 in.	3.91 in.	3.66 in.
<u>SFT44T45K391B-F</u>	No	45 μ F	440V	-10%/+10%	-40°C	70°C	—	3.91 in.	—
<u>SFD44T45K391B-F</u>	No	45 μ F	440V	-10%/+10%	-40°C	70°C	1.97 in.	3.91 in.	3.66 in.
<u>SFT44T50K391B-F</u>	No	50 μ F	440V	-10%/+10%	-40°C	70°C	—	3.91 in.	—
<u>SFD44T50K391B-F</u>	No	50 μ F	440V	-10%/+10%	-40°C	70°C	1.97 in.	3.91 in.	3.66 in.
<u>SFT44T55K391B-F</u>	No	55 μ F	440V	-10%/+10%	-40°C	70°C	—	3.91 in.	—

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>SFD44T55K391B-F</u>	No	55 μ F	440V	-10%/+10%	-40°C	70°C	1.97 in.	3.91 in.	3.66 in.
<u>SFT44T60K475B-F</u>	No	60 μ F	440V	-10%/+10%	-40°C	70°C	—	4.75 in.	—
<u>SFD44T60K391B-F</u>	No	60 μ F	440V	-10%/+10%	-40°C	70°C	1.97 in.	3.91 in.	3.66 in.
<u>SFA66T1K219B-F</u>	No	1 μ F	660V	-10%/+10%	-40°C	70°C	1.31 in.	2.19 in.	2.16 in.
<u>SFA66T1K156B-F</u>	No	1 μ F	660V	-10%/+10%	-40°C	70°C	1.31 in.	1.56 in.	2.16 in.
<u>SFP66T2K238B-F</u>	No	2 μ F	660V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>SFA66T2K219B-F</u>	No	2 μ F	660V	-10%/+10%	-40°C	70°C	1.31 in.	2.19 in.	2.16 in.
<u>SFA66T2K156B-F</u>	No	2 μ F	660V	-10%/+10%	-40°C	70°C	1.31 in.	1.56 in.	2.16 in.
<u>SFP66T3K238B-F</u>	No	3 μ F	660V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>SFA66T3K288B-F</u>	No	3 μ F	660V	-10%/+10%	-40°C	70°C	1.31 in.	2.88 in.	2.16 in.
<u>SFA66T4K288B-F</u>	No	4 μ F	660V	-10%/+10%	-40°C	70°C	1.31 in.	2.88 in.	2.16 in.

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>SFP66T5K238B-F</u>	No	5 μ F	660V	-10%/+10%	-40°C	70°C	—	2.38 in.	—
<u>SFA66T5K388B-F</u>	No	5 μ F	660V	-10%/+10%	-40°C	70°C	1.31 in.	3.88 in.	2.16 in.
<u>SFA66T6K388B-F</u>	No	6 μ F	660V	-10%/+10%	-40°C	70°C	1.31 in.	3.88 in.	2.16 in.
<u>SFP66T7.5K284B-F</u>	No	7.5 μ F	660V	-10%/+10%	-40°C	70°C	—	2.84 in.	—
<u>SFC66T8K291B-F</u>	No	8 μ F	660V	-10%/+10%	-40°C	70°C	1.91 in.	2.91 in.	2.91 in.
<u>SFA66T8K475B-F</u>	No	8 μ F	660V	-10%/+10%	-40°C	70°C	1.31 in.	4.75 in.	2.16 in.
<u>SFP66T10K284B-F</u>	No	10 μ F	660V	-10%/+10%	-40°C	70°C	—	2.84 in.	—
<u>SFC66T10K291B-F</u>	No	10 μ F	660V	-10%/+10%	-40°C	70°C	1.91 in.	2.91 in.	2.91 in.
<u>SFA66T10K475B-F</u>	No	10 μ F	660V	-10%/+10%	-40°C	70°C	1.31 in.	4.75 in.	2.16 in.
<u>SFC66T12K391B-F</u>	No	12 μ F	660V	-10%/+10%	-40°C	70°C	1.91 in.	3.91 in.	2.91 in.
<u>SFS66T12.5K291B-F</u>	No	12.5 μ F	660V	-10%/+10%	-40°C	70°C	—	2.91 in.	—

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>SFS66T15K384B-F</u>	No	15 μ F	660V	-10%/+10%	-40°C	70°C	—	3.84 in.	—
<u>SFC66T15K391B-F</u>	No	15 μ F	660V	-10%/+10%	-40°C	70°C	1.91 in.	3.91 in.	2.91 in.
<u>SFT66T17.5K391B-F</u>	No	17.5 μ F	660V	-10%/+10%	-40°C	70°C	—	3.91 in.	—
<u>SFC66T18K391B-F</u>	No	18 μ F	660V	-10%/+10%	-40°C	70°C	1.91 in.	3.91 in.	2.91 in.
<u>SFT66T20K391B-F</u>	No	20 μ F	660V	-10%/+10%	-40°C	70°C	—	3.91 in.	—
<u>SFD66T20K391B-F</u>	No	20 μ F	660V	-10%/+10%	-40°C	70°C	1.97 in.	3.91 in.	3.66 in.
<u>SFT66T25K475B-F</u>	No	25 μ F	660V	-10%/+10%	-40°C	70°C	—	4.75 in.	—
<u>SFD66T25K391B-F</u>	No	25 μ F	660V	-10%/+10%	-40°C	70°C	1.97 in.	3.91 in.	3.66 in.
<u>SFT66T30K475B-F</u>	No	30 μ F	660V	-10%/+10%	-40°C	70°C	—	4.75 in.	—
<u>SFD66T30K391B-F</u>	No	30 μ F	660V	-10%/+10%	-40°C	70°C	1.97 in.	3.91 in.	3.66 in.
<u>SFT66T35K475B-F</u>	No	35 μ F	660V	-10%/+10%	-40°C	70°C	—	4.75 in.	—

Part Number	For New Design	Capacitance	Voltage AC	Tolerance	Min Temp	Max Temp	Width	Height	Length
<u>SFD66T35K475B-F</u>	No	35 μ F	660V	-10%/+10%	-40°C	70°C	1.97 in.	4.75 in.	3.66 in.
<u>SFT66T40K475B-F</u>	No	40 μ F	660V	-10%/+10%	-40°C	70°C	—	4.75 in.	—
<u>SFD66T40K475B-F</u>	No	40 μ F	660V	-10%/+10%	-40°C	70°C	1.97 in.	4.75 in.	3.66 in.

Showing 1 to 322 of 322 entries.