

CentralTM Semiconductor Corp.

145 Adams Avenue, Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

MPS3704
MPS3705
MPS3706

SILICON NPN TRANSISTOR

JEDEC TO-92 CASE (EBC)

DESCRIPTION

The CENTRAL SEMICONDUCTOR MPS3704 thru MPS3706 are NPN silicon planar transistors for general purpose switching and amplifier applications.

MAXIMUM RATINGS ($T_A=25^\circ\text{C}$)

	SYMBOL	MPS3704 MPS3705	MPS3706	UNIT
Collector-Base Voltage	V_{CB0}	50	40	V
Collector-Emitter Voltage	V_{CE0}	30	20	V
Emitter-Base Voltage	V_{EB0}	5.0	5.0	V
Collector Current	I_C	600	600	mA
Power Dissipation	P_D	625	625	mW
Operating and Storage Junction Temperature	T_J, T_{STG}	-65 TO +150		$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$)

SYMBOL	TEST CONDITIONS	MPS3704		MPS3705		MPS3706		UNIT
		MIN	MAX	MIN	MAX	MIN	MAX	
I_{CB0}	$V_{CB}=20\text{V}$		100		100		100	nA
I_{EB0}	$V_{EB}=3.0\text{V}$		100		100		100	nA
BV_{CB0}	$I_C=100\mu\text{A}$	50		50		40		V
BV_{CE0}	$I_C=10\text{mA}$	30		30		20		V
BV_{EB0}	$I_E=100\mu\text{A}$	5.0		5.0		5.0		V
$V_{CE(SAT)}$	$I_C=100\text{mA}, I_B=5.0\text{mA}$		0.6		0.8		1.0	V
$V_{BE(ON)}$	$V_{CE}=2.0\text{V}, I_C=100\text{mA}$	0.5	1.0	0.5	1.0	0.5	1.0	V
h_{FE}	$V_{CE}=2.0\text{V}, I_C=50\text{mA}$	100	300	50	100	30	600	
f_T	$V_{CE}=2.0\text{V}, I_C=50\text{mA}, f=20\text{MHz}$	100		100		100		MHz
C_{ob}	$V_{CB}=10\text{V}, I_E=0, f=1.0\text{MHz}$		12		12		12	pF

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix " TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centrasemi.com

Worldwide Field Representatives:
www.centrasemi.com/wwreps

Worldwide Distributors:
www.centrasemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centrasemi.com/terms