

MPSA75  
MPSA76  
MPSA77

**SILICON  
PNP DARLINGTON TRANSISTORS**



**TO-92 CASE**



[www.centralemi.com](http://www.centralemi.com)

**DESCRIPTION:**

The CENTRAL SEMICONDUCTOR MPSA75 series devices are silicon PNP Darlington transistors, manufactured by the epitaxial planar process, designed for applications requiring extremely high gain.

**MARKING: FULL PART NUMBER**

**MAXIMUM RATINGS:** ( $T_A=25^\circ\text{C}$ )

|                                            |
|--------------------------------------------|
| Collector-Base Voltage                     |
| Collector-Emitter Voltage                  |
| Emitter-Base Voltage                       |
| Continuous Collector Current               |
| Power Dissipation                          |
| Operating and Storage Junction Temperature |
| Thermal Resistance                         |

| SYMBOL         | MPSA75 | MPSA76      | MPSA77 | UNITS              |
|----------------|--------|-------------|--------|--------------------|
| $V_{CBO}$      | 40     | 50          | 60     | V                  |
| $V_{CES}$      | 40     | 50          | 60     | V                  |
| $V_{EBO}$      |        | 10          |        | V                  |
| $I_C$          |        | 500         |        | mA                 |
| $P_D$          |        | 625         |        | mW                 |
| $T_J, T_{stg}$ |        | -65 to +150 |        | $^\circ\text{C}$   |
| $\Theta_{JA}$  |        | 200         |        | $^\circ\text{C/W}$ |

**ELECTRICAL CHARACTERISTICS:** ( $T_A=25^\circ\text{C}$ )

| SYMBOL        | TEST CONDITIONS                        | MPSA75 |     | MPSA76 |     | MPSA77 |     | UNITS |
|---------------|----------------------------------------|--------|-----|--------|-----|--------|-----|-------|
|               |                                        | MIN    | MAX | MIN    | MAX | MIN    | MAX |       |
| $I_{CBO}$     | $V_{CB}=30\text{V}$                    | -      | 100 | -      | -   | -      | -   | nA    |
| $I_{CBO}$     | $V_{CB}=40\text{V}$                    | -      | -   | -      | 100 | -      | -   | nA    |
| $I_{CBO}$     | $V_{CB}=50\text{V}$                    | -      | -   | -      | -   | -      | 100 | nA    |
| $I_{CES}$     | $V_{CE}=30\text{V}$                    | -      | 500 | -      | -   | -      | -   | nA    |
| $I_{CES}$     | $V_{CB}=40\text{V}$                    | -      | -   | -      | 500 | -      | -   | nA    |
| $I_{CES}$     | $V_{CB}=50\text{V}$                    | -      | -   | -      | -   | -      | 500 | nA    |
| $I_{EBO}$     | $V_{EB}=10\text{V}$                    | -      | 100 | -      | 100 | -      | 100 | nA    |
| $BV_{CBO}$    | $I_C=100\mu\text{A}$                   | 40     | -   | 50     | -   | 60     | -   | V     |
| $BV_{CES}$    | $I_C=100\mu\text{A}$                   | 40     | -   | 50     | -   | 60     | -   | V     |
| $V_{CE(SAT)}$ | $I_C=100\text{mA}, I_B=0.1\text{mA}$   | -      | 1.5 | -      | 1.5 | -      | 1.5 | V     |
| $V_{BE(ON)}$  | $V_{CE}=5.0\text{V}, I_B=100\text{mA}$ | -      | 2.0 | -      | 2.0 | -      | 2.0 | V     |
| $h_{FE}$      | $V_{CE}=5.0\text{V}, I_C=10\text{mA}$  | 10K    | -   | 10K    | -   | 10K    | -   |       |
| $h_{FE}$      | $V_{CE}=5.0\text{V}, I_C=100\text{mA}$ | 10K    | -   | 10K    | -   | 10K    | -   |       |
| $f_T$         | $V_{CE}=5.0\text{V}, I_C=10\text{mA}$  | 125    | -   | 125    | -   | 125    | -   | MHz   |


R1 (18-March 2014)

MPSA75  
MPSA76  
MPSA77

SILICON  
PNP DARLINGTON TRANSISTORS



#### TO-92 CASE - MECHANICAL OUTLINE



| DIMENSIONS |        |       |             |      |
|------------|--------|-------|-------------|------|
| SYMBOL     | INCHES |       | MILLIMETERS |      |
|            | MIN    | MAX   | MIN         | MAX  |
| A (DIA)    | 0.175  | 0.205 | 4.45        | 5.21 |
| B          | 0.170  | 0.210 | 4.32        | 5.33 |
| C          | 0.500  | -     | 12.70       | -    |
| D          | 0.016  | 0.022 | 0.41        | 0.56 |
| E          | 0.100  |       | 2.54        |      |
| F          | 0.050  |       | 1.27        |      |
| G          | 0.125  | 0.165 | 3.18        | 4.19 |
| H          | 0.080  | 0.105 | 2.03        | 2.67 |
| I          | 0.015  |       | 0.38        |      |

TO-92 (REV: R1)

#### LEAD CODE:

- 1) Emitter
- 2) Base
- 3) Collector

MARKING:  
FULL PART NUMBER


R1 (18-March 2014)

MPSA75  
MPSA76  
MPSA77

SILICON  
PNP DARLINGTON TRANSISTORS



## TYPICAL ELECTRICAL CHARACTERISTICS



R1 (18-March 2014)

## OUTSTANDING SUPPORT AND SUPERIOR SERVICES



---

### PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

---

### DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

---

### REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix " TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

---

### CONTACT US

#### Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.  
145 Adams Avenue  
Hauppauge, NY 11788 USA  
Main Tel: (631) 435-1110  
Main Fax: (631) 435-1824  
Support Team Fax: (631) 435-3388  
[www.centrasemi.com](http://www.centrasemi.com)

**Worldwide Field Representatives:**  
[www.centrasemi.com/wwreps](http://www.centrasemi.com/wwreps)

**Worldwide Distributors:**  
[www.centrasemi.com/wwdistributors](http://www.centrasemi.com/wwdistributors)

---

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: [www.centrasemi.com/terms](http://www.centrasemi.com/terms)