

SCRs (Silicon Controlled Rectifiers)
Metal/Plastic Packages
0.8 to 110 Amperes RMS
15 to 1200 Volts

I_T (AMPS)	0.8					
@ T_C (°C)	55	55	55	55	60	
I_{TSM} (AMPS)	6.0	6.0	6.0	6.0	10	
CASE	 TO-18				 TO-92 Pinout C G A	 TO-92 Pinout A G C
V_{RRM} (VOLTS)						
15	2N876	2N884				
30	2N877	2N885	2N3001	2N3005	2N5060	BRX44*
60	2N878	2N886	2N3002	2N3006	2N5061	BRX45*
100	2N879	2N887	2N3003	2N3007	2N5062	BRX46*
150	2N880	2N888			2N5063	
200	2N881	2N889	2N3004	2N3008	2N5064	BRX47*
300	2N882	2N890			2N6564	BRX48*
400	2N883	2N891			2N6565	BRX49*

I_{GT}	200μA	20μA	20μA	200μA	200μA	200μA
V_{GT}	0.8V	0.7V	0.7V	0.8V	0.8V	0.8V
I_H	5.0mA	5.0mA	3.0mA	5.0mA	5.0mA	5.0mA

* TO-92-18R lead forming available. Please consult factory.

SCRs

(Continued)

I_T (AMPS)	0.8				
@ T_C (°C)	60				
I_{TSM} (AMPS)	10				
CASE	 TO-92 Pinout A G C			 TO-92 Pinout C G A	
V_{RRM} (VOLTS)					
30	C103Y*				
60	C103YY*				
100	C103A*				
200	C103B*	CS55B*	CS55BZ*	CS92B	CS92BZ
400		CS55D*	CS55DZ*	CS92D	CS92DZ
600				CS92M	CS92MZ
800				CS92N	CS92NZ

I_{GT}	200μA	200μA	20μA	200μA	20μA
V_{GT}	0.8V	0.8V	0.8V	0.8V	0.8V
I_H	5.0mA	5.0mA	5.0mA	5.0mA	5.0mA

* TO-92-18R lead forming available. Please consult factory.

SCRs




(Continued)

I_T (AMPS)	1.0		1.6		
@ T_C (°C)	90	90	70	70	70
I_{TSM} (AMPS)	10	10	15	15	15
	TO-18				
CASE	TO-18		TO-39		
V_{RRM} (VOLTS)					
25					2N2322
50			2N1595	2N1595A	2N2323
100			2N1596	2N1596A	2N2324
150					2N2325
200	CS18B	CS18BZ	2N1597	2N1597A	2N2326
250					2N2327
300			2N1598	2N1598A	2N2328
400	CS18D	CS18DZ	2N1599	2N1599A	2N2329
600	CS18M	CS18MZ			
800	CS18N	CS18NZ			

I_{GT}	200μA	20μA	10mA	2.0mA	200μA
V_{GT}	0.8V	0.8V	2.0V	2.0V	0.8V
I_H	5.0mA	5.0mA	20mA	5.0mA	2.0mA

SCRs



(Continued)

I_T (AMPS)	1.6	4.0			
@ T_C (°C)	55	90	85	85	30
I_{TSM} (AMPS)	6.0	35	30	30	20
					
CASE	TO-18	TO-39	TO-202	TO-202-2	TO-202
V_{RRM} (VOLTS)					
50	2N6605				
60	2N6606				
100	2N6607				C106A1
200	2N6608	CS39-4B	CS202-4B	CS202-4B-2	C106B1
300					C106C1
400		CS39-4D	CS202-4D	CS202-4D-2	C106D1
500					C106E1
600		CS39-4M	CS202-4M	CS202-4M-2	C106M1
800		CS39-4N			

I_{GT}	200 μ A	200 μ A	200 μ A	200 μ A	200 μ A
V_{GT}	0.8V	0.8V	0.8V	0.8V	0.8V
I_H	5.0mA	5.0mA	5.0mA	5.0mA	5.0mA

SCRs



(Continued)

I_T (AMPS)	8.0			10	12
@ T_C (°C)	90	100	100	90	90
I_{TSM} (AMPS)	90	100	100	100	120
					
CASE	TO-220	TO-64		TO-220	
V_{RRM} (VOLTS)					
25		2N1770,A	2N4167		
50		2N1771,A	2N4168		
100		2N1772,A	2N4169		
150		2N1773,A			
200	CS220-8B	2N1774,A	2N4170	CS220-10B	CS220-12B
250		2N1775,A			
300		2N1776,A	2N4171		
400	CS220-8D	2N1777,A	2N4172	CS220-10D	CS220-12D
500		2N1778,A	2N4173		
600	CS220-8M	2N2619	2N4174	CS220-10M	CS220-12M
800	CS220-8N			CS220-10N	CS220-12N
1000					CS220-12P

I_{GT}	15mA	15mA	30mA	15mA	15mA
V_{GT}	1.5V	1.5V	1.5V	1.5V	1.5V
I_H	30mA	25mA	30mA	30mA	30mA

SCRs

(Continued)




I_T (AMPS)	16			25	
@ T_C (°C)	90	90	90	70	90
I_{TSM} (AMPS)	200	200	160	200	250
CASE					
	TO-3 50 mil			TO-48	
V_{RRM} (VOLTS)					
25				2N681,A	
50				2N682,A	
100	2N3668			2N683,A	
150				2N684,A	
200	2N3669	CS3-16B	CS220-16B*	2N685,A	CS220-25B
250				2N686,A	
300				2N687,A	
400	2N3670	CS3-16D	CS220-16D*	2N688,A	CS220-25D
500				2N689,A	
600	2N4103	CS3-16M	CS220-16M*	2N690,A	CS220-25M
700				2N691,A	
800		CS3-16N	CS220-16N*	2N692,A	CS220-25N
1000			CS220-16P*		CS220-25P
1200					CS220-25PB

I_{GT}	40mA	25mA	25mA	40mA	40mA
V_{GT}	2.0V	2.0V	1.5V	2.0V	1.5V
I_H	50mA	40mA	40mA	50mA	50mA

* Not recommended for new designs.

SCRs

(Continued)





I_T (AMPS)	30	35	
@ T_C (°C)	85	75	85
I_{TSM} (AMPS)	400	330	400
			
CASE	TO-218 ISOL	TO-48	TO-218
V_{RRM} (VOLTS)	ISOLATED		
200*	CS218I-30B	CS48-35B	CS218-35B*
400*	CS218I-30D	CS48-35D	CS218-35D*
600	CS218I-30M	CS48-35M	CS218-35M*
800	CS218I-30N	CS48-35N	CS218-35N*
1000	CS218I-30P	CS48-35P	CS218-35P*
1200	CS218I-30PB	CS48-35PB	CS218-35PB*

I_{GT}	50mA	40mA	50mA
V_{GT}	1.5V	1.5V	1.5V
I_H	75mA	100mA	75mA

* Not recommended for new designs.

SCRs

(Continued)

I_T (AMPS)	50	55	70	110	
@ T_C (°C)	75	75	110	80	80
I_{TSM} (AMPS)	500	500	1000	1600	1600
					
CASE	TO-218 ISOL	TO-218	TO-65	TO-83	TO-94
V_{RRM} (VOLTS)	ISOLATED				
200	CS218I-50B	CS218-55B*	CS65-70B	CS83-110B	CS94-110B
400	CS218I-50D	CS218-55D*	CS65-70D	CS83-110D	CS94-110D
600	CS218I-50M	CS218-55M*	CS65-70M	CS83-110M	CS94-110M
800	CS218I-50N	CS218-55N*	CS65-70N	CS83-110N	CS94-110N
1000	CS218I-50P	CS218-55P*	CS65-70P	CS83-110P	CS94-110P
1200	CS218I-50PB	CS218-55PB*	CS65-70PB	CS83-110PB	CS94-110PB

I_{GT}	80mA	80mA	100mA	100mA	100mA
V_{GT}	1.5V	1.5V	3.0V	3.0V	3.0V
I_H	150mA	150mA	200mA	100mA	100mA

* Not recommended for new designs.