



CYPRESS

CY29949

2.5V or 3.3V 200-MHz 1:15 Clock Distribution Buffer

Features


- 2.5V or 3.3V operation
- 200-MHz clock support
- LVPECL or LVCMOS/LVTTL clock input
- LVCMOS-/LVTTL-compatible outputs
- 15 clock outputs: drive up to 30 clock lines
- 1X and 1/2X configurable outputs
- Output three-state control
- 350 ps max. output-to-output skew
- Pin compatible with MPC949, MPC9449
- Available in Commercial and Industrial temp. range
- 52-pin TQFP package

Description

The CY29949 is a low-voltage 200-MHz clock distribution buffer with the capability to select either a differential LVPECL or LVCMOS/LVTTL compatible input clocks. These clock sources can be used to provide for test clocks as well as the primary system clocks. All other control inputs are LVCMOS/LVTTL compatible. The 15 outputs are LVCMOS or LVTTL compatible and can drive 50Ω series or parallel terminated transmission lines. For series terminated transmission lines, each output can drive one or two traces giving the device an effective fanout of 1:30.

The CY29949 is capable of generating 1X and 1/2X signals from a 1X source. These signals are generated and retimed internally to ensure minimal skew between the 1X and 1/2X signals. SEL(A:D) inputs allow flexibility in selecting the ratio of 1X to 1/2X outputs.

The CY29949 outputs can also be three-stated via the MR/OE# input. When MR/OE# is set HIGH, it resets the internal flip-flops and three-states the outputs.



Pin Description^[1]

| Pin | Name | PWR | I/O | Description |
|--|-----------|------|-------|--|
| 6 | PECL_CLK | | I, PD | PECL Input Clock |
| 7 | PECL_CLK# | | I, PU | PECL Input Clock |
| 4, 5 | TCLK(0,1) | | I, PU | External Reference/Test Clock Input |
| 49, 51 | QA(1,0) | VDDC | O | Clock Outputs |
| 42, 44, 46 | QB(2:0) | VDDC | O | Clock Outputs |
| 31, 33, 35, 37 | QC(3:0) | VDDC | O | Clock Outputs |
| 16, 18, 20, 22, 24, 28 | QD(5:0) | VDDC | O | Clock Outputs |
| 9, 10, 11, 12 | DSEL(A:D) | | I, PD | Divider Select Inputs. When HIGH, selects ÷2 input divider. When LOW, selects ÷1 input divider. |
| 2 | TCLK_SEL | | I, PD | TCLK Select Input. When LOW, TCLK0 clock is selected and when HIGH TCLK1 is selected. |
| 8 | PCLK_SEL | | I, PD | PECL Select Input. When HIGH, PECL clock is selected and when LOW TCLK(0,1) is selected |
| 1 | MR/OE# | | I, PD | Output Enable Input. When asserted LOW, the outputs are enabled and when asserted HIGH, internal flip-flops are reset and the outputs are three-stated. If more than 1 bank is being used in /2 mode, a reset must be performed (MR/OE# asserted high) after power-up to ensure that all internal flip flops are set to the same state. |
| 17, 21, 25, 32, 36, 41, 45, 50 | VDDC | | | 2.5V or 3.3V Power Supply for Output Clock Buffers |
| 3 | VDD | | | 2.5V or 3.3V Power Supply |
| 13, 15, 19, 23, 29, 30, 34, 38, 43, 47, 48, 52 | VSS | | | Common Ground |
| 14, 26, 27, 39, 40, | NC | | | Not Connected |

Note:

1. PD = internal pull-down, PU = internal pull-up.

Maximum Ratings^[2]

Maximum Input Voltage Relative to V_{SS} : $V_{SS} - 0.3V$
 Maximum Input Voltage Relative to V_{DD} : $V_{DD} + 0.3V$
 Storage Temperature: $-65^{\circ}C$ to $+150^{\circ}C$
 Operating Temperature: $-40^{\circ}C$ to $+85^{\circ}C$
 Maximum ESD Protection 2 kV
 Maximum Power Supply: 5.5V
 Maximum Input Current: ± 20 mA

This device contains circuitry to protect the inputs against damage due to high static voltages or electric field; however, precautions should be taken to avoid application of any voltage higher than the maximum rated voltages to this circuit. For proper operation, V_{in} and V_{out} should be constrained to the range:

$$V_{SS} < (V_{in} \text{ or } V_{out}) < V_{DD}$$

Unused inputs must always be tied to an appropriate logic voltage level (either V_{SS} or V_{DD}).

DC Parameters ($V_{DD} = V_{DDC} = 3.3V \pm 10\%$ or $2.5V \pm 5\%$, over the specified temperature range)



| Parameter | Description | Conditions | Min. | Typ. | Max. | Unit |
|-----------|--|--|----------------|------|----------------|----------|
| V_{IL} | Input Low Voltage | $V_{DD} = 3.3V$, PECL_CLK single ended | 1.49 | – | 1.825 | V |
| | | $V_{DD} = 2.5V$, PECL_CLK single ended | 1.10 | – | 1.45 | |
| | | All other inputs | V_{SS} | – | 0.8 | |
| V_{IH} | Input High Voltage | $V_{DD} = 3.3V$, PECL_CLK single ended | 2.135 | – | 2.42 | V |
| | | $V_{DD} = 2.5V$, PECL_CLK single ended | 1.75 | – | 2.0 | |
| | | All other inputs | 2.0 | – | V_{DD} | |
| I_{IL} | Input Low Current ^[3] | | – | – | –100 | μA |
| I_{IH} | Input High Current ^[3] | | – | – | 100 | |
| V_{PP} | Peak-to-Peak Input Voltage PECL_CLK | | 300 | – | 1000 | mV |
| V_{CMR} | Common Mode Range ^[4] PECL_CLK | $V_{DD} = 3.3V$ | $V_{DD} - 2.0$ | – | $V_{DD} - 0.6$ | V |
| | | $V_{DD} = 2.5V$ | $V_{DD} - 1.2$ | – | $V_{DD} - 0.6$ | |
| V_{OL} | Output Low Voltage ^[5] | $I_{OL} = 20$ mA | – | – | 0.4 | V |
| V_{OH} | Output High Voltage ^[5] | $I_{OH} = -20$ mA, $V_{DD} = 3.3V$ | 2.5 | – | – | V |
| | | $I_{OH} = -20$ mA, $V_{DD} = 2.5V$ | 1.8 | – | – | |
| I_{DDQ} | Quiescent Supply Current | | – | 5 | 7 | mA |
| I_{DD} | Dynamic Supply Current | $V_{DD} = 3.3V$, Outputs @ 100 MHz, CL = 30 pF | – | 200 | – | mA |
| | | $V_{DD} = 3.3V$, Outputs @ 160 MHz, CL = 30 pF | – | 330 | – | |
| | | $V_{DD} = 2.5V$, Outputs @ 100 MHz, CL = 30 pF | – | 140 | – | |
| | | $V_{DD} = 2.5V$, Outputs @ 160 MHz, CL = 30 pF | – | 235 | – | |
| Z_{out} | Output Impedance | $V_{DD} = 3.3V$ | 12 | 15 | 18 | Ω |
| | | $V_{DD} = 2.5V$ | 14 | 18 | 22 | |
| C_{in} | Input Capacitance | | – | 4 | – | pF |

Notes:





- Multiple Supplies:** The voltage on any input or I/O pin cannot exceed the power pin during power-up. Power supply sequencing is NOT required.
- Inputs have pull-up/pull-down resistors that effect input current.
- The V_{CMR} is the difference from the most positive side of the differential input signal. Normal operation is obtained when the "High" input is within the V_{CMR} range and the input lies within the V_{PP} specification.
- Driving series or parallel terminated 50 Ω (or 50 Ω to $V_{DD}/2$) transmission lines.

AC Parameters ($V_{DD} = V_{DDC} = 3.3V \pm 10\%$ or $2.5V \pm 5\%$, over the specified temperature range)^[6]

| Parameter | Description | Conditions | Min. | Typ. | Max. | Unit |
|------------|---|----------------------------------|------|------|------|------|
| Fmax | Input Frequency ^[7] | $V_{DD} = 3.3V$ | – | – | 200 | MHz |
| | | $V_{DD} = 2.5V$ | – | – | 170 | |
| Tpd | PECL_CLK to Q Delay ^[7] | $V_{DD} = 3.3V$ | 4.0 | – | 8.6 | ns |
| | TCLK to Q Delay ^[7] | | 4.2 | – | 10.5 | |
| | PECL_CLK to Q Delay ^[7] | $V_{DD} = 2.5V$ | 6.0 | – | 10.6 | |
| | TCLK to Q Delay ^[7] | | 6.2 | – | 10.5 | |
| FoutDC | Output Duty Cycle ^[7, 8] | Measured at $V_{DD}/2$ | 45 | – | 55 | % |
| tpZL, tpZH | Output Enable Time (all outputs) | | 2 | – | 10 | ns |
| tpLZ, tpHZ | Output Disable Time (all outputs) | | 2 | – | 10 | ns |
| Tskew | Output-to-Output Skew ^[7, 9] | | – | 250 | 350 | ps |
| Tskew(pp) | Part-to-Part Skew ^[10] | PECL_CLK to Q | – | 1.5 | 2.75 | ns |
| | | TCLK to Q | – | 2.0 | 4.0 | |
| Tr/Tf | Output Clocks Rise/Fall Time ^[9] | 0.8V to 2.0V, $V_{DD} = 3.3V$ | 0.10 | – | 1.0 | ns |
| | | 0.6V to 1.8V, $V_{DD} = 2.5V$ | 0.10 | – | 1.3 | |


Figure 1. LVC MOS_CLK CY29949 Test Reference for $V_{CC} = 3.3V$ and $V_{CC} = 2.5V$

Figure 2. PECL_CLK CY29949 Test Reference for $V_{CC} = 3.3V$ and $V_{CC} = 2.5V$
Notes:


6. Parameters are guaranteed by design and characterization. Not 100% tested in production. All parameters specified with loaded outputs.
7. Outputs driving 50Ω transmission lines.
8. 50% input duty cycle.
9. See *Figures 1 and 2*.
10. Part-to-Part skew at a given temperature and voltage.


Figure 3. Propagation Delay (TPD) Test Reference

Figure 4. LVCMOS Propagation Delay (TPD) Test Reference

Figure 5. Output Duty Cycle (FoutDC)

Figure 6. Output-to-Output Skew tsk(0)
Ordering Information

| Part Number | Package Type | Production Flow |
|-------------|-----------------------------|----------------------------|
| CY29949AI | 52 Pin TQFP | Industrial, -40°C to +85°C |
| CY29949AIT | 52 Pin TQFP - Tape and Reel | Industrial, -40°C to +85°C |
| CY29949AC | 52 Pin TQFP | Commercial, 0°C to +70°C |
| CY29949ACT | 52 Pin TQFP - Tape and Reel | Commercial, 0°C to +70°C |

Package Drawing and Dimensions

52-Lead Thin Plastic Quad Flat Pack (10 x 10 x 1.0 mm) A52B



All product and company names mentioned in this document may be the trademarks of their respective holders.

Document History Page

Document Title: CY29949 2.5V or 3.3V 200-MHz 1:15 Clock Distribution Buffer
Document Number: 38-07289

| REV. | ECN NO. | Issue Date | Orig. of Change | Description of Change |
|------|---------|------------|-----------------|---|
| ** | 111100 | 02/01/02 | BRK | New data sheet |
| *A | 116783 | 08/14/02 | HWT | Added commercial temperature range to the Ordering Information table |
| *B | 118463 | 09/09/02 | HWT | Corrected the package diagram from 52 LQFP to 52 TQFP |
| *C | 122881 | 12/22/02 | RBI | Added power-up requirements to Maximum Ratings |
| *D | 130132 | 11/07/03 | RGL | Fixed block diagram and MR/OE# description in the Pin Description table |