EAO – Your Expert Partner for **Human Machine Interfaces**

K14-131.221081 - Illuminated pushbutton

K14-131.221081 - Illuminated pushbutton



Attention: The preview is based on a sample product. This can differ from your current configuration.

Mounting

 $\begin{array}{ll} \text{Design} & \text{flush} \\ \text{Mounting cut-out} & \varnothing \ 30,5 \ \text{mm} \end{array}$

Front

Front dimension Ø 35 mm Front shape round

Other Attributes

Weight 0.031 kg
Operation current 4/7 mA ±15 %
Operating voltage 24 V AC/DC

Operating-/Indication part

Lens illumination illuminative
Lens colour green
Lens material Plastic
Lens optics transparent
Lens profile flush

IP-Rating

Front protection IP67

Connection Method

Terminal Soldering terminal

Actuator

Switching action Momentary
Housing colour black
Housing material Plastic

Switching element

Switching system Snap-action switching element

Switching current 5 /

Contacts 1 NC + 1 NO

Contact material

Switching voltage 250 V AC

Illumination

LED colour green

Function


Illuminated pushbutton

e a o


EAO – Your Expert Partner for **Human Machine Interfaces**

K14-131.221081 - Illuminated pushbutton


Dimensions



Mounting cut-outs



Wiring diagram



Legend

Contacts: NC = Normally closed, NO = Normally open