



1915L 19" Touchscreen Monitor

[Overview](#)[Specifications](#)[Configurations](#)[Resources](#)

Overview

The Elo 1915L standard format touchscreen monitor is built to withstand the rigors of continuous public use with a rugged built-for-touch design. Its stylish, thin and modern look, coupled with a retail-focused feature set and is an attractive solution for commercial touchscreen monitor needs. The 1915L can be used in a wide variety of environments with its ability to register inputs from a finger, gloved hand or soft stylus with a fast and accurate response. The touchmonitor is available with Elo's industry-leading touch technologies and multiple mounting options to support most application uses.

Integrated touch.

The 1915L desktop LCD touchmonitor is available with a choice of Elo's single touch AccuTouch® five-wire resistive or IntelliTouch® surface acoustic wave (SAW), both with a dual serial/ USB touch interface.





Flexible mounting.

The Elo 1915L offers multiple mounting options to ensure installation flexibility including: wall- and pole-mount via standard VESA mount patterns as well as tabletop accommodations with the use of the desktop stand. Capped through-mount holes on the base of the touchmonitor ensure table-top security.

Commercial grade.

The 1915L touchscreen monitor delivers the quality and reliability Elo is known for and is backed by our three-year standard warranty. All our products go through rigorous reliability testing (over 20 tests) to deliver 50,000 MTBF.



Other features.

- Affordability paired with Elo quality OR Consumer-grade pricing with Elo commercial-grade reliability
- Long-lasting product cycle
- Dual serial/USB interface
- Mounting holes on stand bottom for tabletop security
- Digital on-screen display (OSD)
- Three-year standard warranty
- Designed for touch features such as a stable tilt stand
- Sealed touchscreen against dirt, dust and liquid
- Removable stand and VESA mounting option
- Controls on the side rather than the front, plus lockout function for public use
- Worldwide agency approvals

Specifications

Part Number(s)	IntelliTouch - E266835 AccuTouch - E607608
Enclosure Color	Dark Gray
Touch Technology & Capacity	5-Wire Resistive (AccuTouch®) - Single-Touch SAW (IntelliTouch® Surface Acoustic Wave) - Single Touch
Surface Treatment	Anti-glare
Diagonal Size	19" diagonal, Active matrix TFT LCD (LED)
Aspect Ratio	5:4
Active Area (mm)	14.8" x 11.9" / 376.3mm x 301.1mm
Resolution	1280 x 1024
Other Supported Resolutions	1280 x 1024 at 60 or 75 Hz 1152 x 864 at 75 Hz 1024 x 768 at 60, 65, 70 or 75 Hz 832 x 624 at 75 Hz (Mac) 800 x 600 at 56, 60, 72 or 75 Hz 720 x 400 at 70 Hz 720 x 350 at 70 Hz 640 x 480 at 60, 66, 72 or 75 Hz
Viewing Angle	Horizontal: ±85° or 170° total / Vertical: ±80° or 160° total
Number of Colors	16.7 million
Brightness (typical)	LCD panel: 250 nits AccuTouch: 193 nits IntelliTouch: 225 nits
Response Time-total (typical)	5 msec
Contrast Ratio	1000:1
Input Video Format	Analog VGA
Input Video Signal Connector	Mini D-Sub 15-Pin VGA type
Power Supply	Internal AC, power cable-C5 type, optional external DC (power brick) Monitor input power signal specifications: 12VDC +/- 5%
Input Voltage	100-240VAC, 50/60Hz
Input Connector	Coaxial power jack (2.0mm (+0.0 -0.1mm) pin outer diameter, 6.4mm (+/- 0.3mm) barrel inner diameter, 8.8mm (+/- 0.3mm) Barrel depth)

Input Frequency	Horizontal: 31.5-80 kHz Vertical: 56.3-75 Hz
Adapter Input Connector	IEC 60320 C14
Adapter Input Voltage Range	100-240VAC, 50/60Hz
Power Consumption (Typical)	ON (monitor + 100V AC): 16.25W SLEEP (monitor + 100V AC): 1.19W OFF (monitor + 100V AC): 0.63W
On Screen Display	Controls (side): menu, up, down, select, power Settings: contrast, brightness, H/V position, RGB (color temp), clock, phase, recall Languages: English, German, Spanish, Japanese, French Lockouts: power, user controls
Monitor Dimensions (with Stand)	16.9" x 14.9" x 8.2" / 429mm x 379mm x 207mm
Shipping Box Dimensions	21.28" x 19.50" x 11.23" / 540mm x 495mm x 285mm
Weight (with stand)	17.4 lb / 7.9 kg
Shipping Weight (With stand)	25.8 lb / 11.7 kg
Operating Temperature	0°C to 40°C / 32°F to 104°F
Storage Temperature	-20°C to 60°C / -4°F to 140°F
Humidity	Operating: 20% to 80%; Storage: 10% to 90%
Sealability	Touchscreen sealed to bezel; Touchscreen sealed to LCD
MTBF	50,000 hours demonstrated
Stand Options	Tilt, remove
Mounting Options	100 mm VESA mount Threaded-through mounting holes, under stand
Other Features	Security lock receptacle
Warranty	3-year
Extended Warranty Options	4 year warranty coverage - Elo P/N: E898247 5 year warranty coverage - Elo P/N: E898449 3 year warranty coverage + AUR - Elo P/N: E898648 4 year warranty coverage + AUR - Elo P/N: E894921 5 year warranty coverage + AUR - Elo P/N: E895125
Regulatory approvals and declarations	UL, cUL, FCC, CE, VCCI, IC, RCM, Argentina S Mark, TUV, CCC, China RoHS
	User Guide CD Quick Installation Guide (QIG)

What's in the Box

AC Power Cord Mickey 1.8M BK EU/KOREA
AC Power Cord UL/SP-030+IS-034 1.8M BK
Cable A55336-000 USB A-B 1830mmBK
Cable DSUB-9PX2 1800mm BK W/PEBAG
Cable VGA PC99 1.8M BK

Replacement DC Power Supply

The monitor may also be powered with DC voltage. An optional 12V DC power brick, Elo P/N: E005277, is available at additional cost.

AC Power Cable

North American and EU AC power cables included (C5 type). For touchmonitors shipped to the UK, add a UK AC power cable at no cost by specifying Elo P/N: E540272.

USA: E042259
EU: E690013
UK: E235317

Optional Power Supply Brick

E217485 - Must also order appropriate following power cord-C14 Socket

Optional IntelliTouch Stylus Pen

Stylus pen with rubber tip, designed specifically for use with IntelliTouch surface wave touch technology. Part number D82064-000, available at additional cost.

Touch/Video/Audio/Accessory Cables:

Detachable touch and video cables are included

Optional Stand

Dark Grey - Elo P/N: E335194

Configurations (2)

Refine your search:

Touch Techn

Clear Filters

Compare



E607608

- Dark Gray
- Dual serial/USB
- Bezel
- Anti-glare

Compare



E266835

- Dark Gray
- Dual serial/USB
- Bezel
- Anti-glare



Resources (22)

Drawings and Certificates

Dimensional Drawing

[Go](#)

CAD Drawings

[Go](#)

Agency Approval Certificates

[Go](#)

EU Regulation 2019/2013

[Energy Efficiency Label](#)

Energy Efficiency Fiche

[Go](#)

WEEE Report

[Go](#)

Collateral

Spec Sheet

[Go](#)

User Guides

English

[Go](#)

French

[Go](#)

Italian

[Go](#)

German

[Go](#)

Simplified Chinese

[Go](#)

Traditional Chinese

[Go](#)

Japanese

[Go](#)

Spanish

[Go](#)

Korean

[Go](#)

Russian

[Go](#)

Quick Install Guide

[Go](#)

Quick Installation Guide (No Driver)

[Go](#)

Additional Support Resources

Extended Warranty Information

[Go](#)

Pixels and Image Sticking

[Go](#)

Download Drivers

[Go](#)

Get Started with Elo Today.
Contact Sales

elo

Products

Mobile Computers
Touchscreen Monitors
Touchscreen Signage
Open Frame Touchscreens
Touchscreen Computers
POS Terminals
Medical-Grade Touchscreens
Touchscreen Components
Touchscreen Display Modules
Accessories

Solutions

Essentials for Android
Point-of-Sale
Self-Service
Retail
Restaurant/QSR
Grocery
Healthcare
Touchscreen Signage
Corporate
Industry 4.0

About

Company
Team
Press
Events
Careers
Environment
How to Buy

Better Touch, Better Business.

Contact Sales at Elo.

Go Elo Today

Call Us

1 (408) 597 8000

EloView®
Elo Access™
Custom Products

Embedded OEM Solutions

Email Us
EloSales.NA@elotouch.com

Services

EloCare™
OS 360
Advance Unit Replacement
Accidental Damage Protection
Extended Warranty
On-Site Exchange
Professional Services

Support

Overview
Technical Support
Customer Service
Supplier Portal
Service & Repair
Downloads
Documentation
Warranty Information
Portal (E-Commerce)

Partners

Elo Elite Partner Program
Software & Hardware Partners
Elo ManRep Portal
Elo Distributor Portal