



## **Aluminum electrolytic capacitors**

Capacitors with 4-pin snap-in terminals and solder pins

**Series/Type:** B43514, B43524

**Date:** December 2006

### Long-life grade capacitors

#### Applications

- Frequency converters
- Professional switch-mode power supplies

#### Features

- Long useful life
- High reliability and high ripple current capability
- High volumetric efficiency
- Many different case sizes
- Pinning ensures correct insertion

#### Construction


- Charge/discharge-proof, polar
- Aluminum case, fully insulated
- Overload protection by safety vent in case

#### Terminals


- 4-pin snap-in terminals (6.3 mm and 4.5 mm length)
- Solder pin mounting on printed circuit boards, pins fit standardized spacings on PCB



B43514




B43524



## Specifications and characteristics in brief

Rated voltage $V_R$	350 ... 450 V DC	
Surge voltage $V_S$	$1.1 \cdot V_R$	
Rated capacitance $C_R$	330 ... 2200 $\mu$ F	
Capacitance tolerance	$\pm 20\% \triangle M$	
Leakage current $I_{leak}$ (5 min, 20 °C)	$I_{leak} \leq 0.3 \mu A \cdot \left( \frac{C_R}{\mu F} \cdot \frac{V_R}{V} \right)^{0.7} + 4 \mu A$	
Self-inductance ESL	Approx. 20 nH	
Useful life 105 °C, $V_R$ , $I_{AC,R}$ 85 °C, $V_R$ , $I_{AC,max}$ 40 °C, $V_R$ , $2.2 \cdot I_{AC,R}$	> 3000 h > 7000 h > 200000 h	Requirements: $\Delta C/C \leq \pm 30\%$ of initial value ESR $\leq 3$ times initial specified limit $I_{leak} \leq$ initial specified limit
Voltage endurance test 105 °C, $V_R$	2000 h	Post test requirements: $\Delta C/C \leq \pm 10\%$ of initial value ESR $\leq 1.3$ times initial specified limit $I_{leak} \leq$ initial specified limit
Vibration resistance test	To IEC 60068-2-6, test Fc: Displacement amplitude 0.35 mm, frequency range 10 ... 55 Hz, acceleration max. 5 g, duration $3 \times 2$ h. Capacitor mounted by its body which is rigidly clamped to the work surface.	
IEC climatic category	To IEC 60068-1: $V_R \leq 400$ V DC: 40/105/56 (–40 °C/+105 °C/56 days damp heat test) $V_R > 400$ V DC: 25/105/56 (–25 °C/+105 °C/56 days damp heat test)	
Detail specification	Similar to CECC 30301-808	
Sectional specification	IEC 60384-4	




## B43514, B43524

Extended temperature range – 105 °C


### Dimensional drawings

#### B43514, 4-pin snap-in terminals




Standard snap-in terminals: length  $(6.3 \pm 1)$  mm.  
Also available with length of  $(4.5 - 1)$  mm.

#### B43524, solder pins




Dimensions (mm)			Approx. weight (g)	Packing units (pcs.)
d +1	l ±2	l <sub>max</sub>		
35	50	54	63	60
35	60	64	76	36
35	70	74	88	36
35	80	84	101	36
35	100	104	126	36
40	40	44	71	33
40	50	54	89	33
40	60	64	107	33
40	70	74	125	33
40	80	84	143	33
40	100	104	178	33
45	40	—	90	28
45	50	—	113	28
45	60	—	136	28
45	70	—	158	28
45	80	—	181	28
45	100	—	226	28



Pole markings: Plus: +; Minus: –

All pin holes must be drilled into the PC-board, since the unconnected pins serve as mountings. These pins must be soldered to isolated pads or pads with the same potential as the negative pole (solder pin and 4-pin snap-in terminals).




## Packing of 4-pin snap-in terminal and solder pin capacitors



For ecological reasons the packing is pure cardboard.

## Ordering codes for terminal styles

4-pin snap-in terminal capacitors Version	Identification in 3rd block of ordering code
Standard terminals (6.3 ±1) mm	M000
Short terminals (4.5 – 1) mm	M007



**B43514, B43524**
**Extended temperature range – 105 °C**
**Overview of available types**

$V_R$ (V DC)	350	400	420	450
	Case dimensions $d \times l$ (mm)			
$C_R$ (μF)				
330				35 × 50 40 × 40
390		35 × 50	35 × 50 40 × 40	35 × 60 40 × 50
470	35 × 50	35 × 60 40 × 50 45 × 40	35 × 60 40 × 50	35 × 70 40 × 60 45 × 50
560	35 × 60 40 × 50	35 × 70 40 × 50	35 × 70 40 × 50	35 × 80 40 × 60 45 × 50
680	35 × 70 40 × 50	35 × 80 40 × 60 45 × 50	35 × 80 40 × 60 45 × 50	40 × 70 45 × 60
820	35 × 80 40 × 60	40 × 70 45 × 60	40 × 70 45 × 60	
1000	40 × 70 45 × 60	35 × 100 40 × 80 45 × 70	40 × 80 45 × 70	40 × 100 45 × 80
1200				45 × 100
1500	40 × 100 45 × 80	45 × 100	45 × 100	
2200	45 × 100			

The capacitance and voltage ratings listed above are available in different cases upon request.

Other voltage and capacitance ratings are also available upon request.

Capacitors with solder pins are only available in 35 and 40 mm case diameters.



### Technical data and ordering codes

$C_R$	Case dimensions	$ESR_{typ}$	$ESR_{max}$	$Z_{max}$	$I_{AC,max}$	$I_{AC,max}$	$I_{AC,R}$	Ordering code
100 Hz	d × l	100 Hz	100 Hz	10 kHz	100 Hz	100 Hz	100 Hz	(composition see below)
20 °C	mm	20 °C	20 °C	20 °C	60 °C	85 °C	105 °C	
μF		mΩ	mΩ	mΩ	A	A	A	

#### $V_R = 350 \text{ V DC}$

470	35 × 50	190	280	220	5.9	4.4	2.2	B435*4A4477M00#
560	35 × 60	160	230	190	6.9	5.1	2.6	B435*4A4567M00#
560	40 × 50	160	230	190	6.8	5.1	2.5	B435*4C4567M00#
680	35 × 70	140	190	150	7.5	5.6	2.8	B435*4A4687M00#
680	40 × 50	140	190	150	7.0	5.2	2.6	B435*4C4687M00#
820	35 × 80	110	160	130	8.7	6.5	3.3	B435*4A4827M00#
820	40 × 60	110	160	130	8.2	6.1	3.1	B435*4C4827M00#
1000	40 × 70	90	130	110	9.6	7.2	3.6	B435*4A4108M00#
1000	45 × 60	90	130	110	9.1	6.8	3.4	B43514C4108M00#
1500	40 × 100	60	90	70	13.6	10.0	5.1	B435*4A4158M00#
1500	45 × 80	60	90	70	12.4	9.2	4.6	B43514C4158M00#
2200	45 × 100	50	60	50	16.4	12.0	6.1	B43514A4228M00#

#### $V_R = 400 \text{ V DC}$

390	35 × 50	230	330	270	5.3	4.0	2.0	B435*4A9397M00#
470	35 × 60	190	280	220	6.3	4.7	2.4	B435*4A9477M00#
470	40 × 50	190	280	220	6.2	4.6	2.3	B435*4C9477M00#
470	45 × 40	190	280	220	5.8	4.3	2.2	B43514E9477M00#
560	35 × 70	160	230	190	6.8	5.1	2.6	B435*4A9567M00#
560	40 × 50	160	230	190	6.3	4.7	2.4	B435*4C9567M00#
680	35 × 80	140	190	150	8.0	5.9	3.0	B435*4A9687M00#
680	40 × 60	140	190	150	7.5	5.6	2.8	B435*4C9687M00#
680	45 × 50	140	190	150	7.0	5.2	2.6	B43514E9687M00#
820	40 × 70	110	160	130	8.7	6.5	3.2	B435*4A9827M00#
820	45 × 60	110	160	130	8.2	6.1	3.1	B43514C9827M00#
1000	35 × 100	90	130	110	10.6	7.9	4.0	B435*4A9108M00#
1000	40 × 80	90	130	110	10.1	7.5	3.8	B435*4C9108M00#
1000	45 × 70	90	130	110	9.6	7.2	3.6	B43514E9108M00#
1500	45 × 100	60	90	70	13.6	10.0	5.1	B43514A9158M00#

Capacitors with solder pins are only available in 35 and 40 mm case diameters.

### Composition of ordering code

\* = Terminal type


1 = 4-pin snap-in terminals

2 = solder pin

# = Terminal style

0 = solder pin and 4-pin snap-in standard terminals (6.3 ±1) mm

7 = 4-pin snap-in short terminals (4.5 –1) mm



**B43514, B43524**

**Extended temperature range – 105 °C**

### Technical data and ordering codes

$C_R$	Case dimensions	$ESR_{typ}$	$ESR_{max}$	$Z_{max}$	$I_{AC,max}$	$I_{AC,max}$	$I_{AC,R}$	Ordering code
100 Hz	d × l	100 Hz	100 Hz	10 kHz	100 Hz	100 Hz	100 Hz	(composition see below)
20 °C	mm	20 °C	20 °C	20 °C	60 °C	85 °C	105 °C	
μF		mΩ	mΩ	mΩ	A	A	A	
<b><math>V_R = 420 \text{ V DC}</math></b>								
390	35 × 50	390	520	410	5.3	4.0	2.0	B435*4A0397M00#
390	40 × 40	390	520	410	5.2	3.9	1.9	B435*4C0397M00#
470	35 × 60	320	430	340	6.3	4.7	2.3	B435*4A0477M00#
470	40 × 50	320	430	340	6.2	4.6	2.3	B435*4C0477M00#
560	35 × 70	270	360	290	6.8	5.1	2.5	B435*4A0567M00#
560	40 × 50	270	360	290	6.3	4.7	2.4	B435*4C0567M00#
680	35 × 80	230	300	240	8.0	5.9	3.0	B435*4A0687M00#
680	40 × 60	230	300	240	7.5	5.6	2.8	B435*4C0687M00#
680	45 × 50	230	300	240	7.0	5.2	2.6	B43514E0687M00#
820	40 × 70	190	250	200	8.7	6.5	3.2	B435*4A0827M00#
820	45 × 60	190	250	200	8.2	6.1	3.1	B43514C0827M00#
1000	40 × 80	160	200	160	10.1	7.5	3.8	B435*4A0108M00#
1000	45 × 70	160	200	160	9.6	7.2	3.6	B43514C0108M00#
1500	45 × 100	110	140	110	13.6	10.0	5.0	B43514A0158M00#
<b><math>V_R = 450 \text{ V DC}</math></b>								
330	35 × 50	460	610	490	4.9	3.7	1.8	B435*4A5337M00#
330	40 × 40	460	610	490	4.8	3.6	1.8	B435*4C5337M00#
390	35 × 60	390	520	410	5.7	4.3	2.1	B435*4A5397M00#
390	40 × 50	390	520	410	5.6	4.2	2.1	B435*4C5397M00#
470	35 × 70	320	430	340	6.3	4.7	2.3	B435*4A5477M00#
470	40 × 60	320	430	340	6.2	4.6	2.3	B435*4C5477M00#
470	45 × 50	320	430	340	5.8	4.4	2.2	B43514E5477M00#
560	35 × 80	270	360	290	7.2	5.4	2.7	B435*4A5567M00#
560	40 × 60	270	360	290	6.8	5.1	2.5	B435*4C5567M00#
560	45 × 50	270	360	290	6.4	4.7	2.4	B43514E5567M00#
680	40 × 70	230	300	240	7.9	5.9	3.0	B435*4A5687M00#
680	45 × 60	230	300	240	7.5	5.6	2.8	B43514C5687M00#
1000	40 × 100	160	200	160	11.1	8.3	4.1	B435*4A5108M00#
1000	45 × 80	160	200	160	10.1	7.5	3.8	B43514C5108M00#
1200	45 × 100	130	170	140	12.1	9.0	4.5	B43514A5128M00#

Capacitors with solder pins are only available in 35 and 40 mm case diameters.

### Composition of ordering code

\* = Terminal type

1 = 4-pin snap-in terminals


2 = solder pin

# = Terminal style

0 = solder pin and 4-pin snap-in standard terminals (6.3 ±1) mm


7 = 4-pin snap-in short terminals (4.5 –1) mm






## Useful life

depending on ambient temperature  $T_A$  under ripple current operating conditions<sup>1)</sup>




## Frequency factor of permissible ripple current $I_{AC}$ versus frequency $f$




## Frequency characteristics of ESR

Typical behavior



<sup>1)</sup> Refer to chapter "General technical information, 5.3 Calculation of useful life" on how to interpret the useful life graphs.





**B43514, B43524**

**Extended temperature range – 105 °C**

## Impedance $Z$ versus frequency $f$

Typical behavior at 20 °C





## Cautions and warnings


### Personal safety

The electrolytes used by EPCOS have not only been optimized with a view to the intended application, but also with regard to health and environmental compatibility. They do not contain any solvents that are detrimental to health, e.g. dimethyl formamide (DMF) or dimethyl acetamide (DMAC).

Furthermore, part of the high-voltage electrolytes used by EPCOS are self-extinguishing. They contain flame-retarding substances which will quickly extinguish any flame that may have been ignited.

As far as possible, EPCOS does not use any dangerous chemicals or compounds to produce operating electrolytes. However, in exceptional cases, such materials must be used in order to achieve specific physical and electrical properties because no safe substitute materials are currently known. However, the amount of dangerous materials used in our products has been limited to an absolute minimum. Nevertheless, the following rules should be observed when handling Al electrolytic capacitors:

- Any escaping electrolyte should not come into contact with eyes or skin.
- If electrolyte does come into contact with the skin, wash the affected parts immediately with running water. If the eyes are affected, rinse them for 10 minutes with plenty of water. If symptoms persist, seek medical treatment.
- Avoid breathing in electrolyte vapor or mists. Workplaces and other affected areas should be well ventilated. Clothing that has been contaminated by electrolyte must be changed and rinsed in water.




**B43514, B43524**

**Extended temperature range – 105 °C**

## Product safety

The table below summarize the safety instructions that must be observed without fail. A detailed description can be found in the relevant sections of chapter "General technical information".

Topic	Safety information	Reference Chapter "General technical information"
Polarity	Make sure that polar capacitors are connected with the right polarity.	1 "Basic construction of aluminum electrolytic capacitors"
Reverse voltage	Voltages polarity classes should be prevented by connecting a diode.	3.1.6 "Reverse voltage"
Upper category temperature	Do not exceed the upper category temperatur.	7.2 "Maximum permissible operating temperature"
Maintenance	Make periodic inspections of the capacitors. Before the inspection, make sure that the power supply is turned off and carefully discharge the electricity of the capacitors. Do not apply any mechanical stress to the capacitor terminals.	10 "Maintenance"
Mounting position of screw terminal capacitors	Do not mount the capacitor with the terminals (safety vent) upside down.	11.1. "Mounting positions of capacitors with screw terminals"
Mounting of single-ended capacitors	The internal structure of single-ended capacitors might be damaged if excessive force is applied to the lead wires. Avoid any compressive, tensile or flexural stress. Do not move the capacitor after soldering to PC board. Do not pick up the PC board by the soldered capacitor. Do not insert the capacitor on the PC board with a hole space different to the lead space specified.	11.4 "Mounting considerations for single-ended capacitors"
Robustness of terminals	The following maximum tightening torques must not be exceeded when connecting screw terminals: M5: 2 Nm M6: 2.5 Nm	11.3 "Mounting torques"
Soldering	Do not exceed the specified time or temperature limits during soldering.	11.5 "Soldering"



Topic	Safety information	Reference Chapter "General technical information"
Soldering, cleaning agents	Do not allow halogenated hydrocarbons to come into contact with aluminum electrolytic capacitors.	11.6 "Cleaning agents"
Passive flammability	Avoid external energy, such as fire or electricity.	8.1 "Passive flammability"
Active flammability	Avoid overload of the capacitors.	8.2 "Active flammability"
		Reference Chapter "Capacitors with screw terminals"
Breakdown strength of insulating sleeves	Do not damage the insulating sleeve, especially when ring clips are used for mounting.	"Screw terminals - accessories"

## Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of passive electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of a passive electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of a passive electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as “hazardous”)**. Useful information on this will be found in our Material Data Sheets on the Internet ([www.epcos.com/material](http://www.epcos.com/material)). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the “General Terms of Delivery for Products and Services in the Electrical Industry” published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, EPCOS-JONES, BAOKE, Alu-X, CeraDiode, CSSP, MLSC, PhaseCap, PhaseMod, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMID, SIOV, SIP5D, SIP5K, UltraCap, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at [www.epcos.com/trademarks](http://www.epcos.com/trademarks).