



## Product Status Information

HL63391DG/392DG are Not Recommended for New Design (NRND) status. Please refer to successor product below for new designs and adoptions.

NRND Product	Successor Product
HL63391DG	HL63641DG
<a href="https://www.ushio.co.jp/jp/products/product_file/file/UIE_DS_HL63391DG.pdf">https://www.ushio.co.jp/jp/products/product_file/file/UIE_DS_HL63391DG.pdf</a>	<a href="https://www.ushio.co.jp/jp/products/product_file/file/UIE_DS_HL63641DG.pdf">https://www.ushio.co.jp/jp/products/product_file/file/UIE_DS_HL63641DG.pdf</a>

NRND Product	Successor Product
HL63392DG	HL63642DG
<a href="https://www.ushio.co.jp/jp/products/product_file/file/UIE_DS_HL63392DG.pdf">https://www.ushio.co.jp/jp/products/product_file/file/UIE_DS_HL63392DG.pdf</a>	<a href="https://www.ushio.co.jp/jp/products/product_file/file/UIE_DS_HL63642DG.pdf">https://www.ushio.co.jp/jp/products/product_file/file/UIE_DS_HL63642DG.pdf</a>

For the “Product Life Cycle” definition, please refer to below link.

Japanese; <https://www.ushio.co.jp/jp/laser/news/500958.html>


English; <https://www.ushio.co.jp/en/laser/news/500958.html>

## HL63391DG/392DG

639nm/200mW/Built-in monitor PD



AlGaInP Laser Diode

### Outline



(Unit: mm)

### Internal Circuit



### Features

- Shorter wavelength: 639nm Typ.
- High optical output power: 200mW
- Built in monitor PD
- Operating temperature: +60°C
- Small package:  $\phi 5.6\text{mm}$
- Single transverse mode
- TE mode oscillation

### Application


- Laser module
- Leveler
- Measurement
- Medical
- Light source of optical equipment

### Absolute Maximum Ratings (Tc=25°C)

Item	Symbol	Ratings	Unit
Optical output power (1) (Tc=25 °C) <sup>Note2)</sup>	Po(1)	200	mW
Optical output power (2) (Tc=60 °C) <sup>Note2)</sup>	Po(2)	120	mW
LD Reverse Voltage	V <sub>R(LD)</sub>	2	V
PD Reverse Voltage	V <sub>R(PD)</sub>	30	V
Operating Temperature <sup>Note1) 2)</sup>	Topr	-10 ~ +60	°C
Storage Temperature	Tstg	-40 ~ +85	°C

Note1) Operating temperature is defined by Case temperature "Tc". High increase in temperature of LD chip itself is expected during operation due to high current density. Thus, without proper heat dissipation, it is observed that no specific output power is achieved or it results to LD degradation. It is advised that sufficient measure of heat dissipation should be taken so that LD's maximum operating temperature is not exceeded during actual operation.







Note2) The relation of optical output power vs operating temperature is based on the following figure.



### Optical and Electrical Characteristics (Tc=25°C)

Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Threshold current	I <sub>th</sub>	-	65	80	mA	-
Operating current	I <sub>op</sub>	-	255	290	mA	Po=200mW
Operating voltage	V <sub>op</sub>	-	2.8	3.3	V	Po=200mW
Beam divergence Parallel to the junction	θ <sub>//</sub>	5	8.5	13	°	Po=200mW, FWHM
Beam divergence Perpendicular to the junction	θ <sub>⊥</sub>	10	14	18	°	Po=200mW, FWHM
Lasing Wavelength	λ <sub>p</sub>	633	639	643	nm	Po=200mW
Monitor Current	I <sub>s</sub>	0.4	0.8	1.3	mA	Po=200mW, V <sub>R(PD)</sub> =5V

## Typical Characteristic Curves



## Cautions

1. Ushio Inc. (Ushio) neither warrants nor grants licenses of any our lights or any third party's patent, copyright, trademark, or other intellectual property rights for information contained in this document, Ushio bears no responsibility for problems that may arise with third party's right, including intellectual property rights, in connection with use of the information contained in this document.
2. Products and product specifications may be subject to change without notice. Confirm that you have received the latest product standards or specifications before final design, purchase or use.
3. Ushio makes every attempt to ensure that its products are of high quality and reliability. However, contact our sales office before using the product in an application that demands especially high quality and reliability or where its failure or malfunction may directly threaten human life or cause risk of bodily injury, such as aerospace, aeronautics, nuclear power, combustion control, transportation, traffic safety equipment or medical equipment for life support.
4. Design your application so that the products is used within the ranges guaranteed by Ushio. Particularly for maximum rating, operating supply voltage range, heat radiation characteristics, installation conditions and other characteristics. Ushio bears no responsibility for failure or damage when used beyond the guaranteed ranges. Even within the guaranteed ranges, consider normally foreseeable failure rates or failure modes in semiconductor devices and employ systemic measures such as fail-safes, so that the equipment incorporating Ushio product does not cause bodily injury, fire or other consequential damage due to operation of the Ushio product.
5. This product is not designed to be radiation resistant.
6. No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without written approval from Ushio.
7. Contact our sales office for any questions regarding this document or Ushio products.

1. The laser light is harmful to human body especially to eye no matter what directly or indirectly. The laser beam shall be observed or adjusted through infrared camera or equivalent.
2. This product (without violet laser diode) contains gallium arsenide (GaAs), which may seriously endanger your health even at very low doses. Please avoid treatment which may create GaAs powder or gas, such as disassembly or performing chemical experiments, when you handle the product. When disposing of the product, please follow the laws of your country and separate it from other waste such as industrial waste and household garbage.

## Important Notice

Performance figures, data and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by Ushio before they become applicable to any particular order or contract. In accordance with the Ushio policy of continuous improvement specifications may change without notice. Further details are available from any Ushio sales representative.



Caution - use of controls or adjustments or performance of procedures other than those specified herein may result in hazardous radiation exposure.

## Disclaimer

Product specifications and data shown in this product catalog are subject to change without notice for the purposes of improving product performance, reliability, design, or otherwise.

Product data and parameters in this catalog are typical values based on reasonably up-to-date measurements.

Product data and parameters may vary by user application and over time.

Products shown in this catalog are intended to be used for general electronic equipment. Products are not guaranteed for applications where product malfunction or failure may cause personal injury or death, including but not limited to life-supporting / saving devices, medical devices, safety devices, airplanes, aerospace equipment, automobiles, traffic control systems, and nuclear reactor control systems.