


DOT DENOTES LED COLOR



- NOTE:
- ALL DIMENSIONS IN MM [INCH]
 - GENERAL TOLERANCE: X.X = ± 0.4
X.XX = ± 0.25
 - TERMINAL NOS. FOR REF. ONLY
 - FUNCTION: DPDT
 - RATING: 2A @ 48VDC
 - CONTACT RESISTANCE: 50mΩ MAX. @ 1A 12VDC
 - INSULATION RESISTANCE: 1,000MΩ @ 500VDC
 - DIELECTRIC STRENGTH: 2,000VAC MIN. FOR 1 MINUTE
 - ELECTRICAL LIFE: 50,000 CYCLES
 - OPERATING TEMPERATURE: -20°C TO 55°C
 - INGRESS PROTECTION: IP65
 - SUPPLIED HARDWARE: O-RING AND HEXNUT
 - ▲ DENOTES CRITICAL PARAMETER
 - ILLUMINATION VOLTAGE: 1.8V (FORWARD), 1.8V (REVERSE)



OBJECT ID
100101534

| | | | | |
|-----|--------|----------------|----------|-----|
| B | 24607 | HOUSING UPDATE | 11/23/20 | JM |
| A | 23525 | NEW RELEASE | 8/13/18 | MJR |
| REV | PCR NO | DESCRIPTION | DATE | BY |

| | | | | |
|----------------------|----------------|--------|----------------------|-------|
| TITLE PV10F2V0SS-311 | | | | |
| SCALE 2:3 | DATE 8/13/2018 | DR MJR | DWG 52-PV10F2V0SS311 | REV B |

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED