

# FP1008L

## High frequency, high current power inductors



### Description

- High current carrying capacity
- Low DCR
- Low core loss
- Controlled DCR for sensing circuits
- Inductance range from 100nH to 150nH
- Current range from 50 to 75 amps
- 9.6 x 6.4mm footprint surface mount package in an 8.0mm height
- Ferrite core material
- Halogen free, lead free, RoHS compliant

### Applications

- Servers
- Multi-phase and Vcore regulators
- Voltage Regulator Modules (VRMs)
- Desktop VRMs and EVRDs
- Data networking and storage systems
- Graphics cards and battery power systems
- Point-of-Load modules
- DCR Sensing circuits

### Environmental Data

- Storage temperature range (Component): -40°C to +125°C
- Operating temperature range: -40°C to +125°C (ambient + self-temperature rise)
- Solder reflow temperature: J-STD-020D compliant







## Product Specifications

Part Number <sup>a</sup>	OCL <sup>1</sup> (nH) ±10%	FLL <sup>2</sup> (nH) minimum	I <sub>rms</sub> <sup>3</sup> (amps)	I <sub>sat</sub> <sup>14</sup> (amps)	I <sub>sat</sub> <sup>25</sup> (amps)	I <sub>sat</sub> <sup>36</sup> (amps)	DCR (mΩ) ±5% @ 20°C	K-factor <sup>7</sup>
<b>L1 Version</b>								
FP1008L1-R100-R	100	72	65	75	65	63	0.17	461
FP1008L1-R150-R	150	108	65	50	44	42	0.17	461

1. Open Circuit Inductance (OCL) Test Parameters: 100kHz, 0.1Vrms, 0.0Adc, @ +25°C
2. Full Load Inductance (FLL) Test Parameters: 100kHz, 0.1Vrms, @ I<sub>sat</sub><sup>1</sup>, @ +25°C
3. I<sub>rms</sub>: DC current for an approximate temperature rise of 40°C without core loss. Derating is necessary for AC currents. PCB layout, trace thickness and width, air-flow, and proximity of other heat generating components will affect the temperature rise. It is recommended that the temperature of the part not exceed 125°C under worst case operating conditions verified in the end application.


4. I<sub>sat</sub><sup>1</sup>: Peak current for approximately 20% rolloff @ +25°C
5. I<sub>sat</sub><sup>2</sup>: Peak current for approximately 20% rolloff @ +100°C
6. I<sub>sat</sub><sup>3</sup>: Peak current for approximately 20% rolloff @ +125°C
7. K-factor: Used to determine B<sub>p-p</sub> for core loss (see graph). B<sub>p-p</sub> = K \* L \* ΔI \* 10<sup>-3</sup> B<sub>p-p</sub> (Gauss),  
K: (K-factor from table), L: (Inductance in nH), ΔI (Peak to peak ripple current in Amps).
8. Part Number Definition: FP1008Lx-Rxxx-R  
FP1008L = Product code and size  
x = Version indicator  
Rxxx = inductance value in μH, R = decimal point ,  
-R suffix = RoHS compliant

## Dimensions (mm)



## Recommended Pad Layout


## Schematic




Part marking: 1008Lx (x = Version indicator), Rxxx = Inductance value in uH (R = decimal point)  
wwlyy = date code, R = revision level  
All soldering surfaces to be coplanar within 0.1 millimeters  
PCB tolerances are ±0.1 millimeters unless stated otherwise  
DCR measured from point "a" to point "b"  
Do not route traces or vias underneath the inductor

### Packaging information (mm)


Supplied in tape and reel packaging, 600 parts per 13" diameter reel





### Temperature rise vs. total loss



Core loss vs. B<sub>p-p</sub>



Inductance characteristics



## Solder reflow profile




Table 1 - Standard SnPb Solder ( $T_C$ )

Package Thickness	Volume mm <sup>3</sup> <350	Volume mm <sup>3</sup> ≥350
<2.5mm)	235°C	220°C
≥2.5mm	220°C	220°C

Table 2 - Lead (Pb) Free Solder ( $T_C$ )

Package Thickness	Volume mm <sup>3</sup> <350	Volume mm <sup>3</sup> 350 - 2000	Volume mm <sup>3</sup> >2000
<1.6mm	260°C	260°C	260°C
1.6 – 2.5mm	260°C	250°C	245°C
>2.5mm	250°C	245°C	245°C

## Reference JEDEC J-STD-020D

Profile Feature	Standard SnPb Solder	Lead (Pb) Free Solder
Preheat and Soak		
• Temperature min. ( $T_{smin}$ )	100°C	150°C
• Temperature max. ( $T_{smax}$ )	150°C	200°C
• Time ( $T_{smin}$ to $T_{smax}$ ) ( $t_s$ )	60-120 Seconds	60-120 Seconds
Average ramp up rate $T_{smax}$ to $T_p$	3°C/ Second Max.	3°C/ Second Max.
Liquidous temperature ( $T_L$ )	183°C	217°C
Time at liquidous ( $t_L$ )	60-150 Seconds	60-150 Seconds
Peak package body temperature ( $T_p$ )*	Table 1	Table 2
Time ( $t_p$ )** within 5 °C of the specified classification temperature ( $T_C$ )	20 Seconds**	30 Seconds**
Average ramp-down rate ( $T_p$ to $T_{smax}$ )	6°C/ Second Max.	6°C/ Second Max.
Time 25°C to Peak Temperature	6 Minutes Max.	8 Minutes Max.

\* Tolerance for peak profile temperature ( $T_p$ ) is defined as a supplier minimum and a user maximum.

\*\* Tolerance for time at peak profile temperature ( $t_p$ ) is defined as a supplier minimum and a user maximum.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

**Eaton**  
**Electronics Division**  
1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
www.eaton.com/elx

© 2015 Eaton  
All Rights Reserved  
Printed in USA  
Publication No. 10450 BU-MC15032  
October 2015