Specifications



Photo is representative

Eaton HLS-04-SL

Eaton Bussmann series HLS fuse holder, 0.135 inches short leads, No flanges, 125 Vac, 60 Vdc, 15 A, Four-pole, Tin-plated bifurcated copper terminal

General specifications	
PRODUCT NAME	Eaton Bussmann series HLS fuse holder
CATALOG NUMBER	HLS-04-SL
UPC	051712169936
PRODUCT LENGTH/DEPTH	0.001 in
PRODUCT HEIGHT	0.001 in
PRODUCT WIDTH	0.001 in
PRODUCT WEIGHT	5.5 lb
WARRANTY	Not Applicable
COMPLIANCES	CE Marked RoHS Compliant

Powering Business Worldwide

Electrical rating	
AMPERAGE RATING	15 A

Physical details	
MATERIAL	Tin-plated bifurcated copper

VOLTAGE RATING	125 Vac, 60 Vdc

	terminal
NUMBER OF POLES	Four-pole

General information

SPECIAL FEATURES	0.135 in short leads, No flanges
USED WITH	Used with GMT Type Indicating Series

Resources

CATALOGS	Bussmann series complete full line catalog no. 1007
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - HLS-04-SL
TECHNICAL DATA SHEETS	Bussmann series HLS, HLT, PCT indicating fuse holder data sheet no. 5010 HLS-04-SL~SHORT LEAD MULTIPOLE
TECHNICAL SERVICE BULLETINS	Datasheet - FNQ-30

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.