

Eaton XTCF032C10TD

Catalog Number: XTCF032C10TD

Eaton XT IEC contactor, 32A, 24-27 Vdc, 1NO, 32A, Frame C, 45 mm, 7.5, 7.5, 10, 15 hp (3PH @200, 230, 460, 575 V), Four-pole, Non-reversing, XT IEC series, Screw terminals, Full voltage non-reversing contactor

General specifications



Product Name

Eaton XT IEC contactor

Catalog Number

XTCF032C10TD

EAN

4015081093830

Product Length/Depth

5.43307087 in

Product Height

3.34645669 in

Product Width

2.28346457 in

Product Weight

0.61729433 lb

Compliances

CE Marked
RoHS Compliant

Certifications

UL Listed
CSA Certified
IEC 60947
EN 60947

Catalog Notes

Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)

Product specifications

Amperage Rating

32A

HP rating - max

7.5, 7.5, 10, 15 hp (3PH @200,230,460,575 V)

Number Of Poles

Four-pole

Type

Full voltage non-reversing contactor

Frame size

45 mm

Terminals

Screw terminals

Coil voltage

24-27 Vdc

Contact configuration

1 NO

Continuous ampere rating

32 A

Series

XT IEC

Operation

Non-reversing

Resources

Drawings

[XTCF_C 2D PDF](#)

[XTCF_C AutoCAD 2D Footprint \(mm\)](#)

[XTCF_C 2D Drawing Xchange](#)

[XTCF_C 3D Inventor](#)

[XTCF_C 3D Model Xchange](#)

[XTCF_C AutoCAD 2D Footprint](#)

Specifications and datasheets

[Global Data Sheet - XTCF032C10TD](#)

[Eaton Specification Sheet - XTCF032C10TD](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia