Specifications



Photo is representative



Eaton SD7030-471-R

Eaton SD7030 inductor, 460 uH, 0.34 A Irms, 0.25 A ISAT, 2600 mΩ resistance, SMT mounting, Ferrite, 2-pins, 1500 qty.

General specifications	
PRODUCT NAME	Eaton SD7030 inductor
CATALOG NUMBER	SD7030-471-R
UPC	051712535908
PRODUCT LENGTH/DEPTH	7 mm
PRODUCT HEIGHT	3 mm
PRODUCT WIDTH	7 mm
PRODUCT WEIGHT	0.0013 lb
COMPLIANCES	RoHS Compliant

Powering Business Worldwide

Product specifications

TYPE	Inductor
MOUNTING	SMT
IRMS	0.34 A
ISAT	0.25 A
PACKAGE QUANTITY	1500
MATERIAL	Ferrite
FREQUENCY RATING	Up to 1 MHz
CONTACT CONFIGURATION	Two-pin
TEMPERATURE RATING	-40 to 125 °C
RESISTANCE	2600 mΩ
SERIES	SD7030

Resources

SPECIFICATIONS AND DATASHEETS	Eaton SD7030 shielded drum core power inductors data sheet Eaton Specification Sheet - SD7030-471-R

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.