



Fxx^{*1)}S5Gy^{*2)}-0995

e.g. F09S5G1-0995

*1) xx No. of contacts 09, 15, 25 or 37
 *2) y for performance classes 1, 2 or 3
 (contact cycle for G1/G2/G3 = 500/200/50)

xx	A [mm]	B [mm]	C [mm]	*E [mm]	*F [mm]	*G [mm]	*H [mm]	*J [mm]
09	30.8	16.4	25					
15	39.1	24.7	33.3	$\phi 1$			9.4	2.54
25	53	38.5	47.04			10.6		
37	69.3	54.9	63.5					

*PCB hole patterns, ϕE , ϕF , G, H, J on supplement AM0024

No.	St.	Type Description / Material
7	2	Snap-in rivet
6	2	Grounding bracket
5	2	Clinch nut
4	1	Plastic bracket
3	xx	Signal contact
2	1	Shell
1	1	Insulator

Title	
PCB 1.6mm / Brass	fin plated
Brass	fin plated
KW 4-40 / Brass	fin plated
FKW1/4 GS / PC	black
S5 / Brass	G1/G2/G3
Steel	fin plated
PBT (-55°C - +125°C)	white
Surface plating/Colour/Class	

NAME / DATE	SCALE	TITLE
ADENÄNGER 01-08-2005	2:1	D-Sub Miniature Connector
DRAWN		
CHECKED		

REV.	DATE	CH.-NO.	DWG.NO.	REPLACEMENT FOR:
2	09-08-2007	21699	FxxS5Gy-0995	
1				