

A

Jumpers

for 0.6-0.64 mm wire wrap pins and Ø 0.6-0.7 mm

B

C

D

E

F

G

H

I

K

L

M

N

art. no.	no. of contacts	surface	version	grid			
CAB 4 G ...	2	0.1 μm gold	closed	2.54			
CAB 4 Z ...	2	5.0 μm tin	closed	2.54			
CAB 5 05 G ...	2	0.5 μm gold	closed, hole for probe trip	5.08			
CAB 5 10 G ...	2	1.0 μm gold	closed, hole for probe trip	5.08			
CAB 5 Z ...	2	5.0 μm tin	closed, hole for probe trip	5.08			
CAB 6 05 G ...	2	0.5 μm gold	open, suitable for miniature test probes	2.54			
CAB 6 10 G ...	2	1.0 μm gold	open, suitable for miniature test probes	2.54			
CAB 6 Z ...	2	5.0 μm tin	open, suitable for miniature test probes	2.54			
CAB 9 G ...	2	0.1 μm gold	tag, open	2.54			
please indicate: ... colour B = blue G = grey R = red S = black							

Colour "grey" except for CAB 9.

The flexible contacts are shorting two pins. The jumpers can be mounted behind and next to each other.

G 77

Male headers 2.54 SMD
Male headers 2.54 solder
Male headers 2.54 press-fit
Male headers 2.00 SMD

→ G 37 - 42
→ G 8
→ G 51
→ G 61 - 62

Male headers 2.00 solder
Technical data
Special male & female headers
Jump. links 2.00 & 2.54 solder

→ G 56 - 58
→ G 73 - 78
→ G 19
→ G 20