Fox Part Number: FT5HNBPK20.0




HCMOS, CERAMIC, 5.0 x 3.2mm, SMD, TCXO MODEL: T5HN (Formerly FOX924Series)

RoHS / REACH Compliant / Pb Free /


A. Specifications

20.000 MHz
±1.5 PPM Max
±2.5 PPM Max
±0.3 PPM Max
±0.2 PPM Max
-30°C ~ +85°C
-40°C ~ +85°C
3.3V ±5%
6.0 mA Max
0.5V Max
80% V _{DD} Min
15 pF Max
±1 PPM Max
260°C / 10 Seconds
1
Au
62.69 mg

B. Mechanical / Dimensions (mm)



Recommended Solder Pad Layout



Pin Connections

#1 V_C #3 Output #2 GND #4 V_{DD}

NOTE: The above specifications, having been carefully prepared and checked, is believed to be accurate at the time of publication; however, no responsibility is assumed by Fox Electronics for inaccuracies.

Reference / Comments	Title / Description: PRODUCT SPECIFICATIONS			
	Drawing Number: DWG	-101354	Rev:	Size: A
	Part Number: FT5HNBPK20.0			Cage: 61429
	Draftsperson: AR	Approved	i: CR	Date: 10-16-2018
		Page 1 c	of 2	

Fox Part Number: FT5HNBPK20.0




HCMOS, CERAMIC, 5.0 x 3.2mm, SMD, TCXO MODEL: T5HN (Formerly FOX924Series)

RoHS / REACH Compliant / Pb Free /

Tape & Reel Specification

Tape Specifications (millimeters)							
Α	В	С	D	E	F	STD Reel QTY	
Ф1.5	4.0	8.0	5.5	12.0	1.7	1,000	



Reel Specifications (millimeters)						
G	Н	I	J	K	L	M
2.0	Ф13	Ф21	Ф80	Ф254	13.5	2.0

<u>NOTE</u>: The above specifications, having been carefully prepared and checked, is believed to be accurate at the time of publication; however, no responsibility is assumed by Fox Electronics for inaccuracies.

Reference / Comments	Title / Description: PRODUCT SPECIFICATIONS			
	Drawing Number: DWG-	101354	Rev:	Size: A
	Part Number: FT5HNBPK20.0			Cage: 61429
	Draftsperson: AR	Approved	: CR	Date: 10-16-2018
		Page 2 o	f 2	