



HCMOS 2.5x2.0mm SMD Oscillator

O2HS

(former F210, F230, F240 Series)

DATASHEET

- HCMOS Output
- Stabilities to ± 20 PPM
- Temperature Ranges as wide as -40°C to $+85^{\circ}\text{C}$
- Supply Voltages: 1.0V, 1.8V, 2.5V, 3.3V, Variable (1.7 ~ 3.63V)

1.0V ELECTRICAL CHARACTERISTICS

PARAMETERS	MAX (unless otherwise noted)
Frequency Range (F_o)	1.8 ~ 50.0 MHz
Storage Temperature Range (T_{STG})	$-55 \sim +125^{\circ}\text{C}$
Supply Voltage (V_{DD})	1.0V $\pm 5\%$
Input Current (I_{DD})	
1.8 ~ 32.1 MHz	2.5 mA
$>32.1 \sim 50.0$ MHz	3.5 mA
Standby Current	5 μA
Output Symmetry (50% V_{DD})	40% ~ 60%
Rise/Fall Time (20%/80% V_{DD} Levels) (T_R/T_F)	
1.8 ~ 32.1 MHz	5 nS
$>32.1 \sim 50.0$ MHz	3.5 nS
Output Voltage (V_{OL})	20 % V_{DD}
(V_{OH})	80 % V_{DD} Min
Output Load (HCMOS)	15 pF
Start-up Time (T_S)	5 mS
Output Disable Time ¹	250 nS
Output Enable Time ¹	5 mS

ENABLE / DISABLE FUNCTION

Pin1	Output (pin 3)
OPEN ¹	Active
'1' Level $V_{IH} \geq 70\%V_{DD}$	Active
'0' Level $V_{IL} \leq 30\%V_{DD}$	High Z

• Available Options by Stability & Operating Temp for 1.0V

Frequency Stability ²	Operating Temperature ($^{\circ}\text{C}$)	Frequency Range (MHz)
$\pm 100\text{PPM}$	$-10 \sim +70$	1.8 ~ 50.0
$\pm 100\text{PPM}$	$-40 \sim +85$	1.8 ~ 50.0
$\pm 50\text{PPM}$	$-10 \sim +70$	1.8 ~ 50.0
$\pm 50\text{PPM}$	$-40 \sim +85$	1.8 ~ 50.0
$\pm 25\text{PPM}$	$-10 \sim +70$	1.8 ~ 50.0
$\pm 25\text{PPM}$ ³	$-40 \sim +85$	1.8 ~ 50.0
$\pm 20\text{PPM}$ ³	$-10 \sim +70$	1.8 ~ 50.0

¹ An internal pull-up resistor from pin 1 to pin 4 allows active output if pin 1 is left open

² Inclusive of 25°C tolerance, operating temperature range, input voltage change, load change, shock, vibration, reflow, and one-year aging.

³ Inclusive of 25°C tolerance and operating temperature range





HCMOS 2.5x2.0mm SMD Oscillator

O2HS

(former F210, F230, F240 Series)

DATASHEET

1.8V ELECTRICAL CHARACTERISTICS

PARAMETERS	MAX (unless otherwise noted)
Frequency Range (F _O)	1.25 ~ 133.0 MHz
Storage Temperature Range (T _{STG})	-55 ~ +100°C
Supply Voltage (V _{DD})	1.8V±5%
Input Current (I _{DD})	
1.25 ~ 10.0 MHz	2.5 mA
>10.0 ~ 20.0 MHz	3.5 mA
>20.0 ~ 30.0 MHz	4.0 mA
>30.0 ~ 40.0 MHz	4.5 mA
>40.0 ~ 60.0 MHz	6.0 mA
>60.0 ~ 100.0 MHz	10.0 mA
>100.0 ~ 133.0 MHz	20.0 mA
Standby Current	10 uA
Output Symmetry (50% V _{DD})	
1.25 ~ 50.0 MHz	45% ~ 55%
>50.0 MHz	40% ~ 60%
Rise/Fall Time (10%/90% V _{DD} Levels) (T _R /T _F)	10 nS
Output Voltage (V _{OL})	10 % V _{DD}
(V _{OH})	90 % V _{DD} Min
Output Load (HCMOS)	15 pF
Start-up Time (T _S)	10 mS
Output Disable Time ¹	10 uS
Output Enable Time ¹	10 mS

ENABLE / DISABLE FUNCTION

Pin1	Output (pin 3)
OPEN ¹	Active
'1' Level V _{IH} ≥ 70%V _{DD}	Active
'0' Level V _{IL} ≤ 30%V _{DD}	High Z

• Available Options by Stability & Operating Temp for 1.8V

Frequency Stability ²	Operating Temperature (°C)	Frequency Range (MHz)
±100PPM	-10 ~ +70	1.25 ~ 133.0
±100PPM	-40 ~ +85	1.25 ~ 133.0
±50PPM	-10 ~ +70	1.25 ~ 133.0
±50PPM	-40 ~ +85	1.25 ~ 133.0
±25PPM	-10 ~ +70	1.25 ~ 133.0
±25PPM ³	-40 ~ +85	1.25 ~ 133.0

¹ An internal pull-up resistor from pin 1 to pin 4 allows active output if pin 1 is left open

² Inclusive of 25°C tolerance, operating temperature range, input voltage change, load change, shock, vibration, reflow, and one-year aging.

³ Inclusive of 25C tolerance and operating temperature range





HCMOS 2.5x2.0mm SMD Oscillator

O2HS

(former F210, F230, F240 Series)

DATASHEET

2.5V ELECTRICAL CHARACTERISTICS

PARAMETERS	MAX (unless otherwise noted)
Frequency Range (F _O)	1.25 ~ 170.0 MHz
Storage Temperature Range (T _{STG})	-55 ~ +100°C
Supply Voltage (V _{DD})	2.5V±5%
Input Current (I _{DD})	
1.25 ~ 19.999999 MHz	5 mA
20.0 ~ 39.999999 MHz	9 mA
40.0 ~ 50.0 MHz	11 mA
>50.0MHz ~ 170MHz	30 mA
Standby Current	10 uA
Output Symmetry (50% V _{DD})	
1.25 ~ 50.0 MHz	45% ~ 55%
>50.0 MHz	40% ~ 60%
Rise/Fall Time (10%/90% V _{DD} Levels) (T _R /T _F)	10 nS
Output Voltage (V _{OL})	10 % V _{DD}
(V _{OH})	90 % V _{DD} Min
Output Load (HCMOS)	15 pF
Start-up Time (T _S)	10 mS
Output Disable Time ¹	200 nS
Output Enable Time ¹	10 mS

ENABLE / DISABLE FUNCTION ²

Pin1	Output (pin 3)
OPEN ¹	Active
'1' Level V _{IH} ≥ 80%V _{DD}	Active
'0' Level V _{IL} ≤ 20%V _{DD}	High Z

• Available Options by Stability & Operating Temp for 2.5V

Frequency Stability ²	Operating Temperature (°C)	Frequency Range (MHz)
±100PPM	-20 ~ +70	1.25 ~ 170.0
±100PPM	-40 ~ +85	1.25 ~ 170.0
±50PPM	-20 ~ +70	1.25 ~ 170.0
±50PPM	-40 ~ +85	1.25 ~ 170.0
±25PPM	-20 ~ +70	1.25 ~ 170.0
±25PPM ³	-40 ~ +85	1.25 ~ 170.0

¹ An internal pull-up resistor from pin 1 to pin 4 allows active output if pin 1 is left open

² Inclusive of 25°C tolerance, operating temperature range, input voltage change, load change, shock, vibration, reflow, and one-year aging.

³ Inclusive of 25C tolerance and operating temperature range





HCMOS 2.5x2.0mm SMD Oscillator

O2HS

(former F210, F230, F240 Series)

DATASHEET

3.3V ELECTRICAL CHARACTERISTICS

PARAMETERS	MAX (unless otherwise noted)
Frequency Range (F _O)	1.25 ~ 170.0 MHz
Storage Temperature Range (T _{STG})	-55 ~ +100°C
Supply Voltage (V _{DD})	3.3V±5%
Input Current (I _{DD})	
1.25 ~ 19.999999 MHz	7 mA
20.0 ~ 39.999999 MHz	13 mA
40.0 ~ 50.0 MHz	19 mA
>50.0 ~ 170.0 MHz	40 mA
Standby Current	10 uA
Output Symmetry (50% V _{DD})	
1.25 ~ 50.0 MHz	45% ~ 55%
>50.0 MHz	40% ~ 60%
Rise/Fall Time (10%/90% V _{DD} Levels) (T _R /T _F)	10 nS
Output Voltage (V _{OL})	10 % V _{DD}
(V _{OH})	90 % V _{DD} Min
Output Load (HCMOS)	15 pF
Start-up Time (T _S)	10 mS
Output Disable Time ¹	200 nS
Output Enable Time ¹	10 mS

ENABLE / DISABLE FUNCTION ²

Pin1	Output (pin 3)
OPEN ¹	Active
'1' Level V _{IH} ≥ 80%V _{DD}	Active
'0' Level V _{IL} ≤ 20%V _{DD}	High Z

• Available Options by Stability & Operating Temp for 3.3V

Frequency Stability ²	Operating Temperature (°C)	Frequency Range (MHz)
±100PPM	-20 ~ +70	1.25 ~ 170.0
±100PPM	-40 ~ +85	1.25 ~ 170.0
±50PPM	-20 ~ +70	1.25 ~ 170.0
±50PPM	-40 ~ +85	1.25 ~ 170.0
±25PPM	-20 ~ +70	1.25 ~ 170.0
±25PPM ³	-40 ~ +85	1.25 ~ 170.0

¹ An internal pull-up resistor from pin 1 to pin 4 allows active output if pin 1 is left open

² Inclusive of 25°C tolerance, operating temperature range, input voltage change, load change, shock, vibration, reflow, and one-year aging.

³ Inclusive of 25C tolerance and operating temperature range





HCMOS 2.5x2.0mm SMD Oscillator

O2HS

(former F210, F230, F240 Series)

DATASHEET

VARIABLE VOLTAGE ELECTRICAL CHARACTERISTICS

PARAMETERS	MAX (unless otherwise noted)
Frequency Range (F _O)	0.75 ~ 156.25 MHz
Storage Temperature Range (T _{STG})	-55 ~ +125°C
Supply Voltage (V _{DD}) 0.75 ~ 135.0 MHz >135.0 ~ 156.25 MHz	1.7V ~ 3.63V 2.25V ~ 3.63V
Input Current (I _{DD}) 0.75 ~ 19.999 MHz 20.0 ~ 39.999 MHz 40.0 ~ 59.999 MHz 60.0 ~ 84.999 MHz 85.0 ~ 135.0 MHz >135.0 ~ 156.250 MHz	4 mA 6 mA 10 mA 15 mA 30 mA 40 mA
Standby Current	10 uA
Output Symmetry (50% V _{DD}) 0.75 ~ 84.999 MHz 85.0 ~ 156.25 MHz	45% ~55 % 40% ~60 %
Rise/Fall Time (10%/90% V _{DD} Levels) (T _R /T _F)	6 nS
Output Voltage (V _{OL}) (V _{OH})	10 % V _{DD} 90 % V _{DD} Min
Output Load (HCMOS)	15 pF
Start-up Time (T _S)	5 mS
Output Disable Time ¹	200 nS
Output Enable Time ¹	5 mS

ENABLE / DISABLE FUNCTION

Pin1	Output (pin 3)
OPEN ¹	Active
'1' Level V _{IH} ≥ 70%V _{DD}	Active
'0' Level V _{IL} ≤ 30%V _{DD}	High Z

• Available Options by Stability & Operating Temp for Variable Voltage

Frequency Stability ²	Operating Temperature (°C)	Frequency Range (MHz)
±100PPM	-20 ~ +70	0.75 ~ 156.25
±100PPM	-40 ~ +85	0.75 ~ 156.25
±50PPM	-20 ~ +70	0.75 ~ 156.25
±50PPM	-40 ~ +85	0.75 ~ 156.25
±25PPM	-20 ~ +70	0.75 ~ 156.25
±25PPM ³	-40 ~ +85	0.75 ~ 156.25
±20PPM ³	-20 ~ +70	0.75 ~ 156.25

¹ An internal pull-up resistor from pin 1 to pin 4 allows active output if pin 1 is left open

² Inclusive of 25°C tolerance, operating temperature range, input voltage change, load change, shock, vibration, reflow, and one-year aging.

³ Inclusive of 25C tolerance and operating temperature range






HCMOS 2.5x2.0mm SMD Oscillator

O2HS


(former F210, F230, F240 Series)

DATASHEET

DIMENSIONS / MECHANICAL SPECIFICATIONS



Recommended Solder Pad Layout



All dimensions are in millimeters.

Pin Connections

#1	E/D	#3	Output
#2	GND	#4	V _{DD}

Maximum Soldering Temp / Time	260°C / 10 Seconds x 2
Moisture Sensitivity Level (MSL)	1
Termination Finish	Au over Ni
Seal Method	Seam
Lead (Pb) Free	Yes
ROHS/REACH Compliant	Yes

Notes:

*A 0.01μF capacitor should be placed between V_{DD} (Pin 4) and GND (Pin2) to minimize power supply line noise.

*Dimensional drawing is for reference to critical specifications defined by size measurements.

Certain non-critical visual attributes, such as side castellations, reference pin shape, etc. may vary.



Title / Description: O2HS SERIES STANDARD SPECIFICATIONS	
Drawing Number: O2HS-DOC-1	Size: A
Part Number:	Cage: 61429
Draftsperson: MAJ	Approved: BEC
Revision Date: 06/19/2019	



HCMOS 2.5x2.0mm SMD Oscillator

O2HS

(former F210, F230, F240 Series)

DATASHEET

Tape Specifications (millimeters)						Reel Specifications (millimeters)								
A	B	C	D	E	F	Reel Qty		G	H	I	J	K	L	M
Ø1.55	4.0	4.0	3.5	8.0	1.15	-T3 = 3,000 (default) -T1 = 1,000 -T2 = 2,000		2.0	Ø13	Ø21	Ø60	Ø180	9.0	2.0

Available Options & Part Identification*

Example: **F O2HS B B M 25.0**

F	O2HS	B	B	M	25.0
Fox	Model Number	Voltage M = 1.0V±5% K = 1.8V±5% H = 2.5V±5% B = 3.3V±5% V = 1.7 to 3.63V W = 2.25 to 3.63V	Stability A = ±100 PPM B = ±50 PPM D = ±25 PPM E = ±20 PPM	Operating Temperature F = -20 to +70°C M = -40 to +85°C P = -40 to +105°C	Frequency (MHz)

*Not all frequencies in the frequency range, or every combination of stability, temp range, and voltage available. See stabilities and op temps for each V_{DD}.



Corporate Headquarters
5570 Enterprise Parkway
Fort Myers, FL 33905
<http://www.FOXONLINE.com>

Sales
1-888-GET-2-FOX (1-888-438-2369)
or
1-239-693-0099
<http://www.FOXONLINE.com/repdisty>

Tech Support
<http://www.FOXONLINE.com/email>

Product use: Fox Electronics reserves the right to modify the products and/or specifications described herein at any time and at Fox Electronics' sole discretion. All information in this document, including descriptions of product features and performance, is subject to change without notice. Performance specifications and the operating parameters of the described products are determined in the independent state and are not guaranteed to perform the same way when installed in customer products. The information contained herein is provided without representation or warranty of any kind, whether express or implied, including, but not limited to, the suitability of Fox Electronics' products for any particular purpose, an implied warranty of merchantability, or non-infringement of the intellectual property rights of others. This document is presented only as a guide and does not convey any license under intellectual property rights of Fox Electronics or any third parties.

Fox Electronics' products are not intended for use in applications involving extreme environmental conditions or in life support systems or similar devices where the failure or malfunction of a Fox Electronics product can be reasonably expected to significantly affect the health or safety of users. Anyone using a Fox Electronics product in such a manner does so at their own risk, absent an express, written agreement by Fox Electronics.

Fox Electronics and the Fox logo are registered trademarks of Fox Electronics. Product specification is subject to change without notice. Other trademarks and service marks used herein, including protected names, logos and designs, are the property of Fox Electronics or their respective third-party owners.



Title / Description: O2HS SERIES STANDARD SPECIFICATIONS	
Drawing Number: O2HS-DOC-1	Size: A
Part Number:	Cage: 61429
Draftsperson: MAJ	Approved: BEC
Revision Date: 06/19/2019	